



# SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## Intel Corporation

Endeavor (Intel Xeon E7-4890 v2, 2.80 GHz,  
DDR3-1600 MHz, SMT on, Turbo off)

**SPECmpiM\_peak2007 = Not Run**

**SPECmpiM\_base2007 = 14.6**

**MPI2007 license:** 13


**Test sponsor:** Intel Corporation

**Tested by:** Pavel Shelepuhin

**Test date:** Feb-2014

**Hardware Availability:** Feb-2014

**Software Availability:** Dec-2013



## Results Table

Benchmark	Base								Peak							
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	60	152	10.3	<u>151</u>	<u>10.4</u>	151	10.4									
107.leslie3d	60	394	13.3	392	13.3	<u>393</u>	<u>13.3</u>									
113.GemsFDTD	60	323	19.5	<u>323</u>	<u>19.6</u>	322	19.6									
115.fds4	60	181	10.8	<u>180</u>	<u>10.8</u>	180	10.8									
121.pop2	60	275	15.0	271	15.2	<u>273</u>	<u>15.1</u>									
122.tachyon	60	247	11.3	246	11.4	<u>246</u>	<u>11.4</u>									
126.lammps	60	299	9.76	<u>299</u>	<u>9.76</u>	298	9.79									
127.wrf2	60	340	22.9	<u>344</u>	<u>22.7</u>	345	22.6									
128.GAPgeomfem	60	124	16.6	123	16.7	<u>124</u>	<u>16.7</u>									
129.tera_tf	60	<u>256</u>	<u>10.8</u>	255	10.9	256	10.8									

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



# SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## Intel Corporation

Endeavor (Intel Xeon E7-4890 v2, 2.80 GHz,  
DDR3-1600 MHz, SMT on, Turbo off)

[SPECmpIM\\_peak2007 = Not Run](#)

[SPECmpIM\\_base2007 = 14.6](#)

MPI2007 license: 13

Test date: Feb-2014

Test sponsor: Intel Corporation

Hardware Availability: Feb-2014

Tested by: Pavel Shelepuhin

Software Availability: Dec-2013

## Results Table (Continued)

Benchmark	Base								Peak							
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
130.socorro	60	<u>121</u>	<u>31.5</u>	121	31.5	122	31.4									
132.zeusmp2	60	<u>230</u>	<u>13.5</u>	232	13.4	230	13.5									
137.lu	60	230	16.0	<u>230</u>	<u>16.0</u>	228	16.1									

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

### Hardware Summary

Type of System: Homogeneous  
 Compute Node: Endeavor Node  
 Interconnects: IB Switch  
     Gigabit Ethernet  
 File Server Node: NFS  
 Total Compute Nodes: 1  
 Total Chips: 4  
 Total Cores: 60  
 Total Threads: 120  
 Total Memory: 512 GB  
 Base Ranks Run: 60  
 Minimum Peak Ranks: --  
 Maximum Peak Ranks: --

### Software Summary

C Compiler: Intel C++ Composer XE 2013 for Linux, Version 14.0.0.080 Build 20130728  
 C++ Compiler: Intel C++ Composer XE 2013 for Linux, Version 14.0.0.080 Build 20130728  
 Fortran Compiler: Intel Fortran Composer XE 2013 for Linux, Version 14.0.0.080 Build 20130728  
 Base Pointers: 64-bit  
 Peak Pointers: 64-bit  
 MPI Library: Intel MPI Library 4.1.3.045 for Linux  
 Other MPI Info: None  
 Pre-processors: No  
 Other Software: None

## Node Description: Endeavor Node

### Hardware

Number of nodes: 1  
 Uses of the node: compute  
 Vendor: Intel  
 Model: S4TR1SY4Q  
 CPU Name: Intel Xeon E7-4890 v2  
 CPU(s) orderable: 1-4 chips  
 Chips enabled: 4  
 Cores enabled: 60  
 Cores per chip: 15  
 Threads per core: 2  
 CPU Characteristics: Intel Turbo Boost Technology disabled, 8.0 GT/s QPI, Hyper-Threading enabled  
 CPU MHz: 2800  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 38400 KB I+D on chip per chip, 38400 KB shared / 15 cores  
 Other Cache: None  
 Memory: 512 GB (32 x 16 GB 2Rx4 PC3-12800R-11, ECC)  
 Disk Subsystem: 2 x 300 GB SAS HDDs  
 Other Hardware: None  
 Adapter: Intel (ESB2) 82575EB Dual-Port Gigabit Ethernet Controller

### Software

Adapter: Intel (ESB2) 82575EB Dual-Port Gigabit Ethernet Controller  
 Adapter Driver: e1000  
 Adapter Firmware: None  
 Adapter: Mellanox MCX353A-FCAT ConnectX-3 OFED 1.5.3.1  
 Adapter Driver: 2.10.0  
 Operating System: Red Hat EL 6.4, kernel 2.6.32-358  
 Local File System: Linux/ext2  
 Shared File System: NFS  
 System State: Multi-User  
 Other Software: Platform LSF 9.1.1.1

Continued on next page



# SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## Intel Corporation

Endeavor (Intel Xeon E7-4890 v2, 2.80 GHz,  
DDR3-1600 MHz, SMT on, Turbo off)

**SPECmpIM\_peak2007 = Not Run**

**SPECmpIM\_base2007 = 14.6**

**MPI2007 license:** 13

**Test date:** Feb-2014

**Test sponsor:** Intel Corporation

**Hardware Availability:** Feb-2014

**Tested by:** Pavel Shelepuhin

**Software Availability:** Dec-2013

### Node Description: Endeavor Node

Number of Adapters:	1
Slot Type:	PCI-Express x8
Data Rate:	1Gbps Ethernet
Ports Used:	2
Interconnect Type:	Ethernet
Adapter:	Mellanox MCX353A-FCAT ConnectX-3
Number of Adapters:	1
Slot Type:	PCIe x8 Gen3
Data Rate:	InfiniBand 4x FDR
Ports Used:	1
Interconnect Type:	InfiniBand

### Node Description: NFS

Hardware		Software	
Number of nodes:	1	Adapter:	Intel 82563GB Dual-Port Gigabit
Uses of the node:	fileserver	Adapter Driver:	Ethernet Controller
Vendor:	Intel	e1000e	
Model:	S7000FC4UR	Adapter Firmware:	N/A
CPU Name:	Intel Xeon CPU	Operating System:	RedHat EL 5 Update 4
CPU(s) orderable:	1-4 chips	Local File System:	None
Chips enabled:	4	Shared File System:	NFS
Cores enabled:	16	System State:	Multi-User
Cores per chip:	4	Other Software:	None
Threads per core:	2		
CPU Characteristics:	--		
CPU MHZ:	2926		
Primary Cache:	32 KB I + 32 KB D on chip per core		
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores		
L3 Cache:	None		
Other Cache:	None		
Memory:	64 GB		
Disk Subsystem:	8 disks, 500GB/disk, 2.7TB total		
Other Hardware:	None		
Adapter:	Intel 82563GB Dual-Port Gigabit Ethernet Controller		
Number of Adapters:	1		
Slot Type:	PCI-Express x8		
Data Rate:	1Gbps Ethernet		
Ports Used:	1		
Interconnect Type:	Ethernet		



# SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## Intel Corporation

Endeavor (Intel Xeon E7-4890 v2, 2.80 GHz,  
DDR3-1600 MHz, SMT on, Turbo off)

**SPECmpiM\_peak2007 = Not Run**

**SPECmpiM\_base2007 = 14.6**

**MPI2007 license:** 13

**Test date:** Feb-2014

**Test sponsor:** Intel Corporation

**Hardware Availability:** Feb-2014

**Tested by:** Pavel Shelepuhin

**Software Availability:** Dec-2013

### Interconnect Description: IB Switch

<b>Hardware</b>		<b>Software</b>
Vendor:	Mellanox	
Model:	Mellanox MSX6025F-1BFR	
Switch Model:	Mellanox MSX6025F-1BFR	
Number of Switches:	46	
Number of Ports:	36	
Data Rate:	InfiniBand 4x FDR	
Firmware:	7.2.0	
Topology:	Fat tree	
Primary Use:	MPI traffic	

### Interconnect Description: Gigabit Ethernet

<b>Hardware</b>		<b>Software</b>
Vendor:	Force10 Networks	
Model:	Force10 S50, Force10 C300	
Switch Model:	Force10 S50, Force10 C300	
Number of Switches:	15	
Number of Ports:	48	
Data Rate:	1Gbps Ethernet, 10Gbps Ethernet	
Firmware:	8.2.1.0	
Topology:	Fat tree	
Primary Use:	Cluster File System	

### Submit Notes

The config file option 'submit' was used.

### General Notes

130.socorro (base): "nullify\_ptr" src.alt was used.

**MPI startup command:**

mpiexec.hydra command was used to start MPI jobs.

**BIOS settings:**

Intel Hyper-Threading Technology (SMT): Enabled (default is Enabled)  
Intel Turbo Boost Technology (Turbo) : Disabled (default is Enabled)

**RAM configuration:**

Compute nodes have 4x16-GB RDIMM on each memory channel.

**Network:**

Forty six 36-port switches: 18 core switches and 28 leaf switches.  
Each leaf has one link to each core. Remaining 18 ports on 25 of 28 leafs  
are used for compute nodes. On the remaining 3 leafs the ports are used

Continued on next page



# SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## Intel Corporation

Endeavor (Intel Xeon E7-4890 v2, 2.80 GHz,  
DDR3-1600 MHz, SMT on, Turbo off)

**SPECmpIM\_peak2007 = Not Run**

**SPECmpIM\_base2007 = 14.6**

**MPI2007 license:** 13

**Test date:** Feb-2014

**Test sponsor:** Intel Corporation

**Hardware Availability:** Feb-2014

**Tested by:** Pavel Shelepuhin

**Software Availability:** Dec-2013

## General Notes (Continued)

for FS nodes and other peripherals.

**Job placement:**

Each MPI job was assigned to a topologically compact set of nodes, i.e.  
the minimal needed number of leaf switches was used for each job: 1 switch  
for 60/120/240/480 ranks.

Platform LSF was used for job submission. It has no impact on performance.  
Information can be found at: <http://www.platform.com>

## Base Compiler Invocation

C benchmarks:  
  mpicc

C++ benchmarks:

126.lammps: mpiicpc

Fortran benchmarks:  
  mpiifort

Benchmarks using both Fortran and C:  
  mpicc mpiifort

## Base Portability Flags

121.pop2: -DSPEC\_MPI\_CASE\_FLAG  
126.lammps: -DMPICH\_IGNORE\_CXX\_SEEK  
  127.wrf2: -DSPEC\_MPI\_CASE\_FLAG -DSPEC\_MPI\_LINUX  
130.socorro: -assume nostd\_intent\_in

## Base Optimization Flags

C benchmarks:  
  -O3 -xCORE-AVX-I -no-prec-div

C++ benchmarks:

126.lammps: -O3 -xCORE-AVX-I -no-prec-div

Fortran benchmarks:  
  -O3 -xCORE-AVX-I -no-prec-div

Benchmarks using both Fortran and C:  
  -O3 -xCORE-AVX-I -no-prec-div



# SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## Intel Corporation

Endeavor (Intel Xeon E7-4890 v2, 2.80 GHz,  
DDR3-1600 MHz, SMT on, Turbo off)

**SPECmpIM\_peak2007 = Not Run**

**SPECmpIM\_base2007 = 14.6**

**MPI2007 license:** 13

**Test date:** Feb-2014

**Test sponsor:** Intel Corporation

**Hardware Availability:** Feb-2014

**Tested by:** Pavel Shelepuhin

**Software Availability:** Dec-2013

The flags file that was used to format this result can be browsed at

[http://www.spec.org/mpi2007/flags/EM64T\\_Intel140\\_flags.html](http://www.spec.org/mpi2007/flags/EM64T_Intel140_flags.html)

You can also download the XML flags source by saving the following link:

[http://www.spec.org/mpi2007/flags/EM64T\\_Intel140\\_flags.xml](http://www.spec.org/mpi2007/flags/EM64T_Intel140_flags.xml)

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC MPI2007 v2.0.1.

Report generated on Tue Jul 22 13:47:56 2014 by SPEC MPI2007 PS/PDF formatter v1463.

Originally published on 5 March 2014.