# SPEC® MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## SGI

SGI ICE X
(Intel Xeon E5-2690 v3, 2.6 GHz)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 9.83

**MPI2007 license:** 14
**Test sponsor:** SGI
**Tested by:** SGI

**Test date:** Jul-2014
**Hardware Availability:** Sep-2014
**Software Availability:** Apr-2014




## Results Table

| Benchmark | Base | | | | | | | Peak | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Ranks | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Ranks | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 121.pop2 | 192 | 420 | 9.27 | 411 | 9.46 | **412** | **9.44** | | | | | | | |
| 122.tachyon | 192 | 376 | 5.17 | 373 | 5.21 | **375** | **5.18** | | | | | | | |
| 125.RAxML | 192 | 357 | 8.18 | **359** | **8.14** | 359 | 8.13 | | | | | | | |
| 126.lammps | 192 | 366 | 6.72 | 360 | 6.84 | **360** | **6.83** | | | | | | | |
| 128.GAPgeofem | 192 | **456** | **13.0** | 459 | 12.9 | 454 | 13.1 | | | | | | | |
| 129.tera_tf | 192 | 203 | 5.42 | **203** | **5.42** | 203 | 5.41 | | | | | | | |
| 132.zeusmp2 | 192 | **237** | **8.94** | 235 | 9.01 | 237 | 8.93 | | | | | | | |
| 137.lu | 192 | 292 | 14.4 | 291 | 14.4 | **291** | **14.4** | | | | | | | |
| 142.dmilc | 192 | 214 | 17.2 | 214 | 17.2 | **214** | **17.2** | | | | | | | |
| 143.dleslie | 192 | 236 | 13.1 | 234 | 13.3 | **236** | **13.1** | | | | | | | |
| 145.lGemsFDTD | 192 | 368 | 12.0 | **370** | **11.9** | 371 | 11.9 | | | | | | | |
| 147.l2wrf2 | 192 | 674 | 12.2 | 671 | 12.2 | **672** | **12.2** | | | | | | | |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

# SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## SGI

SGI ICE X
(Intel Xeon E5-2690 v3, 2.6 GHz)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 9.83

**MPI2007 license:** 14
**Test sponsor:** SGI
**Tested by:** SGI

**Test date:** Jul-2014
**Hardware Availability:** Sep-2014
**Software Availability:** Apr-2014

### Hardware Summary

| | |
|---|---|
| Type of System: | Homogeneous |
| Compute Node: | SGI ICE X IP-131 Compute Node |
| Interconnect: | InfiniBand (MPI and I/O) |
| File Server Node: | SGI Rackable C1103-TY12 |
| Total Compute Nodes: | 8 |
| Total Chips: | 16 |
| Total Cores: | 192 |
| Total Threads: | 192 |
| Total Memory: | 1 TB |
| Base Ranks Run: | 192 |
| Minimum Peak Ranks: | -- |
| Maximum Peak Ranks: | -- |

### Software Summary

| | |
|---|---|
| C Compiler: | Intel C++ Composer XE 2013 for Linux, Version 14.0.3.174 Build 20140422 |
| C++ Compiler: | Intel C++ Composer XE 2013 for Linux Version 14.0.3.174 Build 20140422 |
| Fortran Compiler: | Intel Fortran Composer XE 2013 for Linux, Version 14.0.3.174 Build 20140422 |
| Base Pointers: | 64-bit |
| Peak Pointers: | Not Applicable |
| MPI Library: | SGI MPT 2.09 Patch 11049 |
| Other MPI Info: | OFED 1.5.4 |
| Pre-processors: | None |
| Other Software: | None |

## Node Description: SGI ICE X IP-131 Compute Node

### Hardware

| | |
|---|---|
| Number of nodes: | 8 |
| Uses of the node: | compute |
| Vendor: | SGI |
| Model: | SGI ICE X (Intel Xeon E5-2690 v3, 2.6 GHz) |
| CPU Name: | Intel Xeon E5-2690 v3 |
| CPU(s) orderable: | 1-2 chips |
| Chips enabled: | 2 |
| Cores enabled: | 24 |
| Cores per chip: | 12 |
| Threads per core: | 1 |
| CPU Characteristics: | 12 Core, 2.60 GHz, 9.6 GT/s QPI<br>Intel Turbo Boost Technology up to 3.50 GHz<br>Hyper-Threading Technology disabled |
| CPU MHz: | 2600 |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 256 KB I+D on chip per core |
| L3 Cache: | 30 MB I+D on chip per chip |
| Other Cache: | None |
| Memory: | 128 GB (8 x 16 GB 2Rx4 PC4-17000R-15, ECC) |
| Disk Subsystem: | None |
| Other Hardware: | None |
| Adapter: | Mellanox MT27500 with ConnectX-3 ASIC (PCIe x8 Gen3 8 GT/s) |
| Number of Adapters: | 2 |
| Slot Type: | PCIe x8 Gen3 |
| Data Rate: | InfiniBand 4x FDR |
| Ports Used: | 2 |
| Interconnect Type: | InfiniBand |

### Software

| | |
|---|---|
| Adapter: | Mellanox MT27500 with ConnectX-3 ASIC (PCIe x8 Gen3 8 GT/s) |
| Adapter Driver: | OFED-1.5.4 |
| Adapter Firmware: | 2.30.3000 |
| Operating System: | SUSE Linux Enterprise Server 11 SP3 (x86_64), Kernel 3.0.93-0.8-default |
| Local File System: | NFSv3 |
| Shared File System: | NFSv3 IPoIB |
| System State: | Multi-user, run level 3 |
| Other Software: | SGI Tempo Service Node 2.8.1, Build 709rp49.sles11sp3-1402182002 |

# SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## SGI

SGI ICE X
(Intel Xeon E5-2690 v3, 2.6 GHz)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 9.83

**MPI2007 license:** 14
**Test sponsor:** SGI
**Tested by:** SGI

**Test date:** Jul-2014
**Hardware Availability:** Sep-2014
**Software Availability:** Apr-2014

## Node Description: SGI Rackable C1103-TY12

### Hardware

| | |
|---|---|
| Number of nodes: | 1 |
| Uses of the node: | fileserver |
| Vendor: | SGI |
| Model: | SGI Rackable C1103-TY12 (Intel Xeon X5670, 2.93 GHz) |
| CPU Name: | Intel Xeon X5670 |
| CPU(s) orderable: | 1-2 chips |
| Chips enabled: | 2 |
| Cores enabled: | 12 |
| Cores per chip: | 6 |
| Threads per core: | 2 |
| CPU Characteristics: | Intel Turbo Boost Technology up to 3.33 GHz Hyper-Threading Technology enabled |
| CPU MHz: | 2933 |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 256 KB I+D on chip per chip |
| L3 Cache: | 12 MB I+D on chip per chip |
| Other Cache: | None |
| Memory: | 96 GB (12 * 8 GB 2Rx4 PC3-10600R-9, ECC) |
| Disk Subsystem: | 12 TB RAID 6<br>12 x 1 TB SATA (Seagate Constellation, 7200RPM) |
| Other Hardware: | None |
| Adapter: | Mellanox MT27500 with ConnectX-3 ASIC (PCIe x8 Gen3 8 GT/s) |
| Number of Adapters: | 2 |
| Slot Type: | PCIe x8 Gen3 |
| Data Rate: | InfiniBand 4x FDR |
| Ports Used: | 2 |
| Interconnect Type: | InfiniBand |

### Software

| | |
|---|---|
| Adapter: | Mellanox MT27500 with ConnectX-3 ASIC (PCIe x8 Gen3 8 GT/s) |
| Adapter Driver: | OFED-1.5.2 |
| Adapter Firmware: | 2.30.3000 |
| Operating System: | SUSE Linux Enterprise Server 11 SP1 (x86_64), Kernel 2.6.32.46-0.3-default |
| Local File System: | xfs |
| Shared File System: | -- |
| System State: | Multi-user, run level 3 |
| Other Software: | SGI Foundation Software 2.5, Build 705r10.sles11-1110192111 |

## Interconnect Description: InfiniBand (MPI and I/O)

### Hardware

| | |
|---|---|
| Vendor: | Mellanox Technologies and SGI |
| Model: | None |
| Switch Model: | SGI FDR Integrated IB Switch Blade 2SW9x27 with Mellanox SwitchX device 51000 |
| Number of Switches: | 2 |
| Number of Ports: | 36 |
| Data Rate: | InfiniBand 4x FDR |
| Firmware: | 09.02.3000 |
| Topology: | Enhanced Hypercube |
| Primary Use: | MPI and I/O traffic |

### Software

## Submit Notes

```
The config file option 'submit' was used.
```

## General Notes

```
Software environment:
  export MPI_REQUEST_MAX=65536
  export MPI_TYPE_MAX=32768
  export MPI_IB_RAILS=2
  ulimit -s unlimited

BIOS settings:
  AMI BIOS version DY2E6044
  Hyper-Threading Technology disabled
  Intel Turbo Boost Technology enabled (default)
  Intel Turbo Boost Technology activated with
    modprobe acpi_cpufreq
    cpupower frequency-set -u 2601MHz -d 2601MHz -g performance

Job Placement:
  Each MPI job was assigned to a topologically compact set
  of nodes, i.e. the minimal needed number of switches was
  used for each job: 2 switches for up to 192 ranks,
  4 switches for up to 384 ranks, 8 switches for 768 ranks,
  and 16 switches for 1536 ranks.

Additional notes regarding interconnect:
  The Infiniband network consists of two independent planes,
  with half the switches in the system allocated to each plane.
  I/O traffic is restricted to one plane, while MPI traffic can
  use both planes.
```

# Base Compiler Invocation

C benchmarks:
`icc`

C++ benchmarks:

126.lammps: `icpc`

Fortran benchmarks:
`ifort`

Benchmarks using both Fortran and C:
`icc ifort`

## Base Portability Flags

121.pop2: `-DSPEC_MPI_CASE_FLAG`

## Base Optimization Flags

C benchmarks:
`-O3 -xCORE-AVX2 -no-prec-div`

C++ benchmarks:

126.lammps: `-O3 -xCORE-AVX2 -no-prec-div -ansi-alias`

Fortran benchmarks:
`-O3 -xCORE-AVX2 -no-prec-div`

Benchmarks using both Fortran and C:
`-O3 -xCORE-AVX2 -no-prec-div`

## Base Other Flags

C benchmarks:
`-lmpi`

C++ benchmarks:

126.lammps: `-lmpi`

Fortran benchmarks:
`-lmpi`

Benchmarks using both Fortran and C:
`-lmpi`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/mpi2007/flags/SGI_x86_64_Intel14_flags.20140908.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/mpi2007/flags/SGI_x86_64_Intel14_flags.20140908.xml`

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.


For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.1.
Report generated on Mon Sep 8 13:45:45 2014 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 8 September 2014.