SPEC® MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI ICE X
(Intel Xeon E5-2690 v3, 2.6 GHz)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 84.9

MPI2007 license: 14
Test sponsor: SGI
Tested by: SGI

Test date: Jul-2014
Hardware Availability: Sep-2014
Software Availability: Apr-2014



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
121.pop2	2560	41.8	93.1	41.0	95.0	**41.0**	**94.8**							
122.tachyon	2560	70.3	27.6	49.9	39.0	**50.7**	**38.4**							
125.RAxML	2560	55.8	52.3	55.5	52.6	**55.5**	**52.6**							
126.lammps	2560	28.5	86.1	28.5	86.3	**28.5**	**86.3**							
128.GAPgeofem	2560	57.3	104	57.1	104	**57.1**	**104**							
129.tera_tf	2560	31.9	34.4	**31.9**	**34.4**	31.9	34.5							
132.zeusmp2	2560	28.0	75.6	28.2	75.1	**28.2**	**75.2**							
137.lu	2560	27.0	156	27.1	155	**27.0**	**156**							
142.dmilc	2560	21.1	174	21.0	176	**21.1**	**175**							
143.dleslie	2560	31.8	97.4	**31.9**	**97.2**	32.1	96.6							
145.lGemsFDTD	2560	56.0	78.8	**55.8**	**79.1**	55.7	79.2							
147.l2wrf2	2560	54.5	151	53.3	154	**54.4**	**151**							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI ICE X
(Intel Xeon E5-2690 v3, 2.6 GHz)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 84.9

MPI2007 license: 14
Test sponsor: SGI
Tested by: SGI

Test date: Jul-2014
Hardware Availability: Sep-2014
Software Availability: Apr-2014

Hardware Summary

Type of System:	Homogeneous
Compute Node:	SGI ICE X IP-131 Compute Node
Interconnect:	InfiniBand (MPI and I/O)
File Server Node:	SGI Rackable C1103-TY12
Total Compute Nodes:	128
Total Chips:	256
Total Cores:	3072
Total Threads:	3072
Total Memory:	16 TB
Base Ranks Run:	2560
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

C Compiler:	Intel C++ Composer XE 2013 for Linux, Version 14.0.3.174 Build 20140422
C++ Compiler:	Intel C++ Composer XE 2013 for Linux Version 14.0.3.174 Build 20140422
Fortran Compiler:	Intel Fortran Composer XE 2013 for Linux, Version 14.0.3.174 Build 20140422
Base Pointers:	64-bit
Peak Pointers:	Not Applicable
MPI Library:	SGI MPT 2.09 Patch 11049
Other MPI Info:	OFED 1.5.4
Pre-processors:	None
Other Software:	None

Node Description: SGI ICE X IP-131 Compute Node

Hardware

Number of nodes:	128
Uses of the node:	compute
Vendor:	SGI
Model:	SGI ICE X (Intel Xeon E5-2690 v3, 2.6 GHz)
CPU Name:	Intel Xeon E5-2690 v3
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	24
Cores per chip:	12
Threads per core:	1
CPU Characteristics:	12 Core, 2.60 GHz, 9.6 GT/s QPI Intel Turbo Boost Technology up to 3.50 GHz Hyper-Threading Technology disabled
CPU MHz:	2600
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	30 MB I+D on chip per chip
Other Cache:	None
Memory:	128 GB (8 x 16 GB 2Rx4 PC4-17000R-15, ECC)
Disk Subsystem:	None
Other Hardware:	None
Adapter:	Mellanox MT27500 with ConnectX-3 ASIC (PCIe x8 Gen3 8 GT/s)
Number of Adapters:	2
Slot Type:	PCIe x8 Gen3
Data Rate:	InfiniBand 4x FDR
Ports Used:	2
Interconnect Type:	InfiniBand

Software

Adapter:	Mellanox MT27500 with ConnectX-3 ASIC (PCIe x8 Gen3 8 GT/s)
Adapter Driver:	OFED-1.5.4
Adapter Firmware:	2.30.3000
Operating System:	SUSE Linux Enterprise Server 11 SP3 (x86_64), Kernel 3.0.93-0.8-default
Local File System:	NFSv3
Shared File System:	NFSv3 IPoIB
System State:	Multi-user, run level 3
Other Software:	SGI Tempo Service Node 2.8.1, Build 709rp49.sles11sp3-1402182002

Node Description: SGI Rackable C1103-TY12

Hardware

Number of nodes:	1
Uses of the node:	fileserver
Vendor:	SGI
Model:	SGI Rackable C1103-TY12 (Intel Xeon X5670, 2.93 GHz)
CPU Name:	Intel Xeon X5670
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	12
Cores per chip:	6
Threads per core:	2
CPU Characteristics:	Intel Turbo Boost Technology up to 3.33 GHz Hyper-Threading Technology enabled
CPU MHz:	2933
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per chip
L3 Cache:	12 MB I+D on chip per chip
Other Cache:	None
Memory:	96 GB (12 * 8 GB 2Rx4 PC3-10600R-9, ECC)
Disk Subsystem:	12 TB RAID 6 12 x 1 TB SATA (Seagate Constellation, 7200RPM)
Other Hardware:	None
Adapter:	Mellanox MT27500 with ConnectX-3 ASIC (PCIe x8 Gen3 8 GT/s)
Number of Adapters:	2
Slot Type:	PCIe x8 Gen3
Data Rate:	InfiniBand 4x FDR
Ports Used:	2
Interconnect Type:	InfiniBand

Software

Adapter:	Mellanox MT27500 with ConnectX-3 ASIC (PCIe x8 Gen3 8 GT/s)
Adapter Driver:	OFED-1.5.2
Adapter Firmware:	2.30.3000
Operating System:	SUSE Linux Enterprise Server 11 SP1 (x86_64), Kernel 2.6.32.46-0.3-default
Local File System:	xfs
Shared File System:	--
System State:	Multi-user, run level 3
Other Software:	SGI Foundation Software 2.5, Build 705r10.sles11-1110192111

Interconnect Description: InfiniBand (MPI and I/O)

Hardware

Vendor:	Mellanox Technologies and SGI
Model:	None
Switch Model:	SGI FDR Integrated IB Switch Blade 2SW9x27 with Mellanox SwitchX device 51000
Number of Switches:	30
Number of Ports:	36
Data Rate:	InfiniBand 4x FDR
Firmware:	09.02.3000
Topology:	Enhanced Hypercube
Primary Use:	MPI and I/O traffic

Software

Submit Notes

```
The config file option 'submit' was used.
```

General Notes

```
Software environment:
  export MPI_REQUEST_MAX=65536
  export MPI_TYPE_MAX=32768
  export MPI_IB_RAILS=2
  export MPI_CONNECTIONS_THRESHOLD=0
  ulimit -s unlimited

BIOS settings:
  AMI BIOS version DY2E6044
  Hyper-Threading Technology disabled
  Intel Turbo Boost Technology enabled (default)
  Intel Turbo Boost Technology activated with
    modprobe acpi_cpufreq
    cpupower frequency-set -u 2601MHz -d 2601MHz -g performance

Job Placement:
  Ten ranks were assigned to each CPU chip, leaving 2
  cores per chip idle. There were 30 switches used
  with a topologically compact configuration.

Additional notes regarding interconnect:
  The Infiniband network consists of two independent planes,
  with half the switches in the system allocated to each plane.
  I/O traffic is restricted to one plane, while MPI traffic can
  use both planes.
```

Base Compiler Invocation

C benchmarks:
`icc`

C++ benchmarks:

126.lammps: `icpc`

Fortran benchmarks:
`ifort`

Benchmarks using both Fortran and C:
`icc ifort`

Base Portability Flags

121.pop2: `-DSPEC_MPI_CASE_FLAG`

Base Optimization Flags

C benchmarks:
`-O3 -xCORE-AVX2 -no-prec-div`

C++ benchmarks:

126.lammps: `-O3 -xCORE-AVX2 -no-prec-div -ansi-alias`

Fortran benchmarks:
`-O3 -xCORE-AVX2 -no-prec-div`

Benchmarks using both Fortran and C:
`-O3 -xCORE-AVX2 -no-prec-div`

Base Other Flags

C benchmarks:
`-lmpi`

C++ benchmarks:

126.lammps: `-lmpi`

Fortran benchmarks:
`-lmpi`

Benchmarks using both Fortran and C:
`-lmpi`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/mpi2007/flags/SGI_x86_64_Intel14_flags.20140908.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/mpi2007/flags/SGI_x86_64_Intel14_flags.20140908.xml`

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.1.
Report generated on Mon Sep 8 13:45:55 2014 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 8 September 2014.