SPEC® MPIM2007 Result

Intel Corporation

Endeavor (Intel Xeon E7-8890 v3, 2.50 GHz, DDR4-2133 MHz, SMT on, Turbo off)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 17.1

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: May-2015
Hardware Availability: May-2015
Software Availability: Apr-2015



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	72	136	11.5	**136**	**11.5**	136	11.5							
107.leslie3d	72	317	16.5	**315**	**16.6**	315	16.6							
113.GemsFDTD	72	296	21.3	297	21.2	**296**	**21.3**							
115.fds4	72	168	11.6	**167**	**11.6**	167	11.6							
121.pop2	72	232	17.8	**231**	**17.9**	231	17.9							
122.tachyon	72	203	13.8	205	13.7	**204**	**13.7**							
126.lammps	72	**259**	**11.2**	258	11.3	260	11.2							
127.wrf2	72	295	26.4	295	26.4	**295**	**26.4**							
128.GAPgeofem	72	105	19.6	105	19.7	**105**	**19.6**							
129.tera_tf	72	216	12.8	**217**	**12.8**	218	12.7							

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
130.socorro	72	**100**	**38.0**	100	38.1	100	38.0							
132.zeusmp2	72	202	15.4	199	15.6	**200**	**15.5**							
137.lu	72	176	20.8	178	20.7	**177**	**20.8**							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System:	Homogeneous
Compute Node:	Endeavor Node
Interconnects:	IB Switch Gigabit Ethernet
File Server Node:	NFS
Total Compute Nodes:	1
Total Chips:	4
Total Cores:	72
Total Threads:	144
Total Memory:	512 GB
Base Ranks Run:	72
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

C Compiler:	Intel C++ Composer XE 2015 for Linux, Version 15.0.3.187 Build 20150407
C++ Compiler:	Intel C++ Composer XE 2015 for Linux, Version 15.0.3.187 Build 20150407
Fortran Compiler:	Intel Fortran Composer XE 2015 for Linux, Version 15.0.3.187 Build 20150407
Base Pointers:	64-bit
Peak Pointers:	64-bit
MPI Library:	Intel MPI Library 5.0.3.048 for Linux
Other MPI Info:	None
Pre-processors:	No
Other Software:	None

Node Description: Endeavor Node

Hardware

Number of nodes:	1
Uses of the node:	compute
Vendor:	Intel
Model:	S4TR2KU1Q
CPU Name:	Intel Xeon E7-8890 v3
CPU(s) orderable:	1-4 chips
Chips enabled:	4
Cores enabled:	72
Cores per chip:	18
Threads per core:	2
CPU Characteristics:	Intel Turbo Boost Technology disabled, 9.6 GT/s QPI, Hyper-Threading enabled
CPU MHz:	2500
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	45 MB I+D on chip per chip, 45 MB shared / 18 cores
Other Cache:	None
Memory:	512 GB (32 x 16 GB 2Rx4 PC4-17000R-15, ECC)
Disk Subsystem:	ATA INTEL SSDSA2BZ20, SSDSC2BB80
Other Hardware:	None
Adapter:	Intel (ESB2) 82575EB Dual-Port Gigabit Ethernet Controller

Continued on next page

Software

Adapter:	Intel (ESB2) 82575EB Dual-Port Gigabit Ethernet Controller
Adapter Driver:	e1000
Adapter Firmware:	None
Adapter:	Mellanox MCX353A-FCAT ConnectX-3
Adapter Driver:	OFED 3.5-2-MIC-rc1
Adapter Firmware:	2.31.5050
Operating System:	Red Hat EL 6.5, kernel 2.6.32-358
Local File System:	Linux/xfs
Shared File System:	NFS
System State:	Multi-User
Other Software:	IBM Platform LSF Standard 9.1.1.1

Intel Corporation

Endeavor (Intel Xeon E7-8890 v3, 2.50 GHz, DDR4-2133 MHz, SMT on, Turbo off)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 17.1

MPI2007 license:	13	**Test date:**	May-2015
Test sponsor:	Intel Corporation	**Hardware Availability:**	May-2015
Tested by:	Pavel Shelepugin	**Software Availability:**	Apr-2015

Node Description: Endeavor Node

Number of Adapters:	1
Slot Type:	PCI-Express x8
Data Rate:	1Gbps Ethernet
Ports Used:	2
Interconnect Type:	Ethernet
Adapter:	Mellanox MCX353A-FCAT ConnectX-3
Number of Adapters:	1
Slot Type:	PCIe x8 Gen3
Data Rate:	InfiniBand 4x FDR
Ports Used:	1
Interconnect Type:	InfiniBand

Node Description: NFS

Hardware

Number of nodes:	1
Uses of the node:	fileserver
Vendor:	Intel
Model:	S7000FC4UR
CPU Name:	Intel Xeon CPU
CPU(s) orderable:	1-4 chips
Chips enabled:	4
Cores enabled:	16
Cores per chip:	4
Threads per core:	2
CPU Characteristics:	--
CPU MHz:	2926
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	64 GB
Disk Subsystem:	8 disks, 500GB/disk, 2.7TB total
Other Hardware:	None
Adapter:	Intel 82563GB Dual-Port Gigabit Ethernet Controller
Number of Adapters:	1
Slot Type:	PCI-Express x8
Data Rate:	1Gbps Ethernet
Ports Used:	1
Interconnect Type:	Ethernet

Software

Adapter:	Intel 82563GB Dual-Port Gigabit Ethernet Controller
Adapter Driver:	e1000e
Adapter Firmware:	N/A
Operating System:	RedHat EL 5 Update 4
Local File System:	None
Shared File System:	NFS
System State:	Multi-User
Other Software:	None

Interconnect Description: IB Switch

Hardware

Vendor:	Mellanox
Model:	Mellanox MSX6025F-1BFR
Switch Model:	Mellanox MSX6025F-1BFR
Number of Switches:	46
Number of Ports:	36
Data Rate:	InfiniBand 4x FDR
Firmware:	9.2.8000
Topology:	Fat tree
Primary Use:	MPI traffic

Software

Interconnect Description: Gigabit Ethernet

Hardware

Vendor:	Force10 Networks, Cisco Systems
Model:	Force10 S50N, Force10 C300, Cisco WS-C4948E-F
Switch Model:	Force10 S50N, Force10 C300, Cisco WS-C4948E-F
Number of Switches:	13
Number of Ports:	48
Data Rate:	1Gbps Ethernet, 10Gbps Ethernet
Firmware:	8.3.2.0, 12.2(54)WO
Topology:	Star
Primary Use:	Cluster File System

Software

Submit Notes

```
The config file option 'submit' was used.
```

General Notes

```
130.socorro (base): "nullify_ptrs" src.alt was used.

 MPI startup command:
   mpiexec.hydra command was used to start MPI jobs.

 BIOS settings:
   Intel Hyper-Threading Technology (SMT): Enabled (default is Enabled)
   Intel Turbo Boost Technology (Turbo)  : Disabled (default is Enabled)

 RAM configuration:
   Compute nodes have 4x16-GB RDIMM on each memory channel.

 Network:
   Forty six 36-port switches: 18 core switches and 28 leaf switches.
   Each leaf has one link to each core. Remaining 18 ports on 25 of 28 leafs
   are used for compute nodes. On the remaining 3 leafs the ports are used
```

Continued on next page

General Notes (Continued)

```
    for FS nodes and other peripherals.

  Job placement:
    Each MPI job was assigned to a topologically compact set of nodes, i.e.
    the minimal needed number of leaf switches was used for each job: 1 switch
    for 72/144/288/576 ranks.

  IBM Platform LSF was used for job submission. It has no impact on performance.
    Information can be found at: http://www.ibm.com
```

Base Compiler Invocation

C benchmarks:
`mpiicc`

C++ benchmarks:

126.lammps: `mpiicpc`

Fortran benchmarks:
`mpiifort`

Benchmarks using both Fortran and C:
`mpiicc mpiifort`

Base Portability Flags

121.pop2: `-DSPEC_MPI_CASE_FLAG`
126.lammps: `-DMPICH_IGNORE_CXX_SEEK`
127.wrf2: `-DSPEC_MPI_CASE_FLAG -DSPEC_MPI_LINUX`
130.socorro: `-assume nostd_intent_in`

Base Optimization Flags

C benchmarks:
`-O3 -xCORE-AVX2 -no-prec-div`

C++ benchmarks:

126.lammps: `-O3 -xCORE-AVX2 -no-prec-div`

Fortran benchmarks:
`-O3 -xCORE-AVX2 -no-prec-div`

Benchmarks using both Fortran and C:
`-O3 -xCORE-AVX2 -no-prec-div`

The flags file that was used to format this result can be browsed at
http://www.spec.org/mpi2007/flags/EM64T_Intel140_flags.20140908.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/mpi2007/flags/EM64T_Intel140_flags.20140908.xml

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.1.
Report generated on Wed Jun 10 11:39:47 2015 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 10 June 2015.