SPEC® MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon E7-8890 v3, 2.50 GHz, DDR4-2133 MHz, SMT on, Turbo on)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 12.3

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: May-2015
Hardware Availability: May-2015
Software Availability: Apr-2015



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
121.pop2	288	318	12.2	**318**	**12.2**	317	12.3							
122.tachyon	288	278	6.99	**275**	**7.07**	274	7.09							
125.RAxML	288	281	10.4	283	10.3	**281**	**10.4**							
126.lammps	288	**267**	**9.21**	267	9.22	267	9.21							
128.GAPgeofem	288	**316**	**18.8**	314	18.9	316	18.8							
129.tera_tf	288	171	6.44	**170**	**6.45**	170	6.46							
132.zeusmp2	288	**190**	**11.2**	190	11.2	189	11.2							
137.lu	288	176	23.9	**178**	**23.7**	178	23.7							
142.dmilc	288	**279**	**13.2**	279	13.2	281	13.1							
143.dleslie	288	199	15.6	198	15.6	**199**	**15.6**							
145.lGemsFDTD	288	305	14.5	**305**	**14.5**	305	14.5							
147.l2wrf2	288	548	15.0	**548**	**15.0**	548	15.0							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon E7-8890 v3, 2.50 GHz, DDR4-2133 MHz, SMT on, Turbo on)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 12.3

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: May-2015
Hardware Availability: May-2015
Software Availability: Apr-2015

Hardware Summary

Type of System:	Homogeneous
Compute Node:	Endeavor Node
Interconnects:	IB Switch Gigabit Ethernet
File Server Node:	NFS
Total Compute Nodes:	4
Total Chips:	16
Total Cores:	288
Total Threads:	576
Total Memory:	2 TB
Base Ranks Run:	288
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

C Compiler:	Intel C++ Composer XE 2015 for Linux, Version 15.0.3.187 Build 20150407
C++ Compiler:	Intel C++ Composer XE 2015 for Linux, Version 15.0.3.187 Build 20150407
Fortran Compiler:	Intel Fortran Composer XE 2015 for Linux, Version 15.0.3.187 Build 20150407
Base Pointers:	64-bit
Peak Pointers:	64-bit
MPI Library:	Intel MPI Library 5.0.3.048 for Linux
Other MPI Info:	None
Pre-processors:	No
Other Software:	None

Node Description: Endeavor Node

Hardware

Number of nodes:	4
Uses of the node:	compute
Vendor:	Intel
Model:	S4TR2KU1Q
CPU Name:	Intel Xeon E7-8890 v3
CPU(s) orderable:	1-4 chips
Chips enabled:	4
Cores enabled:	72
Cores per chip:	18
Threads per core:	2
CPU Characteristics:	Intel Turbo Boost Technology up to 3.3 GHz, 9.6 GT/s QPI, Hyper-Threading enabled
CPU MHz:	2500
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	45 MB I+D on chip per chip, 45 MB shared / 18 cores
Other Cache:	None
Memory:	512 GB (32 x 16 GB 2Rx4 PC4-17000R-15, ECC)
Disk Subsystem:	ATA INTEL SSDSA2BZ20, SSDSC2BB80
Other Hardware:	None
Adapter:	Intel (ESB2) 82575EB Dual-Port Gigabit Ethernet Controller
Number of Adapters:	1
Slot Type:	PCI-Express x8
Data Rate:	1Gbps Ethernet
Ports Used:	2
Interconnect Type:	Ethernet
Adapter:	Mellanox MCX353A-FCAT ConnectX-3
Number of Adapters:	1
Slot Type:	PCIe x8 Gen3
Data Rate:	InfiniBand 4x FDR
Ports Used:	1
Interconnect Type:	InfiniBand

Software

Adapter:	Intel (ESB2) 82575EB Dual-Port Gigabit Ethernet Controller
Adapter Driver:	e1000
Adapter Firmware:	None
Adapter:	Mellanox MCX353A-FCAT ConnectX-3
Adapter Driver:	OFED 3.5-2-MIC-rc1
Adapter Firmware:	2.31.5050
Operating System:	Red Hat EL 6.5, kernel 2.6.32-358
Local File System:	Linux/xfs
Shared File System:	NFS
System State:	Multi-User
Other Software:	IBM Platform LSF Standard 9.1.1.1

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon E7-8890 v3, 2.50 GHz, DDR4-2133 MHz, SMT on, Turbo on)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 12.3

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: May-2015
Hardware Availability: May-2015
Software Availability: Apr-2015

Node Description: NFS

Hardware

Number of nodes:	1
Uses of the node:	fileserver
Vendor:	Intel
Model:	S7000FC4UR
CPU Name:	Intel Xeon CPU
CPU(s) orderable:	1-4 chips
Chips enabled:	4
Cores enabled:	16
Cores per chip:	4
Threads per core:	2
CPU Characteristics:	--
CPU MHz:	2926
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	64 GB
Disk Subsystem:	8 disks, 500GB/disk, 2.7TB total
Other Hardware:	None
Adapter:	Intel 82563GB Dual-Port Gigabit Ethernet Controller
Number of Adapters:	1
Slot Type:	PCI-Express x8
Data Rate:	1Gbps Ethernet
Ports Used:	1
Interconnect Type:	Ethernet

Software

Adapter:	Intel 82563GB Dual-Port Gigabit Ethernet Controller
Adapter Driver:	e1000e
Adapter Firmware:	N/A
Operating System:	RedHat EL 5 Update 4
Local File System:	None
Shared File System:	NFS
System State:	Multi-User
Other Software:	None

Interconnect Description: IB Switch

Hardware

Vendor:	Mellanox
Model:	Mellanox MSX6025F-1BFR
Switch Model:	Mellanox MSX6025F-1BFR
Number of Switches:	46
Number of Ports:	36
Data Rate:	InfiniBand 4x FDR
Firmware:	9.2.8000
Topology:	Fat tree
Primary Use:	MPI traffic

Software

Interconnect Description: Gigabit Ethernet

Hardware	
Vendor:	Force10 Networks, Cisco Systems
Model:	Force10 S50N, Force10 C300, Cisco WS-C4948E-F
Switch Model:	Force10 S50N, Force10 C300, Cisco WS-C4948E-F
Number of Switches:	13
Number of Ports:	48
Data Rate:	1Gbps Ethernet, 10Gbps Ethernet
Firmware:	8.3.2.0, 12.2(54)WO
Topology:	Star
Primary Use:	Cluster File System

Software

Submit Notes

```
The config file option 'submit' was used.
```

General Notes

```
MPI startup command:
  mpiexec.hydra command was used to start MPI jobs.

BIOS settings:
  Intel Hyper-Threading Technology (SMT): Enabled (default is Enabled)
  Intel Turbo Boost Technology (Turbo)  : Enabled (default is Enabled)

RAM configuration:
  Compute nodes have 4x16-GB RDIMM on each memory channel.

Network:
  Forty six 36-port switches: 18 core switches and 28 leaf switches.
  Each leaf has one link to each core. Remaining 18 ports on 25 of 28 leafs
  are used for compute nodes. On the remaining 3 leafs the ports are used
  for FS nodes and other peripherals.

Job placement:
  Each MPI job was assigned to a topologically compact set of nodes, i.e.
  the minimal needed number of leaf switches was used for each job: 1 switch
  for 144/288/576 ranks.

IBM Platform LSF was used for job submission. It has no impact on performance.
  Information can be found at: http://www.ibm.com
```

Base Compiler Invocation

C benchmarks:
mpiicc

Continued on next page

Base Compiler Invocation (Continued)

C++ benchmarks:

126.lammps: `mpiicpc`

Fortran benchmarks:
`mpiifort`

Benchmarks using both Fortran and C:
`mpiicc mpiifort`

Base Portability Flags

121.pop2: `-DSPEC_MPI_CASE_FLAG`
126.lammps: `-DMPICH_IGNORE_CXX_SEEK`

Base Optimization Flags

C benchmarks:
`-O3 -xCORE-AVX2 -no-prec-div`

C++ benchmarks:

126.lammps: `-O3 -xCORE-AVX2 -no-prec-div`

Fortran benchmarks:
`-O3 -xCORE-AVX2 -no-prec-div`

Benchmarks using both Fortran and C:
`-O3 -xCORE-AVX2 -no-prec-div`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/mpi2007/flags/EM64T_Intel140_flags.20140908.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/mpi2007/flags/EM64T_Intel140_flags.20140908.xml`

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.1.
Report generated on Wed Jun 10 11:40:20 2015 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 10 June 2015.