SPEC® MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI ICE XA
(Intel Xeon E5-2690 v4, 2.6 GHz)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 6.24

MPI2007 license: 14
Test sponsor: SGI
Tested by: SGI

Test date: Jun-2016
Hardware Availability: May-2016
Software Availability: Jun-2016



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
121.pop2	224	645	6.04	**648**	**6.00**	650	5.99							
122.tachyon	224	473	4.11	**473**	**4.11**	474	4.10							
125.RAxML	224	445	6.56	**445**	**6.56**	445	6.56							
126.lammps	224	**461**	**5.33**	461	5.33	461	5.33							
128.GAPgeofem	224	**808**	**7.34**	811	7.32	807	7.35							
129.tera_tf	224	250	4.40	250	4.39	**250**	**4.39**							
132.zeusmp2	224	**348**	**6.09**	348	6.09	348	6.09							
137.lu	224	640	6.57	654	6.42	**648**	**6.48**							
142.dmilc	224	352	10.5	353	10.4	**352**	**10.5**							
143.dleslie	224	**465**	**6.67**	466	6.66	465	6.67							
145.lGemsFDTD	224	650	6.79	650	6.78	**650**	**6.79**							
147.l2wrf2	224	1224	6.70	1227	6.69	**1225**	**6.70**							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI ICE XA
(Intel Xeon E5-2690 v4, 2.6 GHz)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 6.24

MPI2007 license: 14
Test sponsor: SGI
Tested by: SGI

Test date: Jun-2016
Hardware Availability: May-2016
Software Availability: Jun-2016

Hardware Summary

Type of System:	Homogeneous
Compute Node:	SGI ICE XA IP-125 CS
Interconnect:	InfiniBand (MPI and I/O)
File Server Node:	SGI MIS Server
Total Compute Nodes:	4
Total Chips:	8
Total Cores:	112
Total Threads:	224
Total Memory:	512 GB
Base Ranks Run:	224
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

C Compiler:	Intel C++ Composer XE 2016 for Linux, Version 16.0.3.210 Build 20160415
C++ Compiler:	Intel C++ Composer XE 2016 for Linux Version 16.0.3.210 Build 20160405
Fortran Compiler:	Intel Fortran Composer XE 2016 for Linux, Version 16.0.3.210 Build 20160405
Base Pointers:	64-bit
Peak Pointers:	64-bit
MPI Library:	SGI MPT 2.14 Patch 11328
Other MPI Info:	OFED 3.2.2
Pre-processors:	None
Other Software:	None

Node Description: SGI ICE XA IP-125 CS

Hardware

Number of nodes:	4
Uses of the node:	compute
Vendor:	SGI
Model:	SGI ICE XA (Intel Xeon E5-2690 v4, 2.6 GHz)
CPU Name:	Intel Xeon E5-2690 v4
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	28
Cores per chip:	14
Threads per core:	2
CPU Characteristics:	14 Core, 2.60 GHz, 9.6 GT/s QPI Intel Turbo Boost Technology up to 3.50 GHz Hyper-Threading Technology enabled
CPU MHz:	2600
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	35 MB I+D on chip per chip
Other Cache:	None
Memory:	128 GB (8 x 16 GB 2Rx4 PC4-2400T-R)
Disk Subsystem:	None
Other Hardware:	None
Adapter:	Mellanox MT27700 with ConnectX-4 ASIC (PCIe x16 Gen3 8 GT/s)
Number of Adapters:	2
Slot Type:	PCIe x16 Gen3
Data Rate:	InfiniBand 4X EDR
Ports Used:	1
Interconnect Type:	InfiniBand

Software

Adapter:	Mellanox MT27700 with ConnectX-4 ASIC (PCIe x16 Gen3 8 GT/s)
Adapter Driver:	OFED-3.2.1.5.3
Adapter Firmware:	12.14.0114
Operating System:	SUSE Linux Enterprise Server 11 SP4 (x86_64), Kernel 3.0.101-71.1.10690.1.PTF-default
Local File System:	NFSv3
Shared File System:	NFSv3 IPoIB
System State:	Multi-user, run level 3
Other Software:	SGI Tempo Compute Node 3.3.0, Build 714r18.sles11sp4-1604041900

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI ICE XA
(Intel Xeon E5-2690 v4, 2.6 GHz)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 6.24

MPI2007 license: 14
Test sponsor: SGI
Tested by: SGI

Test date: Jun-2016
Hardware Availability: May-2016
Software Availability: Jun-2016

Node Description: SGI MIS Server

Hardware

Number of nodes:	1
Uses of the node:	fileserver
Vendor:	SGI
Model:	SGI MIS Server
CPU Name:	Intel Xeon E5-2670
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	16
Cores per chip:	8
Threads per core:	1
CPU Characteristics:	Intel Turbo Boost Technology up to 3.30 GHz Hyper-Threading Technology disabled
CPU MHz:	1200
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	20 MB I+D on chip per chip
Other Cache:	None
Memory:	128 GB (12 * 8 GB 2Rx4 PC3-12800R-11, ECC)
Disk Subsystem:	45 TB RAID 6 8 x 6+2 900GB (WD, 10K RPM)
Other Hardware:	None
Adapter:	Mellanox MT27500 with ConnectX-3 ASIC
Number of Adapters:	2
Slot Type:	PCIe x8 Gen3
Data Rate:	InfiniBand 4X FDR
Ports Used:	2
Interconnect Type:	InfiniBand

Software

Adapter:	Mellanox MT27500 with ConnectX-3 ASIC
Adapter Driver:	OFED-3.2.0.1.1
Adapter Firmware:	2.36.5000
Operating System:	SUSE Linux Enterprise Server 11 (x86_64), Kernel 3.0.101-0.46-default
Local File System:	xfs
Shared File System:	--
System State:	Multi-user, run level 3
Other Software:	SGI Foundation Software 2.9, Build 711r2.sles11sp3-1411192056

Interconnect Description: InfiniBand (MPI and I/O)

Hardware

Vendor:	Mellanox Technologies and SGI
Model:	None
Switch Model:	SGI P0002145
Number of Switches:	2
Number of Ports:	36
Data Rate:	InfiniBand 4x EDR
Firmware:	11.0350.0394
Topology:	Enhanced Hypercube
Primary Use:	MPI and I/O traffic

Software

Submit Notes

```
The config file option 'submit' was used.
```

General Notes

```
Software environment:
  export MPI_REQUEST_MAX=65536
  export MPI_TYPE_MAX=32768
  export MPI_IB_RAILS=2
  export MPI_IB_UPGRADE_SENDS=50
  export MPI_IB_IMM_UPGRADE=false
  export MPI_IB_DCIS=2
  export MPI_CONNECTIONS_THRESHOLD=0
  export MPI_IB_MTU=4096
  ulimit -s unlimited
BIOS settings:
  AMI BIOS version HA012036
  Hyper-Threading Technology enabled
  Intel Turbo Boost Technology enabled (default)
  Transparent Hugepages Enabled
Job Placement:
  Each MPI job was assigned to a topologically compact set
  of nodes with 28 ranks per socket.
Additional notes regarding interconnect:
  The Infiniband network consists of two independent planes,
  with half the switches in the system allocated to each plane.
  I/O traffic is restricted to one plane, while MPI traffic can
  use both planes.
```

Base Compiler Invocation

C benchmarks:
`icc`

C++ benchmarks:

126.lammps: `icpc`

Fortran benchmarks:
`ifort`

Benchmarks using both Fortran and C:
`icc ifort`

Base Portability Flags

121.pop2: `-DSPEC_MPI_CASE_FLAG`

Base Optimization Flags

C benchmarks:
`-O3 -xCORE-AVX2 -no-prec-div`

C++ benchmarks:

126.lammps: `-O3 -xCORE-AVX2 -no-prec-div -ansi-alias`

Fortran benchmarks:
`-O3 -xCORE-AVX2 -no-prec-div`

Benchmarks using both Fortran and C:
`-O3 -xCORE-AVX2 -no-prec-div`

Base Other Flags

C benchmarks:
`-lmpi`

C++ benchmarks:

126.lammps: `-lmpi`

Fortran benchmarks:
`-lmpi`

Benchmarks using both Fortran and C:
`-lmpi`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/mpi2007/flags/SGI_x86_64_Intel14_flags.20140908.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/mpi2007/flags/SGI_x86_64_Intel14_flags.20140908.xml`

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.1.
Report generated on Fri Aug 19 11:45:13 2016 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 19 August 2016.