SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Colfax International

Intel Xeon Phi 7210, 1.30 GHz,
SMT on, Turbo off, flat (MCDRAM preferred)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 7.35

MPI2007 license: 3440
Test sponsor: Indiana University
Tested by: Junjie Li

Test date: Sep-2016
Hardware Availability: Aug-2016
Software Availability: Apr-2016



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	64	**195**	**8.03**	195	8.02	193	8.10							
107.leslie3d	64	459	11.4	**462**	**11.3**	462	11.3							
113.GemsFDTD	64	**558**	**11.3**	556	11.3	567	11.1							
115.fds4	64	411	4.75	412	4.74	**411**	**4.74**							
121.pop2	64	**693**	**5.95**	695	5.94	691	5.97							
122.tachyon	64	916	3.05	**918**	**3.05**	918	3.05							
126.lammps	64	802	3.64	804	3.63	**803**	**3.63**							
127.wrf2	64	558	14.0	**558**	**14.0**	559	13.9							
128.GAPgeofem	64	286	7.22	**286**	**7.22**	287	7.20							
129.tera_tf	64	788	3.51	**789**	**3.51**	790	3.51							

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Colfax International

Intel Xeon Phi 7210, 1.30 GHz,
SMT on, Turbo off, flat (MCDRAM preferred)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 7.35

MPI2007 license: 3440
Test sponsor: Indiana University
Tested by: Junjie Li

Test date: Sep-2016
Hardware Availability: Aug-2016
Software Availability: Apr-2016

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
130.socorro	64	**173**	**22.1**	173	22.1	173	22.1							
132.zeusmp2	64	350	8.86	**375**	**8.27**	382	8.11							
137.lu	64	400	9.19	**415**	**8.86**	433	8.49							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System:	Homogeneous
Compute Node:	KNL
File Server Node:	KNL
Head Node:	KNL
Total Compute Nodes:	1
Total Chips:	1
Total Cores:	64
Total Threads:	256
Total Memory:	96 GB
Base Ranks Run:	64
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

C Compiler:	Intel C++ Composer XE 2016 for Linux, Version 16.0.3.210 Build 20160415
C++ Compiler:	Intel C++ Composer XE 2016 for Linux, Version 16.0.3.210 Build 20160415
Fortran Compiler:	Intel Fortran Composer XE 2016 for Linux, Version 16.0.3.210 Build 20160415
Base Pointers:	64-bit
Peak Pointers:	64-bit
MPI Library:	Intel MPI Library for Linux 5.1.3 Build 20160120
Other MPI Info:	None
Pre-processors:	No
Other Software:	None

Node Description: KNL

Hardware

Number of nodes:	1
Uses of the node:	head, compute, fileserver
Vendor:	Colfax International
Model:	None
CPU Name:	Intel Xeon Phi 7210
CPU(s) orderable:	1 chip
Chips enabled:	1
Cores enabled:	64
Cores per chip:	64
Threads per core:	4
CPU Characteristics:	Intel Turbo Boost Technology off, Simultaneous Multithreading (SMT) on
CPU MHz:	1300
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per two cores
L3 Cache:	None
Other Cache:	None
Memory:	96 GB (6 x 16 GB 2Rx8 PC4-2400T-REB-11, ECC)
Disk Subsystem:	Intel S3510 SSD 800GB, SATA3
Other Hardware:	None
Adapter:	0
Number of Adapters:	0
Slot Type:	0
Data Rate:	0

Continued on next page

Software

Adapter:	0
Adapter Driver:	0
Adapter Firmware:	--
Operating System:	CentOS Linux Release 7.2.1511
Local File System:	Linux/ext4
Shared File System:	None
System State:	Multi-User
Other Software:	None

Node Description: KNL

Ports Used:	0
Interconnect Type:	0

Submit Notes

```
The config file option 'submit' was used.
numactl -p 1 mpirun -genv I_MPI_COMPATIBILITY 4  -np $ranks $command
```

General Notes

```
130.socorro (base): "nullify_ptrs" src.alt was used.

 MPI startup command:
   mpirun command was used to start MPI jobs.

 BIOS settings:
   Intel Simultaneous Multithreading (SMT): on
   Intel Turbo Boost Technology (Turbo)  : off
   Cluster Mode: quadrant
   Memory Mode: flat
```

Base Compiler Invocation

C benchmarks:
`mpiicc`

C++ benchmarks:

126.lammps: `mpiicpc`

Fortran benchmarks:
`mpiifort`

Benchmarks using both Fortran and C:
`mpiicc mpiifort`

Base Portability Flags

121.pop2: `-DSPEC_MPI_CASE_FLAG`
126.lammps: `-DMPICH_IGNORE_CXX_SEEK`
127.wrf2: `-DSPEC_MPI_CASE_FLAG -DSPEC_MPI_LINUX`
130.socorro: `-assume nostd_intent_in`

Base Optimization Flags

C benchmarks:
`-O3 -xMIC-AVX512 -no-prec-div -fp-model fast=2 -ipo -fma`

C++ benchmarks:

126.lammps: `-O3 -xMIC-AVX512 -no-prec-div -fp-model fast=2 -ipo -fma`

Fortran benchmarks:
`-O3 -xMIC-AVX512 -no-prec-div -fp-model fast=2 -ipo -fma`

Benchmarks using both Fortran and C:
`-O3 -xMIC-AVX512 -no-prec-div -fp-model fast=2 -ipo -fma`

The flags files that were used to format this result can be browsed at
http://www.spec.org/mpi2007/flags/EM64T_Intel_flags.html
http://www.spec.org/mpi2007/flags/colfax-knl.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/mpi2007/flags/EM64T_Intel_flags.xml
http://www.spec.org/mpi2007/flags/colfax-knl.xml

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.1.
Report generated on Wed Jan 11 12:44:19 2017 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 11 January 2017.