SPEC® MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Cray

Cray XC30 (Intel Xeon E5-2697 v2)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 8.14

MPI2007 license: 3440A
Test sponsor: Indiana University
Tested by: Indiana University

Test date: Mar-2017
Hardware Availability: Apr-2013
Software Availability: Feb-2017



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
121.pop2	192	480	8.10	476	8.17	**477**	**8.16**							
122.tachyon	192	400	4.86	403	4.82	**403**	**4.82**							
125.RAxML	192	500	5.84	502	5.82	**501**	**5.83**							
126.lammps	192	408	6.03	405	6.07	**406**	**6.06**							
128.GAPgeofem	192	535	11.1	531	11.2	**531**	**11.2**							
129.tera_tf	192	231	4.75	234	4.70	**232**	**4.75**							
132.zeusmp2	192	291	7.28	**289**	**7.35**	287	7.39							
137.lu	192	376	11.2	**376**	**11.2**	378	11.1							
142.dmilc	192	304	12.1	311	11.9	**308**	**12.0**							
143.dleslie	192	269	11.5	272	11.4	**269**	**11.5**							
145.lGemsFDTD	192	**454**	**9.71**	454	9.72	455	9.69							
147.l2wrf2	192	**785**	**10.5**	783	10.5	785	10.4							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Cray

Cray XC30 (Intel Xeon E5-2697 v2)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 8.14

MPI2007 license: 3440A
Test sponsor: Indiana University
Tested by: Indiana University

Test date: Mar-2017
Hardware Availability: Apr-2013
Software Availability: Feb-2017

Hardware Summary

Type of System:	Homogeneous
Compute Node:	Big Red II Plus Node
Interconnects:	Infiniband (QDR) Cray Aries
File Server Node:	Data Capacitor II
Total Compute Nodes:	8
Total Chips:	16
Total Cores:	192
Total Threads:	384
Total Memory:	512 GB
Base Ranks Run:	192
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

C Compiler:	Intel C Composer XE 2017 for Linux, Version 17.0.2.174 Build 20170213
C++ Compiler:	Intel C++ Composer XE 2017 for Linux, Version 17.0.2.174 Build 20170213
Fortran Compiler:	Intel Fortran Composer XE 2017 for Linux, Version 17.0.2.174 Build 20170213
Base Pointers:	64-bit
Peak Pointers:	64-bit
MPI Library:	Cray MPI (MPT) 7.5.0
Other MPI Info:	None
Pre-processors:	No
Other Software:	None

Node Description: Big Red II Plus Node

Hardware

Number of nodes:	8
Uses of the node:	compute
Vendor:	Cray
Model:	XC30
CPU Name:	Intel Xeon E5-2697 v2
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	24
Cores per chip:	12
Threads per core:	2
CPU Characteristics:	Intel Turbo Boost Technology disabled, Hyper-Threading enabled
CPU MHz:	2700
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	30 MB I+D on chip per chip
Other Cache:	None
Memory:	64 GB (8 x 8 GB 2Rx4 PC3-14900R-13, ECC)
Disk Subsystem:	None
Other Hardware:	None
Adapter:	Mellanox Technologies MT27500 ConnectX-3
Number of Adapters:	1
Slot Type:	PCIe x16 Gen 3
Data Rate:	40Gbps
Ports Used:	1
Interconnect Type:	40 Gigabit Infiniband (QDR)
Adapter:	Cray Aries
Number of Adapters:	1
Slot Type:	PCIe x16 Gen 3
Data Rate:	126 Gbps
Ports Used:	4
Interconnect Type:	Aries

Software

Adapter:	Mellanox Technologies MT27500 ConnectX-3
Adapter Driver:	1.0-ofed1.5.4.1
Adapter Firmware:	2.33.5100
Adapter:	Cray Aries
Adapter Driver:	Proprietary Cray_kgni
Adapter Firmware:	v004.r091
Operating System:	SUSE Linux Enterprise Server 11 SP3 (x86_64), Cray Linux Environment 5.2 3.0.101-0.46.1_1.0502.8871-cray_ari_c
Local File System:	None
Shared File System:	Lustre
System State:	Multi-User
Other Software:	Slurm 15.08.12

Node Description: Data Capacitor II

Hardware

Number of nodes:	2
Uses of the node:	fileserver
Vendor:	DDN
Model:	DDN SFA12K
CPU Name:	Intel Xeon CPU E5-2620
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	12
Cores per chip:	6
Threads per core:	1
CPU Characteristics:	Intel Turbo Boost Technology up to 2.50 GHz
CPU MHz:	2000
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	15 MB I+D on chip per chip
Other Cache:	None
Memory:	96 GB
Disk Subsystem:	30 TB RAID 6, 10 (8 + 2) x 3 TB SAS Hitachi HUS724030ALS640, 7200RPM, 6.0Gbps
Other Hardware:	None
Adapter:	Mellanox ConnectX MHQH29-XTC
Number of Adapters:	1
Slot Type:	PCIe x8 Gen 2
Data Rate:	40Gbps
Ports Used:	1
Interconnect Type:	40 Gigabit Infiniband (QDR)

Software

Adapter:	Mellanox ConnectX MHQH29-XTC
Adapter Driver:	1.0-ofed1.5.4.1
Adapter Firmware:	2.9.1000
Operating System:	CentOS 6.2
Local File System:	Linux/ext4
Shared File System:	lustre
System State:	Multi-User
Other Software:	None

Interconnect Description: Infiniband (QDR)

Hardware

Vendor:	DDN
Model:	Mellanox SX6506
Switch Model:	Mellanox SX6506
Number of Switches:	1
Number of Ports:	108
Data Rate:	56 Gbps
Firmware:	mellanox SX6506
Topology:	switched
Primary Use:	Lustre fileserver

Software

Interconnect Description: Cray Aries

Hardware

Vendor:	Cray
Model:	Cray Aries
Switch Model:	Cray Aries
Number of Switches:	144
Number of Ports:	48
Data Rate:	126 Gb/s
Firmware:	v004.r091
Topology:	Dragonfly
Primary Use:	MPI traffic

Software

Submit Notes

```
The config file option 'submit' was used.
submit = srun -c 1 -n $ranks -q $command
```

General Notes

```
130.socorro (base): "nullify_ptrs" src.alt was used.

MPI startup command:
  srun command was used to start MPI jobs.

export MPICH_NO_BUFFER_ALIAS_CHECK=true
  If set, the buffer alias error check for collectives is
  disabled. The MPI standard does not allow aliasing of type
  OUT or INOUT parameters on the same collective function
  call. The default is false.

Job placement:
  Slurm is used for job placement.
  Compute nodes are selected by Slurm.
  No specific node selection is used.
```

Base Compiler Invocation

C benchmarks:
`cc`

C++ benchmarks:

126.lammps: `CC`

Fortran benchmarks:
`ftn`

Continued on next page

Base Compiler Invocation (Continued)

Benchmarks using both Fortran and C:
cc ftn

Base Portability Flags

121.pop2: -DSPEC_MPI_CASE_FLAG
126.lammps: -DMPICH_IGNORE_CXX_SEEK

Base Optimization Flags

C benchmarks:
-O3 -ansi-alias -no-prec-div -fp-model fast=2

C++ benchmarks:

126.lammps: -O3 -ansi-alias -no-prec-div -fp-model fast=2

Fortran benchmarks:
-O3 -ansi-alias -no-prec-div -fp-model fast=2

Benchmarks using both Fortran and C:
-O3 -ansi-alias -no-prec-div -fp-model fast=2

The flags file that was used to format this result can be browsed at
http://www.spec.org/mpi2007/flags/EM64T_Intel170_flags.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/mpi2007/flags/EM64T_Intel170_flags.xml

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.1.
Report generated on Mon Dec 11 11:03:50 2017 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 9 December 2017.