SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR650
(Intel Xeon Platinum 8280 CPU, 2.70 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 35.3

MPI2007 license: 28
Test sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test date: Mar-2019
Hardware Availability: Apr-2019
Software Availability: Apr-2019



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	112	70.2	22.3	**70.3**	**22.3**	70.9	22.1							
107.leslie3d	112	172	30.3	**173**	**30.2**	173	30.1							
113.GemsFDTD	112	162	38.9	161	39.1	**162**	**39.0**							
115.fds4	112	76.6	25.5	**76.4**	**25.5**	76.0	25.7							
121.pop2	112	124	33.2	**124**	**33.2**	126	32.9							
122.tachyon	112	82.5	33.9	82.4	34.0	**82.4**	**33.9**							
126.lammps	112	107	27.3	**107**	**27.2**	107	27.1							
127.wrf2	112	**136**	**57.4**	136	57.4	136	57.2							
128.GAPgeofem	112	46.1	44.8	**46.5**	**44.4**	46.6	44.3							
129.tera_tf	112	**97.5**	**28.4**	97.0	28.5	98.2	28.2							

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR650
(Intel Xeon Platinum 8280 CPU, 2.70 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 35.3

MPI2007 license: 28
Test sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test date: Mar-2019
Hardware Availability: Apr-2019
Software Availability: Apr-2019

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
130.socorro	112	75.4	50.6	76.7	49.8	**76.4**	**50.0**							
132.zeusmp2	112	83.7	37.1	84.2	36.8	**84.0**	**36.9**							
137.lu	112	76.9	47.8	76.8	47.9	**76.8**	**47.8**							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System: Homogeneous
Compute Node: ThinkSystem SR650
Interconnect: Intel Omni-Path
File Server Node: NFS
Total Compute Nodes: 2
Total Chips: 4
Total Cores: 112
Total Threads: 112
Total Memory: 1536 GB
Base Ranks Run: 112
Minimum Peak Ranks: --
Maximum Peak Ranks: --

Software Summary

C Compiler: Intel C++ Compiler 17.0 Update 7 for Linux Version 17.0.7 Build 20180403
C++ Compiler: Intel C++ Compiler 17.0 Update 7 for Linux Version 17.0.7 Build 20180403
Fortran Compiler: Intel Fortran Compiler 17.0 Update 7 for Linux Version 17.0.7 Build 20180403
Base Pointers: 64-bit
Peak Pointers: Not Applicable
MPI Library: Intel MPI Library for Linux* OS Version 2018 Update 3 Build 20180411
Other MPI Info: None
Pre-processors: No
Other Software: None

Node Description: ThinkSystem SR650

Hardware

Number of nodes: 2
Uses of the node: compute
Vendor: Lenovo Global Technology
Model: SR650
CPU Name: Intel Xeon Platinum 8280
CPU(s) orderable: 1-2 chips
Chips enabled: 2
Cores enabled: 56
Cores per chip: 28
Threads per core: 1
CPU Characteristics: None
CPU MHz: 2700
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 1 MB I+D on chip per core
L3 Cache: 38.5 MB I+D on chip per chip
Other Cache: None
Memory: 768 GB (24 x 32 GB 2Rx4 PC4-2933Y-R)
Disk Subsystem: 1 x 1 TB 12 Gbps SAS 2.5" SSD (JBOD)
Other Hardware: ThinkSystem RAID 530-8i 2GB Flash
Adapter: Intel Omni-Path 100 Series Single-port PCIe 3.0 x16 HFA
Number of Adapters: 1
Slot Type: PCI-Express Gen3 x16
Data Rate: 100 Gb/s

Continued on next page

Software

Adapter: Intel Omni-Path 100 Series Single-port PCIe 3.0 x16 HFA
Adapter Driver: IFS 10.9.1.0.15
Adapter Firmware: 10.9.0.1.0
Operating System: Red Hat Enterprise Linux Server release 7.6, Kernel 3.10.0-957.el7.x86_64
Local File System: xfs
Shared File System: nfs
System State: Multi-user, run level 3
Other Software: NONE

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR650
(Intel Xeon Platinum 8280 CPU, 2.70 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 35.3

MPI2007 license: 28
Test sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test date: Mar-2019
Hardware Availability: Apr-2019
Software Availability: Apr-2019

Node Description: ThinkSystem SR650

Ports Used:	1
Interconnect Type:	Intel Omni-Path Fabric 100 Series

Node Description: NFS

Hardware

Number of nodes:	1
Uses of the node:	Fileserver
Vendor:	Lenovo Global Technology
Model:	ThinkSystem SR650
CPU Name:	Intel Xeon Platinum 8280
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	56
Cores per chip:	28
Threads per core:	1
CPU Characteristics:	None
CPU MHz:	2700
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per core
L3 Cache:	38.5 MB I+D on chip per chip
Other Cache:	None
Memory:	768 GB (24 x 32 GB 2Rx4 PC4-2933Y-R)
Disk Subsystem:	1 x 1 TB 12 Gbps SAS 2.5" SSD (JBOD)
Other Hardware:	None
Adapter:	Intel Omni-Path 100 Series Single-port PCIe 3.0 x16 HFA
Number of Adapters:	1
Slot Type:	PCI-Express 3.0 x16
Data Rate:	100 Gb/s
Ports Used:	1
Interconnect Type:	Intel Omni-Path Fabric 100 series

Software

Adapter:	Intel Omni-Path 100 Series Single-port PCIe 3.0 x16 HFA
Adapter Driver:	10.9.1.0.15
Adapter Firmware:	10.9.0.1.0
Operating System:	Red Hat Enterprise Linux Server release 7.6
Local File System:	None
Shared File System:	NFS
System State:	Multi-User, run level 3
Other Software:	None

Interconnect Description: Intel Omni-Path

Hardware

Vendor:	Intel
Model:	Intel Omni-Path Fabric 100 Series
Switch Model:	Intel Omni-Path Edge Switch 100 Series 48 Port 2 PSU
Number of Switches:	1
Number of Ports:	48
Data Rate:	100 Gb/s
Firmware:	10.3.0.0.60
Topology:	Mesh
Primary Use:	MPI Traffic

Software

Submit Notes

```
The config file option 'submit' was used.
```

General Notes

```
MPI startup command:
  mpiexec command was used to start MPI jobs.

RAM configuration:
  Compute nodes have 2 x 32 GB RDIMM on each memory channel.

BIOS settings:
  Operating Mode : Maximum Performance Mode
  Intel Hyper-Threading Technology (SMT): Disabled
  SNC (Sub-NUMA Cluster): Enable


Yes: The test sponsor attests, as of date of publication,
that CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication,
that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication,
that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.
```

Base Compiler Invocation

C benchmarks:
`mpiicc`

C++ benchmarks:

126.lammps: `mpiicpc`

Fortran benchmarks:
`mpiifort`

Benchmarks using both Fortran and C:
`mpiicc mpiifort`

Base Portability Flags

121.pop2: `-DSPEC_MPI_CASE_FLAG`
126.lammps: `-DMPICH_IGNORE_CXX_SEEK`
127.wrf2: `-DSPEC_MPI_CASE_FLAG -DSPEC_MPI_LINUX`

Continued on next page

Base Portability Flags (Continued)

130.socorro: `-assume nostd_intent_in`

Base Optimization Flags

C benchmarks:
`-O3 -ipo -xCORE-AVX512 -no-prec-div`

C++ benchmarks:

126.lammps: `-O3 -ipo -xCORE-AVX512 -no-prec-div`

Fortran benchmarks:
`-O3 -ipo -xCORE-AVX512 -no-prec-div`

Benchmarks using both Fortran and C:
`-O3 -ipo -xCORE-AVX512 -no-prec-div`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/mpi2007/flags/EM64T_Intel121_flags.20170711.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/mpi2007/flags/EM64T_Intel121_flags.20170711.xml`

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.1.
Report generated on Tue Apr 2 18:30:12 2019 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 2 April 2019.