SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR950
(Intel Xeon Platinum 8280L CPU, 2.70 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 28.6

MPI2007 license: 28
Test sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test date: Mar-2019
Hardware Availability: Apr-2019
Software Availability: Apr-2019



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	84	85.7	18.3	**86.0**	**18.2**	86.7	18.0							
107.leslie3d	84	**219**	**23.8**	219	23.9	221	23.6							
113.GemsFDTD	84	227	27.8	228	27.7	**228**	**27.7**							
115.fds4	84	104	18.8	**104**	**18.7**	107	18.2							
121.pop2	84	135	30.5	**135**	**30.5**	135	30.6							
122.tachyon	84	**109**	**25.6**	109	25.5	109	25.7							
126.lammps	84	138	21.2	138	21.1	**138**	**21.1**							
127.wrf2	84	178	43.7	179	43.6	**179**	**43.6**							
128.GAPgeofem	84	**61.9**	**33.4**	62.1	33.2	61.8	33.4							
129.tera_tf	84	107	25.9	105	26.3	**107**	**25.9**							

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR950
(Intel Xeon Platinum 8280L CPU, 2.70 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 28.6

MPI2007 license: 28
Test sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test date: Mar-2019
Hardware Availability: Apr-2019
Software Availability: Apr-2019

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
130.socorro	84	69.2	55.1	**69.4**	**55.0**	69.6	54.9							
132.zeusmp2	84	102	30.5	**102**	**30.5**	102	30.4							
137.lu	84	101	36.5	98.5	37.3	**99.2**	**37.1**							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System:	Homogeneous
Compute Node:	ThinkSystem SR950
Interconnect:	N/A
Total Compute Nodes:	1
Total Chips:	3
Total Cores:	84
Total Threads:	84
Total Memory:	576 GB
Base Ranks Run:	84
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

C Compiler:	Intel C++ Compiler 18.0 Update 3 for Linux Version 18.0.3 Build 20180410
C++ Compiler:	Intel C++ Compiler 18.0 Update 3 for Linux Version 18.0.3 Build 20180410
Fortran Compiler:	Intel Fortran Compiler 18.0 Update 3 for Linux Version 18.0.3 Build 20180410
Base Pointers:	64-bit
Peak Pointers:	Not Applicable
MPI Library:	Intel MPI Library for Linux* OS Version 2018 Update 3 Build 20180411
Other MPI Info:	None
Pre-processors:	No
Other Software:	None

Node Description: ThinkSystem SR950

Hardware

Number of nodes:	1
Uses of the node:	compute
Vendor:	Lenovo Global Technology
Model:	SR950
CPU Name:	Intel Xeon Platinum 8280L
CPU(s) orderable:	2,3,4,6,8 chips
Chips enabled:	3
Cores enabled:	84
Cores per chip:	28
Threads per core:	1
CPU Characteristics:	None
CPU MHz:	2700
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per core
L3 Cache:	38.5 MB I+D on chip per chip
Other Cache:	None
Memory:	576 GB (36 x 16 GB 2Rx8 PC4-2933Y-R)
Disk Subsystem:	1 x 1 TB NVMe 2.5" SSD
Other Hardware:	N/A
Adapter:	N/A
Number of Adapters:	0
Slot Type:	N/A
Data Rate:	N/A
Ports Used:	0

Continued on next page

Software

Adapter:	N/A
Adapter Driver:	N/A
Adapter Firmware:	N/A
Operating System:	Red Hat Enterprise Linux Server release 7.6, Kernel 3.10.0-957.el7.x86_64
Local File System:	xfs
Shared File System:	None
System State:	Multi-user, run level 3
Other Software:	None

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR950
(Intel Xeon Platinum 8280L CPU, 2.70 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 28.6

MPI2007 license: 28
Test sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test date: Mar-2019
Hardware Availability: Apr-2019
Software Availability: Apr-2019

Node Description: ThinkSystem SR950

Interconnect Type: None

Interconnect Description: N/A

Hardware

Vendor:	N/A
Model:	N/A
Switch Model:	N/A
Number of Switches:	0
Number of Ports:	0
Data Rate:	N/A
Firmware:	N/A
Topology:	N/A
Primary Use:	N/A

Software

Submit Notes

```
The config file option 'submit' was used.
```

General Notes

```
MPI startup command:
  mpiexec command was used to start MPI jobs.

RAM configuration:
  Compute nodes have 2 x 16 GB RDIMM on each memory channel.

BIOS settings:
  Operating Mode : Maximum Performance Mode
  Intel Hyper-Threading Technology (SMT): Disabled
  SNC (Sub-NUMA Cluster): Enable


Yes: The test sponsor attests, as of date of publication,
that CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication,
that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication,
that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.
```

Base Compiler Invocation

C benchmarks:
`mpiicc`

C++ benchmarks:

126.lammps: `mpiicpc`

Fortran benchmarks:
`mpiifort`

Benchmarks using both Fortran and C:
`mpiicc mpiifort`

Base Portability Flags

121.pop2: `-DSPEC_MPI_CASE_FLAG`
126.lammps: `-DMPICH_IGNORE_CXX_SEEK`
127.wrf2: `-DSPEC_MPI_CASE_FLAG -DSPEC_MPI_LINUX`
130.socorro: `-assume nostd_intent_in`

Base Optimization Flags

C benchmarks:
`-O3 -ipo -xCORE-AVX512 -no-prec-div`

C++ benchmarks:

126.lammps: `-O3 -ipo -xCORE-AVX512 -no-prec-div`

Fortran benchmarks:
`-O3 -ipo -xCORE-AVX512 -no-prec-div`

Benchmarks using both Fortran and C:
`-O3 -ipo -xCORE-AVX512 -no-prec-div`

The flags files that were used to format this result can be browsed at
http://www.spec.org/mpi2007/flags/EM64T_Intel121_flags.20170711.html
http://www.spec.org/mpi2007/flags/Lenovo-SPECmpiM_Platform_Flags.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/mpi2007/flags/EM64T_Intel121_flags.20170711.xml
http://www.spec.org/mpi2007/flags/Lenovo-SPECmpiM_Platform_Flags.xml

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.1.
Report generated on Tue Apr 2 18:30:26 2019 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 2 April 2019.