SPEC® MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR665
(AMD EPYC 7H12, 2.6 GHz)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 29.1

MPI2007 license: 28
Test sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test date: Jan-2020
Hardware Availability: Jun-2020
Software Availability: Jun-2020



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
121.pop2	640	**133**	**29.2**	132	29.5	133	29.2							
122.tachyon	640	99.9	19.5	99.3	19.6	**99.5**	**19.5**							
125.RAxML	640	102	28.6	106	27.7	**102**	**28.5**							
126.lammps	640	113	21.8	111	22.2	**111**	**22.2**							
128.GAPgeofem	640	**148**	**40.2**	148	40.2	148	40.0							
129.tera_tf	640	57.4	19.1	**57.4**	**19.2**	55.8	19.7							
132.zeusmp2	640	**106**	**20.0**	105	20.1	106	20.0							
137.lu	640	73.2	57.4	**74.7**	**56.3**	74.7	56.3							
142.dmilc	640	**106**	**34.7**	107	34.6	106	34.7							
143.dleslie	640	65.6	47.3	66.5	46.6	**66.0**	**47.0**							
145.lGemsFDTD	640	187	23.6	188	23.4	**187**	**23.6**							
147.l2wrf2	640	**270**	**30.4**	270	30.4	271	30.3							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR665
(AMD EPYC 7H12, 2.6 GHz)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 29.1

MPI2007 license: 28
Test sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test date: Jan-2020
Hardware Availability: Jun-2020
Software Availability: Jun-2020

Hardware Summary

Type of System:	Homogeneous
Compute Node:	ThinkSystem SR665
Interconnect:	Mellanox ConnectX-6 HDR
File Server Node:	NFS
Total Compute Nodes:	5
Total Chips:	10
Total Cores:	640
Total Threads:	640
Total Memory:	5 TB
Base Ranks Run:	640
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

C Compiler:	Intel C++ Compiler 20.0 for Linux Version 19.1.0.166 Build 20191121
C++ Compiler:	Intel C++ Compiler 20.0 for Linux Version 19.1.0.166 Build 20191121
Fortran Compiler:	Intel Fortran Compiler 20.0 for Linux Version 19.1.0.166 Build 20191121
Base Pointers:	64-bit
Peak Pointers:	Not Applicable
MPI Library:	Open MPI Library Version 4.0.2
Other MPI Info:	None
Pre-processors:	No
Other Software:	None

Node Description: ThinkSystem SR665

Hardware

Number of nodes:	5
Uses of the node:	compute
Vendor:	Lenovo Global Technology
Model:	SR665
CPU Name:	AMD EPYC 7H12
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	128
Cores per chip:	64
Threads per core:	1
CPU Characteristics:	None
CPU MHz:	2600
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	512 KB I+D on chip per core
L3 Cache:	256 MB I+D on chip per chip 16 MB shared / 4 cores
Other Cache:	None
Memory:	1 TB (16 x 64 GB 2Rx4 PC4-3200AA-R)
Disk Subsystem:	1 x 480 GB SATA 2.5" SSD
Other Hardware:	None
Adapter:	Mellanox ConnectX-6 HDR Infiniband
Number of Adapters:	1
Slot Type:	PCI-Express 4.0 x16
Data Rate:	200 Gbs/s
Ports Used:	1
Interconnect Type:	Mellanox ConnectX-6 HDR Infiniband Adapter

Software

Adapter:	Mellanox ConnectX-6 HDR Infiniband
Adapter Driver:	4.7-1.0.0.1.2
Adapter Firmware:	20.25.2006
Operating System:	Red Hat Enterprise Linux Server release 8.1, 4.18.0-147.el8.x86_64
Local File System:	xfs
Shared File System:	None
System State:	Multi-user, run level 3
Other Software:	None

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR665
(AMD EPYC 7H12, 2.6 GHz)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 29.1

MPI2007 license: 28
Test sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test date: Jan-2020
Hardware Availability: Jun-2020
Software Availability: Jun-2020

Node Description: NFS

Hardware

Number of nodes:	1
Uses of the node:	Fileserver
Vendor:	Lenovo Global Technology
Model:	ThinkSystem SR665
CPU Name:	AMD EPYC 7H12 CPU
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	128
Cores per chip:	64
Threads per core:	1
CPU Characteristics:	None
CPU MHz:	2600
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	512 KB I+D on chip per core
L3 Cache:	256 MB I+D on chip per chip 16 MB shared / 4 cores
Other Cache:	None
Memory:	1 TB (16 x 64 GB 2Rx4 PC4-3200AA-R)
Disk Subsystem:	1 x 480 GB SATA 2.5" SSD
Other Hardware:	None
Adapter:	Mellanox ConnectX-6 HDR Infiniband
Number of Adapters:	1
Slot Type:	PCI-Express 4.0 x16
Data Rate:	200 Gb/s
Ports Used:	1
Interconnect Type:	Mellanox ConnectX-6 HDR Infiniband

Software

Adapter:	Mellanox ConnectX-6 HDR Infiniband
Adapter Driver:	4.7-1.0.0.1.2
Adapter Firmware:	20.25.2006
Operating System:	Red Hat Enterprise Linux Server release 8.1
Local File System:	None
Shared File System:	NFS
System State:	Multi-User, run level 3
Other Software:	None

Interconnect Description: Mellanox ConnectX-6 HDR

Hardware

Vendor:	Mellanox
Model:	Infiniband EDR 100Gb/s Switch
Switch Model:	SB7800 Series
Number of Switches:	1
Number of Ports:	36
Data Rate:	100 Gb/s
Firmware:	3.9.0300
Topology:	Mesh
Primary Use:	MPI Traffic

Software

Submit Notes

```
The config file option 'submit' was used.
```

General Notes

```
MPI startup command:
  mpiexec command was used to start MPI jobs.
RAM configuration:
  Compute nodes have 1 x 32 GB RDIMM on each memory channel.
Add "idle=poll" into grub
BIOS settings:
  Operating Mode : Maximum Performance Mode
  Hyper-Threading Technology (SMT): Enabled
  NPS4
Yes: The test sponsor attests, as of date of publication,
that CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication,
that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication,
that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.
```

Base Compiler Invocation

C benchmarks:
/opt/OMPI/O402_I20_H47_R81/bin/mpicc

C++ benchmarks:

126.lammps: /opt/OMPI/O402_I20_H47_R81/bin/mpicxx

Fortran benchmarks:
/opt/OMPI/O402_I20_H47_R81/bin/mpif90

Benchmarks using both Fortran and C:
/opt/OMPI/O402_I20_H47_R81/bin/mpicc
/opt/OMPI/O402_I20_H47_R81/bin/mpif90

Base Portability Flags

121.pop2: -DSPEC_MPI_CASE_FLAG
126.lammps: -DMPICH_IGNORE_CXX_SEEK

Base Optimization Flags

C benchmarks:
-O3 -march=core-avx2 -no-prec-div -ipo

C++ benchmarks:

126.lammps: -O3 -march=core-avx2 -no-prec-div -ipo

Continued on next page

Base Optimization Flags (Continued)

Fortran benchmarks:
`-O3 -march=core-avx2 -no-prec-div -ipo`

Benchmarks using both Fortran and C:
`-O3 -march=core-avx2 -no-prec-div -ipo`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/mpi2007/flags/EM64T_Intel121_flags.20200506.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/mpi2007/flags/EM64T_Intel121_flags.20200506.xml`

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.1.
Report generated on Wed May 6 11:57:18 2020 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 6 May 2020.