



SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR860 V2
(Intel Xeon Platinum 8380H CPU, 2.90 GHz)

SPECmpim_peak2007 = 86.1

SPECmpim_base2007 = 84.7

MPI2007 license: 28


Test sponsor: Lenovo Global Technology

Tested by: Lenovo Global Technology

Test date: Oct-2020

Hardware Availability: Oct-2020

Software Availability: Oct-2020



Results Table

Benchmark	Base								Peak							
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
104.milc	336	23.9	65.5	23.8	65.6	<u>23.9</u>	<u>65.5</u>	336	<u>23.8</u>	<u>65.7</u>	23.8	65.8	23.9	65.6		
107.leslie3d	336	57.9	90.2	<u>58.2</u>	<u>89.6</u>	58.4	89.4	336	58.3	89.6	57.9	90.2	<u>58.0</u>	<u>89.9</u>		
113.GemsFDTD	336	172	36.8	171	36.8	<u>171</u>	<u>36.8</u>	224	135	46.9	134	47.1	<u>134</u>	<u>47.0</u>		
115.fds4	336	22.1	88.2	20.7	94.2	<u>21.2</u>	<u>92.1</u>	336	22.0	88.8	<u>21.9</u>	<u>89.2</u>	20.7	94.3		
121.pop2	336	73.8	55.9	74.1	55.7	<u>73.9</u>	<u>55.9</u>	336	73.7	56.0	<u>73.8</u>	<u>56.0</u>	73.8	56.0		
122.tachyon	336	47.8	58.5	48.0	58.3	<u>47.8</u>	<u>58.5</u>	336	47.8	58.6	<u>47.9</u>	<u>58.4</u>	48.0	58.3		
126.lammps	336	76.9	37.9	76.7	38.0	<u>76.7</u>	<u>38.0</u>	336	<u>76.7</u>	<u>38.0</u>	76.7	38.0	76.7	38.0		
127.wrf2	336	48.5	161	48.3	161	<u>48.3</u>	<u>161</u>	336	48.6	160	48.1	162	<u>48.5</u>	<u>161</u>		
128.GAPgeofem	336	<u>11.4</u>	<u>181</u>	11.4	181	11.5	179	336	11.4	181	<u>11.4</u>	<u>181</u>	11.4	181		
129.tera_tf	336	29.2	94.8	29.9	92.4	<u>29.3</u>	<u>94.6</u>	336	29.2	94.9	<u>29.2</u>	<u>94.8</u>	29.3	94.6		

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR860 V2
(Intel Xeon Platinum 8380H CPU, 2.90 GHz)

SPECmpim_peak2007 = 86.1

SPECmpim_base2007 = 84.7

MPI2007 license: 28
Test sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test date: Oct-2020
Hardware Availability: Oct-2020
Software Availability: Oct-2020

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
130.socorro	336	39.8	95.8	40.0	95.4	40.1	95.3	336	40.2	95.0	39.9	95.6	40.0	95.3
132.zeusmp2	336	25.7	121	25.6	121	25.6	121	336	25.6	121	25.6	121	25.6	121
137.lu	336	25.1	147	25.0	147	25.0	147	336	25.0	147	25.1	147	25.0	147

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System: Homogeneous
 Compute Node: ThinkSystem SR860 V2
 Interconnect: Nvidia Mellanox ConnectX-6 HDR Infiniband
 File Server Node: NFS
 Total Compute Nodes: 3
 Total Chips: 12
 Total Cores: 336
 Total Threads: 336
 Total Memory: 4608 GB
 Base Ranks Run: 336
 Minimum Peak Ranks: 224
 Maximum Peak Ranks: 336

Software Summary

C Compiler: Intel Parallel Studio C Compiler 20 Update 2 for Linux
 Version 19.1.2.254 Build 20200623
 C++ Compiler: Intel Parallel Studio C++ Compiler 20 Update 2 for Linux
 Version 19.1.2.254 Build 20200623
 Fortran Compiler: Intel Parallel Studio Fortran Compiler 20 Update 2 for Linux
 Version 19.1.2.254 Build 20200623
 Base Pointers: 64-bit
 Peak Pointers: Not Applicable
 MPI Library: Intel Parallel Studio MPI Library for Linux* OS
 Version 2020 Update 2 Build 20200624
 Other MPI Info: None
 Pre-processors: No
 Other Software: None

Node Description: ThinkSystem SR860 V2

Hardware

Number of nodes: 3
 Uses of the node: compute
 Vendor: Lenovo Global Technology
 Model: ThinkSystem SR860 V2
 CPU Name: Intel Xeon Platinum 8380H
 CPU(s) orderable: 2,4 chips
 Chips enabled: 4
 Cores enabled: 112
 Cores per chip: 28
 Threads per core: 1
 CPU Characteristics: Intel Turbo Boost Technology up to 4.3 GHz
 CPU MHz: 2900
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core
 L3 Cache: 39424 KB I+D on chip per chip
 Other Cache: None
 Memory: 1536 GB (48 x 32 GB 2Rx8 PC4-3200AA-R)
 Disk Subsystem: 1 x 1 TB SATA 2.5" SSD
 Other Hardware: N/A
 Adapter: Nvidia Mellanox ConnectX-6 HDR Infiniband
 Number of Adapters: 1

Software

Adapter: Nvidia Mellanox ConnectX-6 HDR Infiniband
 Adapter Driver: 5.1-0.6.6
 Adapter Firmware: 20.25.2006
 Operating System: SUSE Linux Enterprise Server 15 SP2
 5.3.18-22-default
 Local File System: xfs
 Shared File System: None
 System State: Multi-user, run level 3
 Other Software: None

Continued on next page



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

SPECmpim_peak2007 = 86.1

ThinkSystem SR860 V2
(Intel Xeon Platinum 8380H CPU, 2.90 GHz)

SPECmpim_base2007 = 84.7

MPI2007 license: 28

Test date: Oct-2020

Test sponsor: Lenovo Global Technology

Hardware Availability: Oct-2020

Tested by: Lenovo Global Technology

Software Availability: Oct-2020

Node Description: ThinkSystem SR860 V2

Slot Type:	PCI-Express 3.0 x16
Data Rate:	200 Gb/s
Ports Used:	1
Interconnect Type:	Nvidia Mellanox ConnectX-6 HDR Infiniband

Node Description: NFS

Hardware

Number of nodes:	1
Uses of the node:	Fileserver
Vendor:	Lenovo Global Technology
Model:	ThinkSystem SR860 V2
CPU Name:	Intel Xeon Platinum 8380H
CPU(s) orderable:	2,4 chips
Chips enabled:	4
Cores enabled:	112
Cores per chip:	28
Threads per core:	1
CPU Characteristics:	Intel Turbo Boost Technology up to 4.3 GHz
CPU MHz:	2900
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per core
L3 Cache:	39424 KB I+D on chip per chip
Other Cache:	None
Memory:	1536 GB (48 x 32 GB 2Rx8 PC4-3200AA-R)
Disk Subsystem:	1 x 1 TB SATA 2.5" SSD
Other Hardware:	None
Adapter:	Nvidia Mellanox ConnectX-6 HDR Infiniband
Number of Adapters:	1
Slot Type:	PCI-Express 3.0 x16
Data Rate:	200 Gb/s
Ports Used:	1
Interconnect Type:	Nvidia Mellanox ConnectX-6 HDR Infiniband

Software

Adapter:	Nvidia Mellanox ConnectX-6 HDR Infiniband
Adapter Driver:	5.1-0.6.6
Adapter Firmware:	20.25.2006
Operating System:	SUSE Linux Enterprise Server 15 SP2
Local File System:	None
Shared File System:	NFS
System State:	Multi-User, run level 3
Other Software:	None

Interconnect Description: Nvidia Mellanox ConnectX-6 HDR Infiniband

Hardware

Vendor:	Nvidia
Model:	Nvidia Mellanox ConnectX-6 HDR Infiniband
Switch Model:	Nvidia Mellanox QM8700
Number of Switches:	1
Number of Ports:	40
Data Rate:	200 Gb/s
Firmware:	3.9.0606
Topology:	Mesh

Software

Continued on next page



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR860 V2
(Intel Xeon Platinum 8380H CPU, 2.90 GHz)

SPECmpiM_peak2007 = 86.1

SPECmpiM_base2007 = 84.7

MPI2007 license: 28

Test sponsor: Lenovo Global Technology

Tested by: Lenovo Global Technology

Test date: Oct-2020

Hardware Availability: Oct-2020

Software Availability: Oct-2020

Interconnect Description: Nvidia Mellanox ConnectX-6 HDR Infiniband

Primary Use: MPI and I/O traffic

Submit Notes

The config file option 'submit' was used.

General Notes

MPI startup command:
mpiexec command was used to start MPI jobs.

RAM configuration:
Compute nodes have 2 x 32 GB RDIMM on each memory channel.

BIOS settings:
Operating Mode : Maximum Performance Mode
Intel Hyper-Threading Technology (SMT): Disabled
SNC (Sub-NUMA Cluster): Enable

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.

Compiler Invocation

C benchmarks:
mpiicc

C++ benchmarks:
126.lammps: mpiicpc

Fortran benchmarks:
mpiifort

Benchmarks using both Fortran and C:
mpiicc mpiifort



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR860 V2
(Intel Xeon Platinum 8380H CPU, 2.90 GHz)

SPECmpiM_peak2007 = 86.1

SPECmpiM_base2007 = 84.7

MPI2007 license: 28

Test sponsor: Lenovo Global Technology

Tested by: Lenovo Global Technology

Test date: Oct-2020

Hardware Availability: Oct-2020

Software Availability: Oct-2020

Portability Flags

121.pop2: -DSPEC_MPI_CASE_FLAG
126.lammps: -DMPICH_IGNORE_CXX_SEEK
127.wrf2: -DSPEC_MPI_CASE_FLAG -DSPEC_MPI_LINUX
130.socorro: -assume nostd_intent_in

Optimization Flags

C benchmarks:

-O3 -ipo -xCORE-AVX512 -no-prec-div

C++ benchmarks:

126.lammps: -O3 -ipo -xCORE-AVX512 -no-prec-div

Fortran benchmarks:

-O3 -ipo -xCORE-AVX512 -no-prec-div

Benchmarks using both Fortran and C:

-O3 -ipo -xCORE-AVX512 -no-prec-div

The flags files that were used to format this result can be browsed at

http://www.spec.org/mpi2007/flags/EM64T_Intel121_flags.20201007.html

http://www.spec.org/mpi2007/flags/Lenovo-SPECmpiM_Platform_Flags.html

You can also download the XML flags sources by saving the following links:

http://www.spec.org/mpi2007/flags/EM64T_Intel121_flags.20201007.xml

http://www.spec.org/mpi2007/flags/Lenovo-SPECmpiM_Platform_Flags.xml

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.1.

Report generated on Wed Nov 4 16:31:43 2020 by SPEC MPI2007 PS/PDF formatter v1463.

Originally published on 4 November 2020.