SPEC® MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR860 V2
(Intel Xeon Platinum 8380H CPU, 2.90 GHz)

SPECmpiL_peak2007 = 28.1

SPECmpiL_base2007 = 28.1

MPI2007 license: 28
Test sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test date: Oct-2020
Hardware Availability: Oct-2020
Software Availability: Oct-2020



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
121.pop2	448	169	23.1	**169**	**23.0**	171	22.8	448	169	23.1	**169**	**23.0**	171	22.8
122.tachyon	448	**216**	**9.02**	216	8.99	215	9.03	448	**216**	**9.02**	216	8.99	215	9.03
125.RAxML	448	**115**	**25.4**	115	25.3	115	25.4	448	**115**	**25.4**	115	25.3	115	25.4
126.lammps	448	**120**	**20.5**	120	20.5	120	20.4	448	**120**	**20.5**	120	20.5	120	20.4
128.GAPgeofem	448	103	57.8	**103**	**57.5**	103	57.5	448	103	57.8	**103**	**57.5**	103	57.5
129.tera_tf	448	**59.7**	**18.4**	59.7	18.4	60.1	18.3	448	**59.7**	**18.4**	59.7	18.4	60.1	18.3
132.zeusmp2	448	78.8	26.9	**78.8**	**26.9**	78.9	26.9	448	78.8	26.9	**78.8**	**26.9**	78.9	26.9
137.lu	448	70.7	59.5	70.9	59.3	**70.7**	**59.4**	448	70.7	59.5	70.9	59.3	**70.7**	**59.4**
142.dmilc	448	**92.5**	**39.8**	92.5	39.8	92.4	39.9	448	**92.5**	**39.8**	92.5	39.8	92.4	39.9
143.dleslie	448	69.4	44.7	**69.7**	**44.5**	70.0	44.3	448	69.4	44.7	**69.7**	**44.5**	70.0	44.3
145.lGemsFDTD	448	176	25.1	**176**	**25.1**	176	25.1	448	176	25.1	**176**	**25.1**	176	25.1
147.l2wrf2	448	278	29.5	**277**	**29.6**	275	29.8	448	278	29.5	**277**	**29.6**	275	29.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR860 V2
(Intel Xeon Platinum 8380H CPU, 2.90 GHz)

SPECmpiL_peak2007 = 28.1

SPECmpiL_base2007 = 28.1

MPI2007 license: 28
Test sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test date: Oct-2020
Hardware Availability: Oct-2020
Software Availability: Oct-2020

Hardware Summary

Type of System:	Homogeneous
Compute Node:	ThinkSystem SR860 V2
Interconnect:	Nvidia Mellanox ConnectX-6 HDR Infiniband
File Server Node:	NFS
Total Compute Nodes:	4
Total Chips:	16
Total Cores:	448
Total Threads:	448
Total Memory:	6 TB
Base Ranks Run:	448
Minimum Peak Ranks:	448
Maximum Peak Ranks:	448

Software Summary

C Compiler:	Intel Parallel Studio C Compiler 20 Update 2 for Linux Version 19.1.2.254 Build 20200623
C++ Compiler:	Intel Parallel Studio C++ Compiler 20 Update 2 for Linux Version 19.1.2.254 Build 20200623
Fortran Compiler:	Intel Parallel Studio Fortran Compiler 20 Update 2 for Linux Version 19.1.2.254 Build 20200623
Base Pointers:	64-bit
Peak Pointers:	Not Applicable
MPI Library:	Intel Parallel Studio MPI Library for Linux* OS Version 2020 Update 2 Build 20200624
Other MPI Info:	None
Pre-processors:	No
Other Software:	None

Node Description: ThinkSystem SR860 V2

Hardware

Number of nodes:	4
Uses of the node:	compute
Vendor:	Lenovo Global Technology
Model:	ThinkSystem SR860 V2
CPU Name:	Intel Xeon Platinum 8380H
CPU(s) orderable:	2,4 chips
Chips enabled:	4
Cores enabled:	112
Cores per chip:	28
Threads per core:	1
CPU Characteristics:	Intel Turbo Boost Technology up to 4.3 GHz
CPU MHz:	2900
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per core
L3 Cache:	39424 KB I+D on chip per chip
Other Cache:	None
Memory:	1536 GB (48 x 32 GB 2Rx8 PC4-3200AA-R)
Disk Subsystem:	1 x 1 TB SATA 2.5" SSD
Other Hardware:	N/A
Adapter:	Nvidia Mellanox ConnectX-6 HDR Infiniband
Number of Adapters:	1
Slot Type:	PCI-Express 3.0 x16
Data Rate:	200 Gb/s
Ports Used:	1
Interconnect Type:	Nvidia Mellanox ConnectX-6 HDR Infiniband

Software

Adapter:	Nvidia Mellanox ConnectX-6 HDR Infiniband
Adapter Driver:	5.1-0.6.6
Adapter Firmware:	20.25.2006
Operating System:	SUSE Linux Enterprise Server 15 SP2 5.3.18-22-default
Local File System:	xfs
Shared File System:	None
System State:	Multi-user, run level 3
Other Software:	None

SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR860 V2
(Intel Xeon Platinum 8380H CPU, 2.90 GHz)

SPECmpiL_peak2007 = 28.1

SPECmpiL_base2007 = 28.1

MPI2007 license: 28
Test sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test date: Oct-2020
Hardware Availability: Oct-2020
Software Availability: Oct-2020

Node Description: NFS

Hardware

Number of nodes:	1
Uses of the node:	Fileserver
Vendor:	Lenovo Global Technology
Model:	ThinkSystem SR860 V2
CPU Name:	Intel Xeon Platinum 8380H
CPU(s) orderable:	2,4 chips
Chips enabled:	4
Cores enabled:	112
Cores per chip:	28
Threads per core:	1
CPU Characteristics:	Intel Turbo Boost Technology up to 4.3 GHz
CPU MHz:	2900
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per core
L3 Cache:	39424 KB I+D on chip per chip
Other Cache:	None
Memory:	1536 GB (48 x 32 GB 2Rx8 PC4-3200AA-R)
Disk Subsystem:	1 x 1 TB SATA 2.5" SSD
Other Hardware:	None
Adapter:	Nvidia Mellanox ConnectX-6 HDR Infiniband
Number of Adapters:	1
Slot Type:	PCI-Express 3.0 x16
Data Rate:	200 Gb/s
Ports Used:	1
Interconnect Type:	Nvidia Mellanox ConnectX-6 HDR Infiniband

Software

Adapter:	Nvidia Mellanox ConnectX-6 HDR Infiniband
Adapter Driver:	5.1-0.6.6
Adapter Firmware:	20.25.2006
Operating System:	SUSE Linux Enterprise Server 15 SP2
Local File System:	None
Shared File System:	NFS
System State:	Multi-User, run level 3
Other Software:	None

Interconnect Description: Nvidia Mellanox ConnectX-6 HDR Infiniband

Hardware

Vendor:	Nvidia
Model:	Nvidia Mellanox ConnectX-6 HDR Infiniband
Switch Model:	Nvidia Mellanox QM8700
Number of Switches:	1
Number of Ports:	40
Data Rate:	200 Gb/s
Firmware:	3.9.0606
Topology:	Mesh
Primary Use:	MPI and I/O traffic

Software

Submit Notes

```
The config file option 'submit' was used.
```

General Notes

```
MPI startup command:
  mpiexec command was used to start MPI jobs.

RAM configuration:
  Compute nodes have 2 x 32 GB RDIMM on each memory channel.

BIOS settings:
  Operating Mode : Maximum Performance Mode
  Intel Hyper-Threading Technology (SMT): Disabled
  SNC (Sub-NUMA Cluster): Enable


Yes: The test sponsor attests, as of date of publication,
that CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication,
that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication,
that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.
```

Base Compiler Invocation

C benchmarks:
`mpiicc`

C++ benchmarks:

126.lammps: `mpiicpc`

Fortran benchmarks:
`mpiifort`

Benchmarks using both Fortran and C:
`mpiicc mpiifort`

Base Portability Flags

121.pop2: `-DSPEC_MPI_CASE_FLAG`
126.lammps: `-DMPICH_IGNORE_CXX_SEEK`

Base Optimization Flags

C benchmarks:
`-O3 -ipo -xCORE-AVX512 -no-prec-div`

Continued on next page

Base Optimization Flags (Continued)

C++ benchmarks:

126.lammps: `-O3 -ipo -xCORE-AVX512 -no-prec-div`

Fortran benchmarks:
`-O3 -ipo -xCORE-AVX512 -no-prec-div`

Benchmarks using both Fortran and C:
`-O3 -ipo -xCORE-AVX512 -no-prec-div`

Peak Optimization Flags

C benchmarks:

122.tachyon: `basepeak = yes`

125.RAxML: `basepeak = yes`

142.dmilc: `basepeak = yes`

C++ benchmarks:

126.lammps: `basepeak = yes`

Fortran benchmarks:

129.tera_tf: `basepeak = yes`

137.lu: `basepeak = yes`

143.dleslie: `basepeak = yes`

145.lGemsFDTD: `basepeak = yes`

Benchmarks using both Fortran and C:

121.pop2: `basepeak = yes`

128.GAPgeofem: `basepeak = yes`

132.zeusmp2: `basepeak = yes`

147.l2wrf2: `basepeak = yes`

The flags files that were used to format this result can be browsed at
`http://www.spec.org/mpi2007/flags/EM64T_Intel121_flags.20201007.html`
`http://www.spec.org/mpi2007/flags/Lenovo-SPECmpiM_Platform_Flags.html`

You can also download the XML flags sources by saving the following links:

http://www.spec.org/mpi2007/flags/EM64T_Intel121_flags.20201007.xml
http://www.spec.org/mpi2007/flags/Lenovo-SPECmpiM_Platform_Flags.xml

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.1.
Report generated on Wed Nov 4 16:32:02 2020 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 4 November 2020.