SPEC® MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR655
(AMD EPYC 7763, 2.45 GHz)

SPECmpiL_peak2007 = 3.23

SPECmpiL_base2007 = 3.23

MPI2007 license: 28
Test sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test date: Mar-2021
Hardware Availability: Jun-2021
Software Availability: Jun-2021



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
121.pop2	64	1117	3.48	**1118**	**3.48**			64	1117	3.48	**1118**	**3.48**		
122.tachyon	64	717	2.71	**724**	**2.69**			64	717	2.71	**724**	**2.69**		
125.RAxML	64	**919**	**3.18**	914	3.19			64	**919**	**3.18**	914	3.19		
126.lammps	64	897	2.74	**899**	**2.73**			64	897	2.74	**899**	**2.73**		
128.GAPgeofem	64	1394	4.26	**1395**	**4.26**			64	1394	4.26	**1395**	**4.26**		
129.tera_tf	64	325	3.39	**325**	**3.38**			64	325	3.39	**325**	**3.38**		
132.zeusmp2	64	670	3.17	**671**	**3.16**			64	670	3.17	**671**	**3.16**		
137.lu	64	1149	3.66	**1152**	**3.65**			64	1149	3.66	**1152**	**3.65**		
142.dmilc	64	**910**	**4.05**	909	4.05			64	**910**	**4.05**	909	4.05		
143.dleslie	64	**895**	**3.46**	894	3.47			64	**895**	**3.46**	894	3.47		
145.lGemsFDTD	64	1707	2.58	**1716**	**2.57**			64	1707	2.58	**1716**	**2.57**		
147.l2wrf2	64	3104	2.64	**3105**	**2.64**			64	3104	2.64	**3105**	**2.64**		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR655
(AMD EPYC 7763, 2.45 GHz)

SPECmpiL_peak2007 = 3.23

SPECmpiL_base2007 = 3.23

MPI2007 license: 28
Test sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test date: Mar-2021
Hardware Availability: Jun-2021
Software Availability: Jun-2021

Hardware Summary

Type of System:	Homogeneous
Compute Node:	ThinkSystem SR655
Interconnect:	Mellanox ConnectX-6 HDR
File Server Node:	NFS
Total Compute Nodes:	1
Total Chips:	1
Total Cores:	64
Total Threads:	64
Total Memory:	256 GB
Base Ranks Run:	64
Minimum Peak Ranks:	64
Maximum Peak Ranks:	64

Software Summary

C Compiler:	Intel C Compiler 20.4 for Linux Version 19.1.3.304 Build 20200925
C++ Compiler:	Intell C++ Compiler 20.4 for Linux Version 19.1.3.304 Build 20200925
Fortran Compiler:	Intel Fortran Compiler 20.4 for Linux Version 19.1.3.304 Build 20200925
Base Pointers:	64-bit
Peak Pointers:	Not Applicable
MPI Library:	Intel MPI Library for Linux Version 2019 Update 11 Build 20210330
Other MPI Info:	None
Pre-processors:	No
Other Software:	None

Node Description: ThinkSystem SR655

Hardware

Number of nodes:	1
Uses of the node:	compute
Vendor:	Lenovo Global Technology
Model:	SR655
CPU Name:	AMD EPYC 7763
CPU(s) orderable:	1 chips
Chips enabled:	1
Cores enabled:	64
Cores per chip:	64
Threads per core:	1
CPU Characteristics:	Turbo up to 3.5 GHz
CPU MHz:	2450
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	512 KB I+D on chip per core
L3 Cache:	256 MB I+D on chip per chip 32 MB shared / 8 cores
Other Cache:	None
Memory:	256 GB (8 x 32 GB 2Rx8 PC4-3200AA-R)
Disk Subsystem:	1 x 480 GB SATA 2.5" SSD
Other Hardware:	None
Adapter:	Mellanox ConnectX-6 HDR Infiniband
Number of Adapters:	1
Slot Type:	PCI-Express 4.0 x16
Data Rate:	200 Gbs/s
Ports Used:	1
Interconnect Type:	Mellanox ConnectX-6 HDR Infiniband Adapter

Software

Adapter:	Mellanox ConnectX-6 HDR Infiniband
Adapter Driver:	5.2-1.0.4
Adapter Firmware:	20.25.2006
Operating System:	Red Hat Enterprise Linux Server release 8.3 4.18.0-240.el8.x86_64
Local File System:	xfs
Shared File System:	None
System State:	Multi-user, run level 3
Other Software:	None

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR655
(AMD EPYC 7763, 2.45 GHz)

SPECmpiL_peak2007 = 3.23

SPECmpiL_base2007 = 3.23

MPI2007 license: 28
Test sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test date: Mar-2021
Hardware Availability: Jun-2021
Software Availability: Jun-2021

Node Description: NFS

Hardware

Number of nodes:	1
Uses of the node:	Fileserver
Vendor:	Lenovo Global Technology
Model:	ThinkSystem SR655
CPU Name:	AMD EPYC 7763 CPU
CPU(s) orderable:	1 chips
Chips enabled:	1
Cores enabled:	64
Cores per chip:	64
Threads per core:	1
CPU Characteristics:	None
CPU MHz:	2450
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	512 KB I+D on chip per core
L3 Cache:	256 MB I+D on chip per chip 32 MB shared / 8 cores
Other Cache:	None
Memory:	256 GB (8 x 32 GB 2Rx4 PC4-3200AA-R)
Disk Subsystem:	1 x 480 GB SATA 2.5" SSD
Other Hardware:	None
Adapter:	Mellanox ConnectX-6 HDR Infiniband
Number of Adapters:	1
Slot Type:	PCI-Express 4.0 x16
Data Rate:	200 Gb/s
Ports Used:	1
Interconnect Type:	Mellanox ConnectX-6 HDR Infiniband

Software

Adapter:	Mellanox ConnectX-6 HDR Infiniband
Adapter Driver:	5.2-1.0.4
Adapter Firmware:	20.25.2006
Operating System:	Red Hat Enterprise Linux Server release 8.3
Local File System:	None
Shared File System:	NFS
System State:	Multi-User, run level 3
Other Software:	None

Interconnect Description: Mellanox ConnectX-6 HDR

Hardware

Vendor:	Mellanox
Model:	Infiniband HDR 200Gb/s Switch
Switch Model:	QM8700 Series
Number of Switches:	1
Number of Ports:	40
Data Rate:	200 Gb/s
Firmware:	3.9.0606
Topology:	Mesh
Primary Use:	MPI Traffic

Software

Submit Notes

```
The config file option 'submit' was used.
```

General Notes

```
MPI startup command:
  mpiexec command was used to start MPI jobs.
RAM configuration:
  Compute nodes have 1 x 32 GB RDIMM on each memory channel.
Add "idle=poll" into grub
BIOS settings:
  Operating Mode : Maximum Performance Mode
  Hyper-Threading Technology (SMT): Disabled
  NPS4
Yes: The test sponsor attests, as of date of publication,
that CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication,
that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication,
that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.
```

Base Compiler Invocation

C benchmarks:
`mpiicc`

C++ benchmarks:

126.lammps: `mpiicpc`

Fortran benchmarks:
`mpiifort`

Benchmarks using both Fortran and C:
`mpiicc mpiifort`

Base Portability Flags

121.pop2: `-DSPEC_MPI_CASE_FLAG`
126.lammps: `-DMPICH_IGNORE_CXX_SEEK`

Base Optimization Flags

C benchmarks:
`-O3 -march=core-avx2 -no-prec-div -ipo`

C++ benchmarks:

126.lammps: `-O3 -march=core-avx2 -no-prec-div -ipo`

Continued on next page

Base Optimization Flags (Continued)

Fortran benchmarks:
`-O3 -march=core-avx2 -no-prec-div -ipo`

Benchmarks using both Fortran and C:
`-O3 -march=core-avx2 -no-prec-div -ipo`

Peak Optimization Flags

C benchmarks:

122.tachyon: `basepeak = yes`

125.RAxML: `basepeak = yes`

142.dmilc: `basepeak = yes`

C++ benchmarks:

126.lammps: `basepeak = yes`

Fortran benchmarks:

129.tera_tf: `basepeak = yes`

137.lu: `basepeak = yes`

143.dleslie: `basepeak = yes`

145.lGemsFDTD: `basepeak = yes`

Benchmarks using both Fortran and C:

121.pop2: `basepeak = yes`

128.GAPgeofem: `basepeak = yes`

132.zeusmp2: `basepeak = yes`

147.l2wrf2: `basepeak = yes`

The flags files that were used to format this result can be browsed at
`http://www.spec.org/mpi2007/flags/Lenovo_Platform_Flags.html`
`http://www.spec.org/mpi2007/flags/EM64T_Intel121_flags.20200506.01.html`

You can also download the XML flags sources by saving the following links:
`http://www.spec.org/mpi2007/flags/Lenovo_Platform_Flags.xml`
`http://www.spec.org/mpi2007/flags/EM64T_Intel121_flags.20200506.01.xml`

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.1.
Report generated on Tue Jun 8 10:02:20 2021 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 8 June 2021.