SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Supermicro

Hyper A+ Server AS -2126HS-TN (AMD EPYC 9755)

SPECmpiM_peak2007 = 96.6

SPECmpiM_base2007 = 96.6

MPI2007 license: 6569
Test sponsor: Supermicro
Tested by: Supermicro

Test date: Sep-2024
Hardware Availability: Oct-2024
Software Availability: Apr-2024



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	256	18.5	84.6	**18.4**	**85.1**	18.3	85.6	256	18.5	84.6	**18.4**	**85.1**	18.3	85.6
107.leslie3d	256	61.4	85.0	**61.5**	**84.9**	61.9	84.4	256	61.4	85.0	**61.5**	**84.9**	61.9	84.4
113.GemsFDTD	256	104	60.7	**104**	**60.6**	104	60.5	256	104	60.7	**104**	**60.6**	104	60.5
115.fds4	256	13.9	141	**13.9**	**140**	13.9	140	256	13.9	141	**13.9**	**140**	13.9	140
121.pop2	256	**61.5**	**67.2**	61.6	67.0	61.3	67.4	256	**61.5**	**67.2**	61.6	67.0	61.3	67.4
122.tachyon	256	30.2	92.6	**29.4**	**95.0**	29.4	95.1	256	30.2	92.6	**29.4**	**95.0**	29.4	95.1
126.lammps	256	**64.2**	**45.4**	64.2	45.4	64.1	45.5	256	**64.2**	**45.4**	64.2	45.4	64.1	45.5
127.wrf2	256	**42.1**	**185**	42.5	183	42.1	185	256	**42.1**	**185**	42.5	183	42.1	185
128.GAPgeofem	256	14.1	147	14.0	147	**14.0**	**147**	256	14.1	147	14.0	147	**14.0**	**147**
129.tera_tf	256	24.4	114	24.4	114	**24.4**	**114**	256	24.4	114	24.4	114	**24.4**	**114**

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Supermicro

Hyper A+ Server AS -2126HS-TN (AMD EPYC 9755)

SPECmpiM_peak2007 = 96.6

SPECmpiM_base2007 = 96.6

MPI2007 license: 6569
Test sponsor: Supermicro
Tested by: Supermicro

Test date: Sep-2024
Hardware Availability: Oct-2024
Software Availability: Apr-2024

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
130.socorro	256	37.6	102	**37.6**	**101**	38.5	99.1	256	37.6	102	**37.6**	**101**	38.5	99.1
132.zeusmp2	256	33.0	93.9	**33.0**	**94.0**	33.0	94.0	256	33.0	93.9	**33.0**	**94.0**	33.0	94.0
137.lu	256	30.4	121	**30.4**	**121**	30.4	121	256	30.4	121	**30.4**	**121**	30.4	121

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System:	Homogeneous
Compute Node:	Hyper A+ Server AS -2126HS-TN
Total Compute Nodes:	1
Total Chips:	2
Total Cores:	256
Total Threads:	256
Total Memory:	1536 GB
Base Ranks Run:	256
Minimum Peak Ranks:	256
Maximum Peak Ranks:	256

Software Summary

C Compiler:	Intel oneAPI DPC++/C++ Compiler 2024.2.1
C++ Compiler:	Intel oneAPI DPC++/C++ Compiler 2024.2.1
Fortran Compiler:	Intel oneAPI DPC++/C++ Compiler 2024.2.1
Base Pointers:	64-bit
Peak Pointers:	64-bit
MPI Library:	Intel MPI Version 2021.13
Other MPI Info:	None
Pre-processors:	No
Other Software:	Jemalloc-5.3.0

Node Description: Hyper A+ Server AS -2126HS-TN

Hardware

Number of nodes:	1
Uses of the node:	compute
Vendor:	Supermicro
Model:	Hyper A+ Server AS -2126HS-TN
CPU Name:	AMD EPYC 9755
CPU(s) orderable:	1,2 chips
Chips enabled:	2
Cores enabled:	256
Cores per chip:	128
Threads per core:	1
CPU Characteristics:	Max. Boost Clock upto 4.1GHz
CPU MHz:	2700
Primary Cache:	32 KB I + 48 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per core
L3 Cache:	512 MB I+D on chip per chip, 32 MB shared / 8 cores
Other Cache:	None
Memory:	1536 GB (24 x 64 GB 2Rx4 PC5-6400B-R, running at 6000)
Disk Subsystem:	1 x 3.5 TB NVMe SSD
Other Hardware:	None
Adapter:	None
Number of Adapters:	1
Slot Type:	None
Data Rate:	None
Ports Used:	0

Continued on next page

Software

Adapter:	None
Adapter Driver:	None
Adapter Firmware:	None
Operating System:	Ubuntu 24.04 LTS 6.8.0-44-generic
Local File System:	ext4
Shared File System:	None
System State:	Multi-user, run level 3
Other Software:	None

Node Description: Hyper A+ Server AS -2126HS-TN

Interconnect Type: None	

Submit Notes

```
The config file option 'submit' was used.
mpiexec.hydra -bootstrap ssh -hosts localhost -genv I_MPI_COMPATIBILITY=3 -np $ranks -ppn $ranks $command
```

General Notes

```
MPI startup command:
  mpiexec.hydra command was used to start MPI jobs.
RAM configuration:
  Compute nodes have 1 x 64 GB RDIMM on each memory channel.
BIOS settings:
  SMT = Disabled
  NUMA nodes per socket = NPS4
  ACPI SRAT L3 Cache as NUMA Domain = Enabled
  Determinism Control = Manual
  Determinism Enable = Power
  xGMI Link Configuration = 4 xGMI Links
  4 Link xGMI max speed = 32Gbps
  TDP Control = Manual
  TDP = 500
  Package Power Limit Control = Manual
  Package Power Limit = 500
NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown)
is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1)
is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2)
is mitigated in the system as tested and documented.
```

Base Compiler Invocation

C benchmarks:
`mpiicc -cc=icx`

C++ benchmarks:

126.lammps: `mpiicpc -cxx=icpx`

Fortran benchmarks:
`mpiifort -fc=ifx`

Benchmarks using both Fortran and C:
`mpiicc -cc=icxmpiifort -fc=ifx`

Base Portability Flags

104.milc: -DSPEC_MPI_LP64
115.fds4: -DSPEC_MPI_LP64
121.pop2: -DSPEC_MPI_CASE_FLAG -DSPEC_MPI_LP64
122.tachyon: -DSPEC_MPI_LP64
126.lammps: -DMPICH_IGNORE_CXX_SEEK
127.wrf2: -DSPEC_MPI_CASE_FLAG -DSPEC_MPI_LINUX -DSPEC_MPI_LP64
128.GAPgeofem: -DSPEC_MPI_LP64
130.socorro: -DSPEC_MPI_LP64
132.zeusmp2: -DSPEC_MPI_LP64

Base Optimization Flags

C benchmarks:
-Ofast -ipo -march=skylake-avx512 -mtune=skylake-avx512 -ansi-alias

C++ benchmarks:

126.lammps: -Ofast -ipo -march=skylake-avx512 -mtune=skylake-avx512 -ansi-alias

Fortran benchmarks:
-Ofast -ipo -march=skylake-avx512 -mtune=skylake-avx512 -nostandard-realloc-lhs -align array64byte

Benchmarks using both Fortran and C:
-Ofast -ipo -march=skylake-avx512 -mtune=skylake-avx512 -ansi-alias -nostandard-realloc-lhs -align array64byte

Base Other Flags

C benchmarks:

104.milc: -Wno-implicit-function-declaration -Wno-implicit-int -limf -Wl,--rpath=/usr/local/lib -ljemalloc

122.tachyon: -limf -Wl,--rpath=/usr/local/lib -ljemalloc

C++ benchmarks:

126.lammps: -Wno-register -limf -Wl,--rpath=/usr/local/lib -ljemalloc

Fortran benchmarks:
-limf -Wl,--rpath=/usr/local/lib -ljemalloc

Benchmarks using both Fortran and C (except as noted below):
-limf -Wl,--rpath=/usr/local/lib -ljemalloc

Continued on next page

Base Other Flags (Continued)

127.wrf2: `-Wno-implicit-int -Wno-implicit-function-declaration -Wno-int-conversion -limf -Wl,--rpath=/usr/local/lib -ljemalloc`

128.GAPgeofem: `-Wno-implicit-function-declaration -Wno-implicit-int -limf -Wl,--rpath=/usr/local/lib -ljemalloc`

132.zeusmp2: `-Wno-implicit-function-declaration -limf -Wl,--rpath=/usr/local/lib -ljemalloc`

Peak Optimization Flags

C benchmarks:

104.milc: `basepeak = yes`

122.tachyon: `basepeak = yes`

C++ benchmarks:

126.lammps: `basepeak = yes`

Fortran benchmarks:

107.leslie3d: `basepeak = yes`

113.GemsFDTD: `basepeak = yes`

129.tera_tf: `basepeak = yes`

137.lu: `basepeak = yes`

Benchmarks using both Fortran and C:

115.fds4: `basepeak = yes`

121.pop2: `basepeak = yes`

127.wrf2: `basepeak = yes`

128.GAPgeofem: `basepeak = yes`

130.socorro: `basepeak = yes`

132.zeusmp2: `basepeak = yes`

The flags file that was used to format this result can be browsed at
http://www.spec.org/mpi2007/flags/Intel_compiler_flags_hpc.2024.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/mpi2007/flags/Intel_compiler_flags_hpc.2024.xml

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.1.
Report generated on Thu Oct 10 12:36:17 2024 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 10 October 2024.