OMPM2001 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

SGI
SGI Origin 300 32X 600MHz R14000A

SPECompMpeak2001 = 12628

SPECompMbase2001 = 11165

SPEC license #: HPG0014 | Tested by: SGI | Test site: SGI | Test date: Dec-2002 | Hardware Avail: May-2002 | Software Avail: Dec-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio
310.wupwise_m	6000	312	19210	312	19210
312.swim_m	6000	456	13154	456	13165
314.mgrid_m	7300	496	14721	498	14650
316.applu_m	4000	264	15149	215	18608
318.galgel_m	5100	615	8288	624	8171
320.equake_m	2600	266	9764	223	11664
324.apsi_m	3400	319	10655	249	13641
326.gafort_m	8700	854	10193	718	12118
328.fma3d_m	4600	623	7379	397	11578
330.art_m	6400	512	12506	466	13720
332.ammp_m	7000	952	7353	928	7546



Hardware

CPU:	R14000A
CPU MHz:	600
FPU:	Integrated
CPU(s) enabled:	32
CPU(s) orderable:	2-32
Primary Cache:	32KBI + 32KBD on chip
Secondary Cache:	4MB(I+D) off chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	32 GB
Disk Subsystem:	1 x 18 GB FC, 20x 18 GB (striped) FC
Other Hardware:	None

Software

OpenMP Threads:	32
Parallel:	OpenMP
Operating System:	IRIX 6.5.18f
Compiler:	MIPSpro 7.4 C, Fortran90
File System:	xfs
System State:	Single-user

Notes/Tuning Information

```
Baseline flags (C benchmarks): -64 -mp -Ofast=ip35
Baseline flags (Fortran benchmarks): -64 -mp -Ofast=ip35 -LNO:fusion=2
Portability Flags:
   318.galgel_m: -fixedform -extend_source

Peak flags:
310.wupwise_m: basepeak=true
312.swim_m: -64 -mp -Ofast=ip35 -LNO:fusion=2
314.mgrid_m: 64 -mp -Ofast=ip35 -LNO:fusion=2
316.applu_m: -64 -mp -Ofast=ip35 -LNO:prefetch=0:fusion=2 -CG:ld_latency=3
318.galgel_m: -64 -mp -Ofast=ip35
320.equake_m: -64 -mp -Ofast=ip35
324.apsi_m: -64 -mp -Ofast=ip35
326.gafort_m: -64 -mp -Ofast=ip35
328.fma3d_m: -64 -mp -Ofast=ip35 -bigp_off -LNO:prefetch=0 -CG:ld_latency=2 -OPT:goto=off
330.art_m: -64 -mp -Ofast=ip35
332.ammp_m: -64 -mp -Ofast=ip35

Baseline user environment:
   limit stacksize 512m
   OMP_NUM_THREADS=32
   OMP_DYNAMIC=FALSE
   MPC_GANG=OFF
```

Copyright ©1999-2002, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
   _DSM_MUSTRUN=

Peak user environment:
316.applu_m: PAGESIZE_DATA=4096, PAGESIZE_STACK=4096, _DSM_PLACEMENT=ROUND_ROBIN
318.galgel_m: _DSM_PLACEMENT=ROUND_ROBIN
324.apsi_m: PAGESIZE_DATA=4096, PAGESIZE_STACK=4096
332.ammp_m: PAGESIZE_DATA=1024, PAGESIZE_STACK=1024, _DSM_PLACEMENT=ROUND_ROBIN

Peak sources:
SPEC OMPL2001 source for 64bit systems modified for SPEC OMPM2001.
Available as SPEC OMPM2001 Source: ompm2001-srcl64bit-20020807.tar.gz.
For 314.mgrid_m, 320.equake_m, 326.gafort_m, 328.fma3d_m, and 330.art_m.


The following O/S parameters were set via systune:
   percent_totalmem_4m_pages = 25 ; percent_totalmem_1m_pages = 25
   percent_totalmem_256k_pages = 10 ; percent_totalmem_64k_pages = 10
```