OMPM2001 Result

Copyright ©1999-2008, Standard Performance Evaluation Corporation

IBM Corporation

IBM BladeCenter JS12 Express (3.8 GHz, 2 core, Red Hat)

SPECompMpeak2001 = 12885

SPECompMbase2001 = 12086

SPEC license #: HPG0005 | Tested by: IBM | Test site: Austin, TX | Test date: Feb-2008 | Hardware Avail: May-2008 | Software Avail: Nov-2007

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio
310.wupwise_m	6000	397	15119	389	15429
312.swim_m	6000	480	12496	476	12602
314.mgrid_m	7300	663	11005	663	11010
316.applu_m	4000	369	10838	327	12220
318.galgel_m	5100	339	15031	323	15791
320.equake_m	2600	152	17099	143	18208
324.apsi_m	3400	320	10635	320	10635
326.gafort_m	8700	799	10893	778	11180
328.fma3d_m	4600	677	6794	671	6858
330.art_m	6400	246	26068	170	37756
332.ammp_m	7000	1035	6762	997	7021



Hardware

CPU:	POWER6
CPU MHz:	3800
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip, 2 threads/core
CPU(s) orderable:	2 cores
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	4 MB I+D on chip per core
L3 Cache:	None
Other Cache:	None
Memory:	32 GB (8x4 GB)
Disk Subsystem:	1x73 GB SAS 15K RPM
Other Hardware:	None

Software

OpenMP Threads:	4
Parallel:	OpenMP
Operating System:	Red Hat Enterprise Linux Advanced Platform 5.1 for IBM POWER
Compiler:	IBM XL C/C++ Advanced Edition for Linux, V9.0 IBM XL Fortran Advanced Edition for Linux, V11.1
Other Software:	IBM Engineering and Scientific Subroutine Library for Linux on POWER, Version 4.3
File System:	ext3
System State:	Multi-User

Notes/Tuning Information

```
Portability Flags Variables
  -qfixed used in: 310.wupwise_m, 312.swim_m, 314.mgrid_m, 316.applu_m, 324.apsi_m
  -qfixed=80 used in: 318.galgel_m
  -qsuffix=f=f90 used in: 318.galgel_m 326.gafort_m, 328.fma3d_m

Base Flags
   C:        -O5 -q32 -qsmp=omp
   FORTRAN:  -O5 -q32 -qsmp=omp

Base & Peak Environment Flags:
  ENV_OMP_NUM_THREADS = 4
  ENV_OMP_DYNAMIC=FALSE
  ENV_XLSMPOPTS=SPINS=0:YIELDS=0:STACK=8000000:STARTPROC=0:STRIDE=1
  ENV_XLFRTEOPTS=intrinthds=1


Peak sources:
  SPEC OMPL2001 source for 32bit systems modified for SPEC OMPM2001 used
  with 312.swim_m, 316.applu_m, 320.equake_m, 326.gafort_m


Peak Flags
  -qsmp=omp used in all cases
```

Copyright ©1999-2008, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
    310.wupwise:    -O5 -q32
                    -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
    312.swim_m:     -O4 -q32
    314.mgrid_m:    -O3 -q64
    316.applu_m:    -O4 -q64
    318.galgel_m:   -O5 -q64 -qessl
                    -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
                    EXTRA_LIBS=-lesslsmp
                    ENV_HUGETLB_MORECORE=yes
    320.equake_m:   -O5 -q64 -qpdf1/pdf2 -qhot=arraypad -Q
                    ENV_HUGETLB_MORECORE=yes
                    ENV_LD_PRELOAD=libhugetlbfs.so
    324.apsi_m:     basepeak = 1
    326.gafort_m:   -O4 -q32
    328.fma3d_m:    -O5 -q64 -qhot=arraypad
    330.art_m:      -O3 -q32 -qhot=arraypad -Q
                    ENV_HUGETLB_MORECORE=yes
                    ENV_LD_PRELOAD=libhugetlbfs.so
    332.ammp_m:     -O5 -q64 -qhot=arraypad -Q
                    ENV_HUGETLB_MORECORE=yes
                    ENV_LD_PRELOAD=libhugetlbfs.so

 C:              IBM XL C for Linux invoked as xlc_r
 Fortran 90:     IBM XL Fortran for Linux invoked as xlf90_r

kernel release 2.6.18-53.el5.

ulimit -s (stack) set to unlimited.

System set to Enhanced mode when defining partition on HMC

Large pages reserved as follows by root user:
    echo 240 > /proc/sys/vm/nr_hugepages
System configured with libhugetlbfs library for application access to large pages

Use flags-description file IBM-20080408-Linux.txt
```