SPEC® OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

Colfax International

(Test Sponsor: Indiana University)

Intel Xeon Phi 7210, 1.30GHz,
SMT off, Turbo off, flat (MCDRAM Preferred)

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 7.19

OMP2012 license: 3440A
Test sponsor: Indiana University
Tested by: Indiana University

Test date: Aug-2016
Hardware Availability: Aug-2016
Software Availability: Apr-2016



Hardware

CPU Name:	Intel Xeon Phi 7210
CPU Characteristics:	Intel Turbo Boost Technology off, Simultaneous Multithreading (SMT) off
CPU MHz:	1300
CPU MHz Maximum:	1500
FPU:	Integrated
CPU(s) enabled:	64 cores, 1 chip, 64 cores/chip, 4 threads/core
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per two cores
L3 Cache:	None
Other Cache:	None
Memory:	96 GB (6 x 16 GB 2Rx8 PC4-2400T-REB-11, ECC)
Disk Subsystem:	Intel S3510 SSD 800GB, SATA3
Other Hardware:	None
Base Threads Run:	64

Continued on next page

Software

Operating System:	CentOS Linux release 7.2.1511 CentOS Linux release 7.2.1511 (Core) 3.10.0-327.13.1.el7.xppsl_1.3.3.151.x86_64
Compiler:	C/C++/Fortran: Version 16.0.3.210 of Intel Composer XE 2016 for Linux Build 20160415
Auto Parallel:	No
File System:	ext4
System State:	Runlevel 3 (multi-user with networking)
Base Pointers:	64-bit
Peak Pointers:	Not Applicable
Other Software:	None

SPEC OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

Colfax International

(Test Sponsor: Indiana University)

Intel Xeon Phi 7210, 1.30GHz,
SMT off, Turbo off, flat (MCDRAM Preferred)

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 7.19

OMP2012 license:3440A
Test sponsor: Indiana University
Tested by: Indiana University

Test date: Aug-2016
Hardware Availability: Aug-2016
Software Availability: Apr-2016

Minimum Peak Threads: --
Maximum Peak Threads: --

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
350.md	64	1071	4.32	**1069**	**4.33**	1067	4.34							
351.bwaves	64	318	14.2	**319**	**14.2**	320	14.1							
352.nab	64	**780**	**4.99**	781	4.98	780	4.99							
357.bt331	64	**603**	**7.86**	601	7.89	604	7.85							
358.botsalgn	64	1360	3.20	1359	3.20	**1359**	**3.20**							
359.botsspar	64	3338	1.57	3347	1.57	**3342**	**1.57**							
360.ilbdc	64	**286**	**12.5**	285	12.5	286	12.5							
362.fma3d	64	**719**	**5.28**	719	5.28	719	5.28							
363.swim	64	180	25.1	**180**	**25.2**	179	25.2							
367.imagick	64	982	7.16	985	7.14	**984**	**7.14**							
370.mgrid331	64	242	18.3	236	18.7	**237**	**18.7**							
371.applu331	64	**441**	**13.8**	439	13.8	443	13.7							
372.smithwa	64	584	9.18	**584**	**9.18**	585	9.16							
376.kdtree	64	1544	2.92	**1545**	**2.91**	1546	2.91							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The config file option 'submit' was used.
submit = numactl -p 1 $command
```

Platform Notes

```
Sysinfo program /home/lijunj/SPEC/omp2012-1.1-run/Docs/sysinfo
Revision 563 of 2016-06-10 (097295389cf6073d8c3b03fa376740a5)
running on knl1.uits.indiana.edu Thu Oct 13 16:12:58 2016

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/omp2012/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : Intel(R) Xeon Phi(TM) CPU 7210 @ 1.30GHz
      1 "physical id"s (chips)
      64 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 64
```

Continued on next page

Platform Notes (Continued)

```
        siblings  : 64
        physical 0: cores 0 1 2 3 6 7 10 11 12 13 14 15 18 19 20 21 22 23 24 25 26
        27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51
        52 53 56 57 58 59 60 61 62 63 64 65 68 69 70 71 72 73
     cache size : 1024 KB

  From /proc/meminfo
     MemTotal:       115216920 kB
     HugePages_Total:       0
     Hugepagesize:       2048 kB

  /usr/bin/lsb_release -d
     CentOS Linux release 7.2.1511 (Core)

  From /etc/*release* /etc/*version*
     centos-release: CentOS Linux release 7.2.1511 (Core)
     centos-release-upstream: Derived from Red Hat Enterprise Linux 7.2 (Source)
     os-release:
        NAME="CentOS Linux"
        VERSION="7 (Core)"
        ID="centos"
        ID_LIKE="rhel fedora"
        VERSION_ID="7"
        PRETTY_NAME="CentOS Linux 7 (Core)"
        ANSI_COLOR="0;31"
        CPE_NAME="cpe:/o:centos:centos:7"
     redhat-release: CentOS Linux release 7.2.1511 (Core)
     system-release: CentOS Linux release 7.2.1511 (Core)
     system-release-cpe: cpe:/o:centos:centos:7

  uname -a:
     Linux knl1.uits.indiana.edu 3.10.0-327.13.1.el7.xppsl_1.3.3.151.x86_64 #1 SMP
     Fri Jun 10 15:04:35 UTC 2016 x86_64 x86_64 x86_64 GNU/Linux

  run-level 3 Oct 13 14:15

  SPEC is set to: /home/lijunj/SPEC/omp2012-1.1-run
     Filesystem     Type  Size  Used Avail Use% Mounted on
     /dev/sda3      ext4  713G   78G  599G  12% /

  Cannot run dmidecode; consider saying 'chmod +s /usr/sbin/dmidecode'

  (End of data from sysinfo program)
```

General Notes

```
  BIOS settings:
    Intel Simultaneous Multithreading (SMT): on
    Intel Turbo Boost Technology (Turbo): off
    Cluster Mode: quadrant
```

Continued on next page

General Notes (Continued)

```
Memory Mode: flat
```

Base Compiler Invocation

C benchmarks:
```
icc
```

C++ benchmarks:
```
icpc
```

Fortran benchmarks:
```
ifort
```

Base Portability Flags

350.md: `-free`
357.bt331: `-mcmodel=medium`
363.swim: `-mcmodel=medium`
367.imagick: `-std=c99`

Base Optimization Flags

C benchmarks:
```
-O3 -ansi-alias -no-prec-div -qopenmp -ipo -xMIC-AVX512
-fp-model fast=2
```

C++ benchmarks:
```
-O3 -ansi-alias -no-prec-div -qopenmp -ipo -xMIC-AVX512
-fp-model fast=2
```

Fortran benchmarks:
```
-O3 -no-prec-div -qopenmp -ipo -xMIC-AVX512 -fp-model fast=2
```

The flags files that were used to format this result can be browsed at
http://www.spec.org/omp2012/flags/Intel-ic16.0-linux64.html
http://www.spec.org/omp2012/flags/colfax-knl.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/omp2012/flags/Intel-ic16.0-linux64.xml
http://www.spec.org/omp2012/flags/colfax-knl.xml

Copyright 2012-2017 Standard Performance Evaluation Corporation

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC OMP2012 v1.1.
Report generated on Wed Jan 11 12:09:32 2017 by SPEC OMP2012 PS/PDF formatter v541.
Originally published on 11 January 2017.