SPEC® OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

Cray
(Test Sponsor: Indiana University)

Cray XC30 (Intel Xeon E5-2697 v2)

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 6.60

OMP2012 license: 3440A
Test sponsor: Indiana University
Tested by: Indiana University

Test date: Jul-2017
Hardware Availability: Apr-2013
Software Availability: Dec-2016



Hardware

CPU Name:	Intel Xeon E5-2697 v2
CPU Characteristics:	Intel Turbo Boost Technology off, Hyper-Threading on
CPU MHz:	2700
CPU MHz Maximum:	2700
FPU:	Integrated
CPU(s) enabled:	24 cores, 2 chips, 12 cores/chip, 2 threads/core
CPU(s) orderable:	1-2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	30 MB I+D on chip per chip
Other Cache:	None
Memory:	64 GB (8 x 8 GB 2Rx4 PC3-14900R-13, ECC)
Disk Subsystem:	None
Other Hardware:	None
Base Threads Run:	48

Continued on next page

Software

Operating System:	SUSE Linux Enterprise Server 11 SP3 (x86_64), Cray Linux Environment 5.2 3.0.101-0.46.1_1.0502.8871-cray_ari_c
Compiler:	C/C++/Fortran: Version 8.5.5 of Cray Programming Environment
Auto Parallel:	No
File System:	Lustre 2.5 (DDN SFA12K) over QDR InfiniBand
System State:	Run level 3 (multi-user)
Base Pointers:	64-bit
Peak Pointers:	Not Applicable
Other Software:	None

SPEC OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

Cray
(Test Sponsor: Indiana University)

Cray XC30 (Intel Xeon E5-2697 v2)

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 6.60

OMP2012 license:3440A
Test sponsor: Indiana University
Tested by: Indiana University

Test date: Jul-2017
Hardware Availability: Apr-2013
Software Availability: Dec-2016

Minimum Peak Threads: --
Maximum Peak Threads: --

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
350.md	48	448	10.3	**448**	**10.3**	448	10.3							
351.bwaves	48	487	9.30	510	8.88	**487**	**9.29**							
352.nab	48	813	4.78	**813**	**4.79**	809	4.81							
357.bt331	48	556	8.52	**568**	**8.35**	569	8.33							
358.botsalgn	48	858	5.07	858	5.07	**858**	**5.07**							
359.botsspar	48	**1161**	**4.52**	1161	4.52	1162	4.52							
360.ilbdc	48	646	5.51	**646**	**5.51**	646	5.51							
362.fma3d	48	**617**	**6.16**	619	6.13	593	6.41							
363.swim	48	649	6.98	651	6.96	**650**	**6.97**							
367.imagick	48	**989**	**7.11**	990	7.10	989	7.11							
370.mgrid331	48	742	5.95	733	6.03	**738**	**5.99**							
371.applu331	48	778	7.78	**795**	**7.62**	796	7.61							
372.smithwa	48	**833**	**6.43**	831	6.45	845	6.34							
376.kdtree	48	**657**	**6.85**	650	6.92	672	6.69							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
Sysinfo program
/N/dc2/projects/hpc/lijunj/spec/omp2012-1.1-run/bigred2plus-cray3/Docs/sysinfo
Revision 563 of 2016-06-10 (097295389cf6073d8c3b03fa376740a5)
running on nid00540 Wed Jul 26 03:01:14 2017

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/omp2012/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : Intel(R) Xeon(R) CPU E5-2697 v2 @ 2.70GHz
      2 "physical id"s (chips)
      48 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 12
      siblings  : 24
      physical 0: cores 0 1 2 3 4 5 8 9 10 11 12 13
      physical 1: cores 0 1 2 3 4 5 8 9 10 11 12 13
   cache size : 30720 KB
```

Continued on next page

Platform Notes (Continued)

```
From /proc/meminfo
   MemTotal:       66072376 kB
   HugePages_Total:       0
   Hugepagesize:       2048 kB

/usr/bin/lsb_release -d
   SUSE Linux Enterprise Server 11 (x86_64)

From /etc/*release* /etc/*version*
   SuSE-release:
      SUSE Linux Enterprise Server 11 (x86_64)
      VERSION = 11
      PATCHLEVEL = 3

uname -a:
   Linux nid00540 3.0.101-0.46.1_1.0502.8871-cray_ari_c #1 SMP Mon Jun 26
   15:18:40 UTC 2017 x86_64 x86_64 x86_64 GNU/Linux


SPEC is set to:
/N/dc2/projects/hpc/lijunj/spec/omp2012-1.1-run/bigred2plus-cray3
   Filesystem                              Type    Size  Used Avail Use% Mounted
   on
   10.10.0.171@o2ib:10.10.0.172@o2ib:/dc2 lustre  5.3P  4.9P  323T  94% /N/dc2

Cannot run dmidecode; consider saying 'chmod +s /usr/sbin/dmidecode'

(End of data from sysinfo program)
```

General Notes

```
Environment Variables:
    ENV_OMP_THREAD_STACK_SIZE=1073741824
    ulimit -s unlimited
```

Base Compiler Invocation

C benchmarks:
cc

C++ benchmarks:
CC

Fortran benchmarks:
ftn

Base Portability Flags

350.md: `-f free`
357.bt331: `-hpic -hdynamic`
363.swim: `-hpic -hdynamic`
367.imagick: `-hc99`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/omp2012/flags/cray.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/omp2012/flags/cray.xml`

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC OMP2012 v1.1.
Report generated on Wed Aug 16 15:43:25 2017 by SPEC OMP2012 PS/PDF formatter v541.
Originally published on 16 August 2017.