SPEC® OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

Supermicro
(Test Sponsor: HZDR)

Supermicro H8QGi+-F

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 2.47

OMP2012 license: 65A
Test sponsor: HZDR
Tested by: HZDR

Test date: Aug-2017
Hardware Availability: Nov-2011
Software Availability: Sep-2016



Hardware

CPU Name:	AMD Opteron 6276
CPU Characteristics:	AMD Turbo CORE technology up to 3.20 GHz
CPU MHz:	2300
CPU MHz Maximum:	3200
FPU:	Integrated
CPU(s) enabled:	64 cores, 4 chips, 16 cores/chip
CPU(s) orderable:	2,4 chips
Primary Cache:	512 KB I on chip per chip, 64 KB I shared / 2 cores; 16 KB D on chip per core
Secondary Cache:	16 MB I+D on chip per chip, 2 MB shared / 2 cores
L3 Cache:	16 MB I+D on chip per chip, 8 MB shared / 8 cores
Other Cache:	None
Memory:	256 GB (32 x 8 GB 2Rx4 PC3-10600R-9, ECC)
Disk Subsystem:	500 GB (1 x 500 GB SATA 7200rpm)
Other Hardware:	--

Continued on next page

Software

Operating System:	Ubuntu 14.04 LTS Kernel 4.4.0-38-generic
Compiler:	C/C++/Fortran: Version 6.2 of the GNU Compilers
Auto Parallel:	No
File System:	ext3
System State:	run-level 5
Base Pointers:	64-bit
Peak Pointers:	Not Applicable
Other Software:	None

SPEC OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

Supermicro
(Test Sponsor: HZDR)

Supermicro H8QGi+-F

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 2.47

OMP2012 license: 65A
Test sponsor: HZDR
Tested by: HZDR

Test date: Aug-2017
Hardware Availability: Nov-2011
Software Availability: Sep-2016

Base Threads Run: 32
Minimum Peak Threads: --
Maximum Peak Threads: --

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
350.md	32	6187	0.748	6179	0.749	**6181**	**0.749**							
351.bwaves	32	6564	0.690	**6587**	**0.688**	6634	0.683							
352.nab	32	**1242**	**3.13**	1232	3.16	1245	3.12							
357.bt331	32	986	4.81	**983**	**4.82**	965	4.91							
358.botsalgn	32	1054	4.13	1059	4.11	**1058**	**4.11**							
359.botsspar	32	**1722**	**3.05**	1718	3.06	1725	3.04							
360.ilbdc	32	41568	0.0856	42727	0.0833	**42402**	**0.0840**							
362.fma3d	32	1390	2.73	**1408**	**2.70**	1409	2.70							
363.swim	32	1388	3.26	1362	3.33	**1384**	**3.27**							
367.imagick	32	1510	4.65	**1512**	**4.65**	1522	4.62							
370.mgrid331	32	**1505**	**2.94**	1492	2.96	1528	2.89							
371.applu331	32	1089	5.57	1249	4.85	**1182**	**5.13**							
372.smithwa	32	548	9.77	543	9.86	**544**	**9.84**							
376.kdtree	32	712	6.32	684	6.58	**707**	**6.36**							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
Sysinfo program /tmp/spec/1.1/Docs/sysinfo
Revision 563 of 2016-06-10 (097295389cf6073d8c3b03fa376740a5)
running on laser081 Thu Aug  3 13:00:40 2017

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/omp2012/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : AMD Opteron(TM) Processor 6276
      4 "physical id"s (chips)
      64 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 8
      siblings  : 16
      physical 0: cores 0 1 2 3 4 5 6 7
      physical 1: cores 0 1 2 3 4 5 6 7
      physical 2: cores 0 1 2 3 4 5 6 7
      physical 3: cores 0 1 2 3 4 5 6 7
```

Continued on next page

Platform Notes (Continued)

```
      cache size : 2048 KB

   From /proc/meminfo
      MemTotal:       264000972 kB
      HugePages_Total:       0
      Hugepagesize:       2048 kB

   /usr/bin/lsb_release -d
      Ubuntu 14.04.5 LTS

   From /etc/*release* /etc/*version*
      debian_version: jessie/sid
      os-release:
         NAME="Ubuntu"
         VERSION="14.04.5 LTS, Trusty Tahr"
         ID=ubuntu
         ID_LIKE=debian
         PRETTY_NAME="Ubuntu 14.04.5 LTS"
         VERSION_ID="14.04"
         HOME_URL="http://www.ubuntu.com/"
         SUPPORT_URL="http://help.ubuntu.com/"
      rh-release: Red Hat Enterprise Linux Server release 7.2 (Maipo)

   uname -a:
      Linux laser081 4.4.0-38-generic #57~14.04.1-Ubuntu SMP Tue Sep 6 17:20:43 UTC
      2016 x86_64 x86_64 x86_64 GNU/Linux

   run-level 5 Jul 21 17:12

   SPEC is set to: /tmp/spec/1.1
      Filesystem     Type  Size  Used Avail Use% Mounted on
      /dev/sda1      ext3   37G  8.1G   27G  24% /

   Cannot run dmidecode; consider saying 'chmod +s /usr/sbin/dmidecode'

   (End of data from sysinfo program)
```

General Notes

```
   Environment:
     OMP_NESTED=FALSE
     OMP_DYNAMIC=FALSE
```

Base Compiler Invocation

C benchmarks:
gcc

Continued on next page

Base Compiler Invocation (Continued)

C++ benchmarks:
g++

Fortran benchmarks:
gfortran

Base Portability Flags

350.md: -ffree-form -fno-range-check

Base Optimization Flags

C benchmarks:
-fopenmp -O3

C++ benchmarks:
-fopenmp -O3

Fortran benchmarks:
-fopenmp -O3

The flags file that was used to format this result can be browsed at
http://www.spec.org/omp2012/flags/gcc62_linux_flags.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/omp2012/flags/gcc62_linux_flags.xml

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC OMP2012 v1.1.
Report generated on Wed Sep 6 18:01:56 2017 by SPEC OMP2012 PS/PDF formatter v541.
Originally published on 6 September 2017.