SPEC® OMPG2012 Result

Copyright 2012-2019 Standard Performance Evaluation Corporation

Intel

Intel Server System R2208WFTZS (2 x Intel Xeon Platinum 8280L, DDR4-2933, Turbo ON, SMT ON)

SPECompG_peak2012 = 28.0

SPECompG_base2012 = 22.8

OMP2012 license: 13
Test sponsor: Intel
Tested by: Intel

Test date: Mar-2019
Hardware Availability: Apr-2019
Software Availability: Jan-2019



Hardware

CPU Name:	Intel Xeon Platinum 8280L
CPU Characteristics:	Turbo ON, SMT ON
CPU MHz:	2700
CPU MHz Maximum:	4000
FPU:	Integrated
CPU(s) enabled:	56 cores, 2 chips, 28 cores/chip, 2 threads/core
CPU(s) orderable:	1,2 Chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per core
L3 Cache:	38.5 MB I+D on chip per chip
Other Cache:	None
Memory:	192 GB (12 x 16 GB 2Rx8 DDR4-2933Y-R)
Disk Subsystem:	Panasas ActiveStor 14 (124TB connected via 10GB Ethernet)
Other Hardware:	None
Base Threads Run:	112

Continued on next page

Software

Operating System:	Oracle Linux Server release 7.6
Compiler:	C/C++/Fortran: Version 19.0.2.187 of Intel Composer XE for Linux
Auto Parallel:	No
File System:	PanFS
System State:	Run Level 3 (multi-user)
Base Pointers:	64-bit
Peak Pointers:	64-bit
Other Software:	None

SPEC OMPG2012 Result

Copyright 2012-2019 Standard Performance Evaluation Corporation

Intel

Intel Server System R2208WFTZS (2 x Intel Xeon Platinum 8280L, DDR4-2933, Turbo ON, SMT ON)

SPECompG_peak2012 = 28.0

SPECompG_base2012 = 22.8

OMP2012 license:13
Test sponsor: Intel
Tested by: Intel

Test date: Mar-2019
Hardware Availability: Apr-2019
Software Availability: Jan-2019

Minimum Peak Threads: 56
Maximum Peak Threads: 112

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
350.md	112	**27.7**	**167**	27.7	167	27.7	167	112	**27.7**	**167**	27.8	166	27.7	167
351.bwaves	112	**226**	**20.0**	225	20.1	227	20.0	56	221	20.5	222	20.4	**222**	**20.4**
352.nab	112	183	21.3	183	21.3	**183**	**21.3**	112	183	21.2	**183**	**21.2**	184	21.2
357.bt331	112	192	24.7	190	25.0	**190**	**24.9**	112	**172**	**27.6**	172	27.6	172	27.6
358.botsalgn	112	235	18.5	**235**	**18.5**	235	18.5	112	224	19.4	224	19.4	**224**	**19.4**
359.botsspar	112	**435**	**12.1**	435	12.1	434	12.1	56	47.9	110	47.8	110	**47.9**	**110**
360.ilbdc	112	255	14.0	**254**	**14.0**	254	14.0	112	250	14.3	**250**	**14.2**	250	14.2
362.fma3d	112	**298**	**12.7**	285	13.3	301	12.6	112	307	12.4	**293**	**13.0**	292	13.0
363.swim	112	303	14.9	**303**	**14.9**	304	14.9	56	307	14.8	289	15.7	**289**	**15.7**
367.imagick	112	238	29.5	231	30.4	**234**	**30.1**	56	**174**	**40.3**	174	40.5	175	40.3
370.mgrid331	112	327	13.5	**327**	**13.5**	327	13.5	56	314	14.1	**315**	**14.0**	315	14.0
371.applu331	112	161	37.6	164	37.0	**162**	**37.4**	112	152	39.8	150	40.5	**152**	**39.9**
372.smithwa	112	137	39.2	139	38.5	**138**	**38.8**	112	**139**	**38.5**	138	39.0	140	38.3
376.kdtree	112	267	16.8	**267**	**16.9**	266	16.9	112	260	17.3	261	17.3	**260**	**17.3**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
Sysinfo program /global/panfs02/innl/aknyaze1/OMP2012/1.1/Docs/sysinfo
Revision 563 of 2016-06-10 (097295389cf6073d8c3b03fa376740a5)
running on elc02 Tue Mar 26 20:16:21 2019

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/omp2012/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : Intel(R) Xeon(R) Platinum 8280L CPU @ 2.70GHz
      2 "physical id"s (chips)
      112 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 28
      siblings  : 56
      physical 0: cores 0 1 2 3 4 5 6 8 9 10 11 12 13 14 16 17 18 19 20 21 22 24
      25 26 27 28 29 30
      physical 1: cores 0 1 2 3 4 5 6 8 9 10 11 12 13 14 16 17 18 19 20 21 22 24
      25 26 27 28 29 30
   cache size : 39424 KB
```

Continued on next page

Platform Notes (Continued)

```
From /proc/meminfo
   MemTotal:       196689540 kB
   HugePages_Total:       0
   Hugepagesize:       2048 kB

From /etc/*release* /etc/*version*
   oracle-release: Oracle Linux Server release 7.6
   os-release:
      NAME="Oracle Linux Server"
      VERSION="7.6"
      ID="ol"
      VARIANT="Server"
      VARIANT_ID="server"
      VERSION_ID="7.6"
      PRETTY_NAME="Oracle Linux Server 7.6"
      ANSI_COLOR="0;31"
   redhat-release: Red Hat Enterprise Linux Server release 7.6 (Maipo)
   system-release: Oracle Linux Server release 7.6
   system-release-cpe: cpe:/o:oracle:linux:7:6:server

uname -a:
   Linux elc02 3.10.0-957.5.1.el7.crt1.x86_64 #1 SMP Fri Feb 1 14:04:43 MST 2019
   x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Mar 25 16:12

SPEC is set to: /global/panfs02/innl/aknyaze1/OMP2012/1.1
   Filesystem                Type   Size  Used Avail Use% Mounted on
   panfs://36.101.212.1/innl panfs  269T  200T   70T  75% /global/panfs02/innl
Additional information from dmidecode:

   Warning: Use caution when you interpret this section. The 'dmidecode' program
   reads system data which is "intended to allow hardware to be accurately
   determined", but the intent may not be met, as there are frequent changes to
   hardware, firmware, and the "DMTF SMBIOS" standard.


(End of data from sysinfo program)
```

General Notes

```
================================================================================
General base OMP Library Settings
  ENV_KMP_AFFINITY=compact,0,verbose

================================================================================
General peak OMP Library Settings
  ENV_KMP_AFFINITY=compact,0,verbose

================================================================================
```

Continued on next page

General Notes (Continued)

```
Per benchmark peak OMP Library Settings

================================================================================
System settings notes:
  Intel Turbo Boost Technology (Turbo)  : Enabled

================================================================================
General OMP Library Settings
  KMP_LIBRARY=turnaround
  KMP_STACKSIZE=292M
  KMP_BLOCKTIME=infinite
  OMP_DYNAMIC=FALSE
  OMP_NESTED=FALSE
  OMP_SCHEDULE=static
Spectre and Meltdown
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown)
is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1)
is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2)
is mitigated in the system as tested and documented.

================================================================================
351.bwaves:peak:
  ENV_KMP_AFFINITY=compact,1,verbose

================================================================================
359.botsspar:peak:
  ENV_KMP_AFFINITY=compact,1,verbose

================================================================================
363.swim:peak:
  ENV_KMP_AFFINITY=compact,1,verbose

================================================================================
367.imagick:peak:
  ENV_KMP_AFFINITY=compact,1,verbose

================================================================================
370.mgrid331:peak:
  ENV_KMP_AFFINITY=compact,1,verbose
```

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Continued on next page

Base Compiler Invocation (Continued)

Fortran benchmarks:
ifort

Base Portability Flags

350.md: -FR
357.bt331: -mcmodel=medium
363.swim: -mcmodel=medium
367.imagick: -std=c99

Base Optimization Flags

C benchmarks:
-O3 -qopenmp -xCORE-AVX512 -qopt-zmm-usage=high -fp-model fast=2 -ansi-alias -no-prec-div -no-prec-sqrt -ipo -qopt-prefetch=0

C++ benchmarks:
-O3 -qopenmp -xCORE-AVX512 -qopt-zmm-usage=high -fp-model fast=2 -ansi-alias -no-prec-div -no-prec-sqrt -ipo -qopt-prefetch=0

Fortran benchmarks:
-O3 -qopenmp -xCORE-AVX512 -qopt-zmm-usage=high -fp-model fast=2 -ansi-alias -no-prec-div -no-prec-sqrt -ipo -qopt-prefetch=0 -align all

Peak Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Peak Portability Flags

350.md: -FR
357.bt331: -mcmodel=medium
363.swim: -mcmodel=medium

Continued on next page

Peak Portability Flags (Continued)

367.imagick: -std=c99

Peak Optimization Flags

C benchmarks:

352.nab: -O3 -qopenmp -xCORE-AVX512 -qopt-zmm-usage=high -fp-model fast=2 -fno-alias -no-prec-div -no-prec-sqrt -ipo -qopt-prefetch=0

358.botsalgn: -O3 -qopenmp -xCORE-AVX512 -qopt-zmm-usage=high -fp-model fast=2 -fno-alias -no-prec-div -no-prec-sqrt

359.botsspar: Same as 358.botsalgn

367.imagick: -O3 -qopenmp -xCORE-AVX512 -qopt-zmm-usage=high -fp-model fast=2 -fno-alias -no-prec-div -no-prec-sqrt -ipo

372.smithwa: Same as 352.nab

C++ benchmarks:
-O3 -qopenmp -xCORE-AVX512 -fp-model fast=2 -fno-alias -no-prec-div -no-prec-sqrt -qopt-prefetch=1

Fortran benchmarks:

350.md: -O3 -qopenmp -xCORE-AVX512 -qopt-zmm-usage=high -fp-model fast=2 -fno-alias -no-prec-div -no-prec-sqrt -ipo -qopt-prefetch=0 -align all

351.bwaves: -O3 -qopenmp -xCORE-AVX512 -qopt-zmm-usage=high -fp-model fast=2 -fno-alias -no-prec-div -no-prec-sqrt -ipo -qopt-prefetch=2 -align all

357.bt331: -O3 -qopenmp -xCORE-AVX512 -qopt-zmm-usage=high -fp-model fast=2 -fno-alias -no-prec-div -no-prec-sqrt -ipo -qopt-prefetch=1 -align all

360.ilbdc: -O3 -qopenmp -xCORE-AVX512 -qopt-zmm-usage=high -fp-model fast=2 -fno-alias -no-prec-div -no-prec-sqrt -ipo -qopt-prefetch=4 -align all

362.fma3d: Same as 350.md

363.swim: -O3 -qopenmp -xCORE-AVX512 -qopt-zmm-usage=high -fp-model fast=2 -no-prec-div -no-prec-sqrt -fno-alias -qopt-malloc-options=3 -ipo -qopt-prefetch=0 -align all

Continued on next page

Peak Optimization Flags (Continued)

370.mgrid331: `-O3 -qopenmp -xCORE-AVX2 -fp-model fast=2 -no-prec-div -no-prec-sqrt -fno-alias -qopt-malloc-options=3 -ipo -qopt-prefetch=0 -align all`

371.applu331: `-O3 -qopenmp -xCORE-AVX2 -fp-model fast=2 -fno-alias -no-prec-div -no-prec-sqrt -qopt-prefetch=0 -align all`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/omp2012/flags/Intel-ic19-linux64.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/omp2012/flags/Intel-ic19-linux64.xml`

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC OMP2012 v1.1.
Report generated on Wed Apr 10 14:05:51 2019 by SPEC OMP2012 PS/PDF formatter v541.
Originally published on 10 April 2019.