SPEC® OMPG2012 Result

Uniwide Technologies

(Test Sponsor: Telecommunications Technology Association)

RB128 (Intel Xeon E5-2699 v4, 2.20 GHz)

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 11.8

OMP2012 license: 068A		**Test date:**	Dec-2019
Test sponsor:	Telecommunications Technology Association	**Hardware Availability:**	May-2017
Tested by:	Telecommunications Technology Association	**Software Availability:**	Dec-2018



Hardware

CPU Name:	Intel Xeon E5-2699 v4
CPU Characteristics:	Intel Turbo Boost Technology up to 3.60 GHz Hyper-threading On.
CPU MHz:	2200
CPU MHz Maximum:	3600
FPU:	Integrated
CPU(s) enabled:	44 cores, 2 chips, 22 cores/chip, 2 threads/core
CPU(s) orderable:	1,2 Chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	55 MB I+D on chip per chip
Other Cache:	None
Memory:	512 GB (16 x 32 GB 2Rx4 PC4-2400T-R)
Disk Subsystem:	2 x 300GB SEAGATE ST300MM0048 SAS RAID0
Other Hardware:	None
Base Threads Run:	88

Continued on next page

Software

Operating System:	CentOS Linux release 7.7.1908 (Core)
Compiler:	C/C++/Fortran: Version 18.0.1.163 of Intel Composer XE for Linux Build 20171018
Auto Parallel:	No
File System:	xfs
System State:	Multi-user, run level 3
Base Pointers:	64-bit
Peak Pointers:	Not Applicable
Other Software:	None

SPEC OMPG2012 Result

Uniwide Technologies
(Test Sponsor: Telecommunications Technology Association)

RB128 (Intel Xeon E5-2699 v4, 2.20 GHz)

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 11.8

OMP2012 license:	068A	**Test date:**	Dec-2019
Test sponsor:	Telecommunications Technology Association	**Hardware Availability:**	May-2017
Tested by:	Telecommunications Technology Association	**Software Availability:**	Dec-2018

Minimum Peak Threads: --
Maximum Peak Threads: --

Results Table

	Base							Peak						
Benchmark	**Threads**	**Seconds**	**Ratio**	**Seconds**	**Ratio**	**Seconds**	**Ratio**	**Threads**	**Seconds**	**Ratio**	**Seconds**	**Ratio**	**Seconds**	**Ratio**
350.md	88	**223**	**20.8**	222	20.9	223	20.7							
351.bwaves	88	421	10.8	420	10.8	**421**	**10.8**							
352.nab	88	269	14.4	268	14.5	**269**	**14.5**							
357.bt331	88	**299**	**15.9**	298	15.9	305	15.5							
358.botsalgn	88	**396**	**11.0**	396	11.0	396	11.0							
359.botsspar	88	**579**	**9.06**	579	9.06	579	9.07							
360.ilbdc	88	457	7.80	458	7.77	**458**	**7.78**							
362.fma3d	88	**466**	**8.16**	473	8.04	461	8.25							
363.swim	88	564	8.03	571	7.93	**569**	**7.96**							
367.imagick	88	**421**	**16.7**	421	16.7	419	16.8							
370.mgrid331	88	**616**	**7.17**	613	7.20	617	7.17							
371.applu331	88	241	25.1	**253**	**23.9**	257	23.6							
372.smithwa	88	473	11.3	479	11.2	**476**	**11.3**							
376.kdtree	88	382	11.8	**382**	**11.8**	382	11.8							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
Sysinfo program /usr/omp2012/Docs/sysinfo
$Rev: 395 $ $Date:: 2012-07-25 #$ 8f8c0fe9e19c658963a1e67685e50647
running on uniwide-rb128 Mon Dec  2 22:41:59 2019

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/omp2012/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : Intel(R) Xeon(R) CPU E5-2699 v4 @ 2.20GHz
      2 "physical id"s (chips)
      88 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 22
      siblings  : 44
      physical 0: cores 0 1 2 3 4 5 8 9 10 11 12 16 17 18 19 20 21 24 25 26 27
      28
      physical 1: cores 0 1 2 3 4 5 8 9 10 11 12 16 17 18 19 20 21 24 25 26 27
      28
   cache size : 56320 KB
```

Continued on next page

Platform Notes (Continued)

```
From /proc/meminfo
   MemTotal:       528087944 kB
   HugePages_Total:       0
   Hugepagesize:       2048 kB

From /etc/*release* /etc/*version*
   centos-release: CentOS Linux release 7.7.1908 (Core)
   centos-release-upstream: Derived from Red Hat Enterprise Linux 7.7 (Source)
   os-release:
      NAME="CentOS Linux"
      VERSION="7 (Core)"
      ID="centos"
      ID_LIKE="rhel fedora"
      VERSION_ID="7"
      PRETTY_NAME="CentOS Linux 7 (Core)"
      ANSI_COLOR="0;31"
      CPE_NAME="cpe:/o:centos:centos:7"
   redhat-release: CentOS Linux release 7.7.1908 (Core)
   system-release: CentOS Linux release 7.7.1908 (Core)
   system-release-cpe: cpe:/o:centos:centos:7

uname -a:
   Linux uniwide-rb128 3.10.0-1062.4.1.el7.x86_64 #1 SMP Fri Oct 18 17:15:30 UTC
   2019 x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Dec 2 13:46

SPEC is set to: /usr/omp2012
   Filesystem              Type  Size  Used Avail Use% Mounted on
   /dev/mapper/centos-root xfs    50G  7.2G   43G  15% /

Additional information from dmidecode:
  BIOS American Megatrends Inc. 3407 01/11/2017
  Memory:
   16x   32 GB
   12x Hynix Semiconductor HMA84GR7AFR4N-UH 32 GB 2133 MT/s 2 rank
   4x Hynix Semiconductor HMA84GR7MFR4N-UH 32 GB 2133 MT/s 2 rank
   8x NO DIMM NO DIMM

(End of data from sysinfo program)
```

General Notes

```
==========================================================================================
System settings notes:
  Intel Turbo Boost Technology (Turbo)  : Enabled
  Hyper-threading : Disabled

==========================================================================================
General OMP Library Settings
```

Continued on next page

General Notes (Continued)

```
    KMP_AFFINITY=compact,0
    KMP_LIBRARY=turnaround
    KMP_STACKSIZE=512M
    KMP_BLOCKTIME=infinite
    OMP_DYNAMIC=FALSE
    OMP_NESTED=FALSE
    OMP_SCHEDULE=static

  ==================================================================================
  Envirionment Variables Settings
    ulimit -s unlimited

  ==================================================================================
  Spectre and Meltdown
  Yes: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown)
  is mitigated in the system as tested and documented.
  Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1)
  is mitigated in the system as tested and documented.
  Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2)
  is mitigated in the system as tested and documented.
```

Base Compiler Invocation

C benchmarks:
`icc`

C++ benchmarks:
`icpc`

Fortran benchmarks:
`ifort`

Base Portability Flags

350.md: `-FR`
357.bt331: `-mcmodel=medium`
363.swim: `-mcmodel=medium`
367.imagick: `-std=c99`

Base Optimization Flags

C benchmarks:
`-ansi-alias -qopenmp -ipo -O3 -no-prec-div -no-prec-sqrt -fp-model fast=2 -xHost`

Continued on next page

Base Optimization Flags (Continued)

C++ benchmarks:

```
-ansi-alias -qopenmp -ipo -O3 -no-prec-div -no-prec-sqrt
-fp-model fast=2 -xHost
```

Fortran benchmarks:

```
-qopenmp -ipo -O3 -no-prec-div -no-prec-sqrt -fp-model fast=2
-xHost
```

The flags file that was used to format this result can be browsed at
http://www.spec.org/omp2012/flags/icc_linux_flags.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/omp2012/flags/icc_linux_flags.xml

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC OMP2012 v1.0.
Report generated on Wed Dec 18 14:50:38 2019 by SPEC OMP2012 PS/PDF formatter v541.
Originally published on 18 December 2019.