



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI 2400 16X 500MHz R14k

SPECfp_rate2000 = 58.2
SPECfp_rate_base2000 = 53.8

SPEC license #: 4 Tested by: SGI Test date: May-2001 Hardware Avail: Jul-2001 Software Avail: May-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	16	588	50.5	16	534	55.6
171.swim	16	1794	32.1	16	1787	32.2
172.mgrid	16	1108	30.1	16	1108	30.1
173.applu	16	1035	37.7	16	945	41.2
177.mesa	16	407	63.8	16	373	69.6
178.galgel	16	256	210	16	226	238
179.art	16	239	202	16	238	203
183.equake	16	765	31.5	16	752	32.1
187.facerec	16	481	73.3	16	477	73.9
188.amp	16	462	88.3	16	462	88.3
189.lucas	16	1182	31.4	16	1177	31.5
191.fma3d	16	1376	28.3	16	1120	34.8
200.sixtrack	16	454	45.0	16	447	45.6
301.apsi	16	1155	41.8	16	745	64.8

Hardware

CPU: R14000
 CPU MHz: 500
 FPU: Integrated
 CPU(s) enabled: 16 cores, 16 chips, 1 core/chip
 CPU(s) orderable: 2-64
 Parallel: No
 Primary Cache: 32KBI + 32KBD on chip
 Secondary Cache: 8MB(I+D) off chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 16 GB
 Disk Subsystem: 1 x 18 GB FC, 4 x 18 GB FC (striped)
 Other Hardware: None

Software

Operating System: IRIX 6.5.12f
 Compiler: MIPSpro 7.3.1.2m C, Fortran90
 SCSL 1.3 Math Library
 File System: xfs
 System State: Single-user

Notes/Tuning Information

Baseline optimization flags (for C benchmarks):
 PASS1 : -Ofast=ip27 -IPA:use_intrinsic -fb_create /tmp/SPEC2000/FBDIR_base/\$(EXEBASE)
 PASS2 : -Ofast=ip27 -IPA:use_intrinsic -fb_opt /tmp/SPEC2000/FBDIR_base/\$(EXEBASE)
 Baseline optimization flags (for Fortran benchmarks): -Ofast=ip27 -LNO:fusion=2
 Portability Flags:
 178.galgel: -fixedform
 Peak optimization flags:
 note: all occurrences of (FEEDBACK) below means compiled with a two-step process:
 PASS1 = -fb_create /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)
 PASS2 = -fb_opt /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)
 168.wupwise: -Ofast=ip27 -IPA:space=1000:linear=on:plimit=10000:callee_limit=5000
 . -INLINE:aggressive=on -OPT:Olimit=0 -LNO:fusion=2:prefetch_ahead=5
 171.swim: -Ofast=ip27 -LNO:cs2=8m -CG:ld_latency=10
 172.mgrid: -Ofast=ip27 -LNO:fusion=2
 173.applu: -Ofast=ip27 -LNO:ou_max=5:ou_prod_max=10:prefetch=0:fusion=2 -CG:ld_latency=3
 177.mesa: -Ofast=ip27 -OPT:goto=off -LNO:opt=0:cs2=8m -CG:ld_latency=6 (FEEDBACK)
 178.galgel: -Ofast=ip27 -LNO:ou_max=7 -CG:ld_latency=3 -lscs (FEEDBACK)



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI 2400 16X 500MHz R14k

SPECfp_rate2000 = 58.2
SPECfp_rate_base2000 = 53.8

SPEC license #: 4 | Tested by: SGI | Test date: May-2001 | Hardware Avail: Jul-2001 | Software Avail: May-2001

Notes/Tuning Information (Continued)

```

.
  RM_SOURCES = lapak.f90
179.art: -Ofast=ip27 -LNO:prefetch=0 -IPA:min_hot=15 -CG:ld_latency=3 (FEEDBACK)
183.quake: -Ofast=ip27 -LNO:prefetch=0 -TENV:X=4 -CG:ld_latency=7 -IPA:space=500 (FEEDBACK)
187.facerec: -Ofast=ip27 -LNO:fusion=2
188.ammp: -Ofast=ip27 -OPT:goto=off -IPA:space=500:plimit=900 -CG:ld_latency=7 (FEEDBACK)
189.lucas: -Ofast=ip27 -LNO:fusion=2:blocking=off -CG:ld_latency=4 -IPA:min_hot=8 (FEEDBACK)
191.fma3d: -Ofast=ip27 -bigp_off -LNO:prefetch=0 -CG:ld_latency=2
.
  -OPT:goto=off:unroll_size=160:unroll_times_max=4 (FEEDBACK)
200.sixtrack:= -Ofast=ip27 -IPA:maxdepth=2 -LNO:prefetch=0 (FEEDBACK)
301.apsi: -Ofast=ip27 -TENV:X=4 -LNO:prefetch=0:blocking=off -IPA:linear=on:use_intrinsic
  setenv PAGESIZE_DATA 4096 ; setenv PAGESIZE_TEXT 4096 ; setenv PAGESIZE_STACK 4096
  systune -i ; percent_totalmem_4m_pages = 40 ; percent_totalmem_1m_pages = 7
  systune -i ; percent_totalmem_256k_pages = 7 ; percent_totalmem_64k_pages = 7
  systune -i ; r12k_bdiag = 0x4000000 ;
  limit stacksize 500000

```

The following is done before building each benchmark that requires (FEEDBACK):

```
rm -rf /tmp/SPEC2000/FBDIR_peak/$baseexe ; mkdir -p /tmp/SPEC2000/FBDIR_peak/$baseexe
```

The first disk mentioned in the Disk Subsystem is the system disk. A striped XFS filesystem was created using the rest of the disks and the benchmark was run on this.