CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER850 (675MHz)

SPECint2000 = 476

SPECint_base2000 = 446

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Oct-2001 | Hardware Avail: Nov-2001 | Software Avail: Dec-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	348	402	349	401
175.vpr	1400	335	418	320	438
176.gcc	1100	306	360	248	444
181.mcf	1800	365	493	328	549
186.crafty	1000	233	430	192	521
197.parser	1800	398	452	390	462
252.eon	1300	274	474	257	507
253.perlbmk	1800	365	493	351	513
254.gap	1100	405	271	407	270
255.vortex	1900	273	696	264	721
256.bzip2	1500	323	464	323	464
300.twolf	3000	571	525	532	563



Hardware

CPU:	SPARC64 GP
CPU MHz:	675
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	4 to 16
Parallel:	None
Primary Cache:	128KBI+128KBD on chip
Secondary Cache:	8MB(I+D) off chip, per CPU
L3 Cache:	None
Other Cache:	None
Memory:	16GB
Disk Subsystem:	2 x 18GB SCSI (10025rpm)
Other Hardware:	None

Software

Operating System:	Solaris 8 7/01
Compiler:	Fujitsu Parallelnavi 1.0.2 with patch 911403-01 Sun Forte Developer 6 update 2
File System:	ufs
System State:	multi user

Notes/Tuning Information

```
Baseline (except 252.eon, for Parallelnavi 1.0.2): -Kfast_GP=3,largepage
fdo_pre0=rm -rf ‘pwd‘/*.fbk
PASS1=-Kpg
PASS2=-Kpu=$(EXEBASE).fbk
(252.eon, for Forte Developer 6 update 2): -fast -xcrossfile -xarch=v8plus
fdo_pre0=rm -rf ‘pwd‘/../feedback.profile ‘pwd‘/SunWS_cache
PASS1=-xprofile=collect:‘pwd‘/../feedback
PASS2=-xprofile=use:‘pwd‘/../feedback

Peak (for Parallelnavi 1.0.2):
fdo_pre0=rm -rf ‘pwd‘/*.fbk
PASS1=-Kpg
PASS2=-Kpu=$(EXEBASE).fbk
164.gzip: -Kfast_GP=4
175.vpr: -Kfast_GP=4,staticclump,memalias,switchopt,cond,GREG,nounroll,largepage,onefile,NOFLTLD=3,xi=30
181.mcf: -Kfast_GP=2,nounroll,memalias,restp,prefetch=2,largepage -x-
197.parser: -Kfast_GP=4,switchopt,cond,staticclump,use_rodata,largepage
253.perlbmk: -Kfast_GP=4,memalias,switchopt,largepage,bcopy
254.gap: -Kfast_GP=3,largepage,memalias,unroll=4
256.bzip2: -Kfast_GP=3,largepage
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
300.twolf: -Kfast_GP=5,GREG,memalias,cfunc,staticclump,use_rodata,xi=10,largepage,nounroll,bcopy
(for Forte Developer 6 update 2)
 fdo_pre0=rm -rf ‘pwd‘/../feedback.profile ‘pwd‘/SunWS_cache
 PASS1=-xprofile=collect:‘pwd‘/../feedback
 PASS2=-xprofile=use:‘pwd‘/../feedback
176.gcc: -fast -xcrossfile -W2,-whole -Wc,-Qgsched-trace_late=1,-Qgsched-T4,-Qiselect-funcalign=64
          -xarch=v8plus -xprefetch
186.crafty: -fast -xcrossfile -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -xalias_level=strong
          -xregs=syst -xchip=ultra2 -xarch=v8plus -W2,-Amemopt
252.eon: -fast -xcrossfile -xsafe=mem -Qoption iropt -Mt500,-restrict_g,-restrict
          -Qoption cg -Qgsched-trace_late=1,-Qgsched-T4 -xarch=v8plus
255.vortex: -fast -xsafe=mem -xcrossfile -W2,-Aheap,-reroll=1,-Aunroll,-Ms1,-Mt500,-Mr6000,-crit
          -Wc,-Qdepgraph-early_cross_call=1 -Wc,-Qiselect-funcalign=32 -Wc,-Qpeep-Sh0
         -xrestrict -xdepend -Wc,-Qgsched-trace_late=1,-Qgsched-T4  -xarch=v8plus -W2,-Amemopt

Portability:
 176.gcc: -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
 186.crafty: -DSUN
 252.eon: -library=iostream
 253.perlbmk: -DSPEC_CPU2000_SOLARIS
 254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_CALLOC_PROTO

Note:
 System Tunables: (for /etc/system)
  consistent_coloring=1, tune_t_fsflushr=86400, autoup=86400,
  shmsys:shminfo_shmmax=8589934592, shmsys:shminfo_shmmni=1024, shmsys:shminfo_shmseg=1024
 (for /etc/opt/FJSVpnrm/lpg.conf)
  TSS=512M, SHMSEGSIZE=256M
 ONESTEP=yes was set for all baseline and peak benchmarks.
 Feedback directed optimization was used for all baseline and peak benchmarks.
 Only one CPU installed on the system board.
 Extended Interleave Mode enabled.
```