



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI Origin 300 16X 500MHz R14k

SPECint_rate2000 = 68.3
SPECint_rate_base2000 = 65.8

SPEC license #: 4 Tested by: SGI Test date: Dec-2001 Hardware Avail: Dec-2001 Software Avail: Nov-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	16	518	50.2	16	500	52.0
175.vpr	16	378	68.7	16	353	73.5
176.gcc	16	311	65.7	16	309	66.2
181.mcf	16	641	52.1	16	641	52.1
186.crafty	16	250	74.3	16	247	75.0
197.parser	16	573	58.4	16	549	60.9
252.eon	16	298	81.1	16	280	86.3
253.perlbnk	16	605	55.3	16	602	55.5
254.gap	16	432	47.2	16	429	47.6
255.vortex	16	358	98.6	16	313	113
256.bzip2	16	441	63.1	16	409	68.1
300.twolf	16	569	97.9	16	569	97.9

Hardware

CPU: R14000
CPU MHz: 500
FPU: Integrated
CPU(s) enabled: 16 cores, 16 chips, 1 core/chip
CPU(s) orderable: 2-32
Parallel: No
Primary Cache: 32KBI + 32KBD on chip
Secondary Cache: 2MB(I+D) off chip
L3 Cache: N/A
Other Cache: N/A
Memory: 16 GB
Disk Subsystem: 1 x 18 GB SCSI, 2 x 18 GB SCSI (striped)
Other Hardware: None

Software

Operating System: IRIX 6.5.14f
Compiler: MIPSpro 7.3.1.2m C, C++
SCSL 1.4 Math Library
File System: xfs
System State: Single-user

Notes/Tuning Information

Baseline optimization flags (C and C++ use same flags):

PASS1 : -Ofast=ip27 -IPA:use_intrinsic -fb_create /tmp/SPEC2000/FBDIR/base/\$(EXEBASE)
PASS2 : -Ofast=ip27 -IPA:use_intrinsic -fb_opt /tmp/SPEC2000/FBDIR/base/\$(EXEBASE)

Portability Flags:

176.gcc: -Dalloca=__builtin_alloca -DMIPS -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSGI
252.eon: -lm
253.perlbnk: -DSPEC_CPU2000_SGI -DI_FCNTL
254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_IOCTL_PROTO
-DSYS_HAS_ANSI -DSYS_HAS_CALLOC_PROTO
300.twolf: -DHAVE_SIGNED_CHAR

Peak optimization flags:

note: all occurrences of (FEEDBACK) below means compiled with a two-step process:

PASS1 = -fb_create /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)
PASS2 = -fb_opt /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)
164.gzip: -Ofast=ip27 -IPA:space=500:plimit=500 -lmalloc (FEEDBACK)
175.vpr: -Ofast=ip27 -IPA:space=300:plimit=10000:callee_limit=5000:linear=on
. -LNO:prefetch Ahead=2 -INLINE:aggressive=on
. -OPT:Olimit=0:alias=disjoint:alias=restrict -CG:ld_latency=10 -lmalloc (FEEDBACK)
181.mcf: basepeak=yes



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI

SGI Origin 300 16X 500MHz R14k

SPECint_rate2000 = 68.3

SPECint_rate_base2000 = 65.8

SPEC license #: 4 Tested by: SGI Test date: Dec-2001 Hardware Avail: Dec-2001 Software Avail: Nov-2001

Notes/Tuning Information (Continued)

```

176.gcc: -Ofast=ip27 -CG:ld_latency=4 (FEEDBACK)
186.crafty: -Ofast=ip27 -LNO:prefetch=0 -OPT:goto=off -CG:ld_latency=4 -lmalloc (FEEDBACK)
197.parser: -Ofast=ip27 -IPA:min_hot=14 (FEEDBACK)
252.eon: -Ofast=ip27 -LNO:prefetch=0 -LANG:exceptions=off -CG:ld_latency=4 -lmalloc -lm
      (FEEDBACK)
253.perlbnk: -Ofast=ip27 -IPA:use_intrinsic -Wl,-x (FEEDBACK)
254.gap: -Ofast=ip27 -IPA:use_intrinsic -OPT:unroll_analysis=off:unroll_size=0:unroll_times_max=4
      -OPT:alias=restrict:alias=disjoint -IPA:min_hot=7 -CG:ld_latency=8 -lmalloc (FEEDBACK)
255.vortex: -Ofast=ip27 -IPA:use_intrinsic
      -OPT:unroll_analysis=off:unroll_size=0:unroll_times_max=4 -LNO:opt=0 -CG:ld_latency=5
      -IPA:min_hot=14 -TENV:X=4 -IPA:space=500:plimit=3600 -OPT:goto=off (FEEDBACK)
256.bzip2: -Ofast=ip27 -IPA:min_hot=5:space=500:plimit=2900 -INLINE:aggressive=on (FEEDBACK)
300.twolf: basepeak=yes

```

The following O/S parameters were set:

```

setenv PAGESIZE_DATA 4096 ; setenv PAGESIZE_TEXT 4096 ; setenv PAGESIZE_STACK 4096
system -i ; percent_totalmem_4m_pages = 40 ; percent_totalmem_1m_pages = 7
system -i ; percent_totalmem_256k_pages = 7 ; percent_totalmem_64k_pages = 7
system -i ; r12k_bdiag = 0x4000000 ;
limit stacksize 500000

```

The following is done before building each benchmark that requires (FEEDBACK):

```

rm -rf /tmp/SPEC2000 ; mkdir /tmp/SPEC2000 ; cd /tmp/SPEC2000 ; mkdir FBDIR_base ; mkdir FBDIR_peak
The first disk mentioned in the Disk Subsystem is the system disk. A striped
XFS filesystem was created using the rest of the disks and the benchmark was
run on this.

```

Jobs are submitted using dplace. Contents of the placement file submit.pf:

```

memories 1 in topology physical near $NODE
threads 1
run thread 0 on memory 0 using cpu $CPU

```