



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems Sun Fire 4800

SPECfp_rate2000 = 122
SPECfp_rate_base2000 = 98.1

SPEC license #:	6	Tested by:	Sun Microsystems	Test date:	Apr-2003	Hardware Avail:	Mar-2003	Software Avail:	May-2003			
2000	1500	1000	500			Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
						168.wupwise	12	232	95.9	12	216	103
						171.swim	12	753	57.3	12	138	313
						172.mgrid	12	460	54.5	12	456	54.9
						173.applu	12	346	84.6	12	256	114
						177.mesa	12	210	92.9	12	198	98.6
						178.galgel	12	156	259	12	129	312
						179.art	12	29.3	1234	12	27.1	1333
						183.eqquake	12	159	114	12	156	116
						187.facerec	12	174	152	12	174	152
						188.ammp	12	470	65.1	12	374	81.9
						189.lucas	12	670	41.6	12	574	48.5
						191.fma3d	12	595	49.1	12	540	54.1
						200.sixtrack	12	288	53.2	12	253	60.5
						301.apsi	12	439	82.4	12	439	82.4

Hardware		Software	
CPU:	UltraSPARC III Cu	Operating System:	Solaris 9 12/02
CPU MHz:	1200	Compiler:	Sun ONE Studio 8 (pre-FCS build 3/9)
FPU:	Integrated	File System:	Sun Performance Library 8 (pre-FCS build 3/9)
CPU(s) enabled:	12 cores, 12 chips, 1 core/chip	System State:	ufs with ufs logging
CPU(s) orderable:	4-12		Multi-User
Parallel:	No		
Primary Cache:	32KBI+64KBD on chip		
Secondary Cache:	8MB(I+D) off chip		
L3 Cache:	None		
Other Cache:	None		
Memory:	24GB 16-way interleaved		
Disk Subsystem:	2 x 36GB		
	4 x (Sun StorEdge T3, 9x18GB raid5)		
	4-way striped		
Other Hardware:	None		

Notes/Tuning Information

Compiler invocation:

```
C: cc
CXX: CC
F90: f90
F77: f90
```

Floating point base flags:

```
C: -fast -xiwo=2 -xalias_level=std with ONESTEP=yes and feedback
F90: -fast -xiwo=2 with ONESTEP=yes and feedback
```

Floating point peak flags:

ONESTEP=yes and feedback for all benchmarks, unless otherwise noted

168.wupwise: -fast -xiwo=2 -Qoption iropt -Ainline:inc=800:cp=1

171.swim: -fast -xpdb=common:3969 -xpagesize=64K -xprefetch=latx:1.6



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire 4800

SPECfp_rate2000 = 122
SPECfp_rate_base2000 = 98.1

SPEC license #: 6

Tested by:

Sun Microsystems

Test date:

Apr-2003

Hardware Avail:

Mar-2003

Software Avail:

May-2003

Notes/Tuning Information (Continued)

```
-Qoption iropt -Atile:skewp,-Ainline:cs=700
  (no feedback)
172.mgrid: -fast -xipo=2
173.applu: -fast -xipo=2
  -Qoption cg -Qlp=1-av=192-fa=1,-Qms_pipe+prefolim=7
  -Qoption iropt -Aujam:inner=g
177.mesa: -fast -xipo=2 -xalias_level=strong -xrestrict
  -Wc,-Qms_pipe+unoovf
178.galgel: -fast -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
  RM_SOURCES=lapak.f90
179.art: -fast -xipo=2 -xalias_level=std
  -Wc,-Qms_pipe-prefst,-Qms_pipe+prefolim=11
183.equake: -fast -xipo=2 -xalias_level=strong -xprefetch_level=2
187.facerec: -fast -xipo=2
188.ammp: -fast -xipo=2 -xalias_level=std -xpagesize=512K -lmopt -lm
189.lucas: -fast -xipo=2 -xprefetch_level=3 -Qoption iropt -Apf:pdl=1
  -Qoption f90comp -array_pad_rows,1977
191.fma3d: -fast -xipo=2 -stackvar -xprefetch_level=3
  -Qoption iropt -Apf:pdl=1
200.sixtrack:-O -dalign -xchip=ultra3 -xarch=v8plusb -fsimple=2
301.apsi: -fast -xipo=2
```

Feedback is done as follows, unless otherwise noted:

```
fdo_pre0: rm -rf ./feedback.profile ./SunWS_cache
PASS1: -xprofile=collect:./feedback
PASS2: -xprofile=use:./feedback
```

Portability:

```
178.galgel: -e -fixed
```

Shell Environments:

```
Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1
```

Kernel Parameters (/etc/system):

```
autoup=900
tune_t_fsflushr=1
```

Processes were bound to CPUs using submit=bind

The benchmark was run on the Sun StorEdge T3 disk resident file system.