CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company

HP Integrity Server rx2600 (1500 MHz, Itanium 2)

SPECint2000 = 1322

SPECint_base2000 = 1322

SPEC license #: 3 | Tested by: HP Richardson | Test date: Jul-2003 | Hardware Avail: Sep-2003 | Software Avail: Sep-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	144	973	144	973
175.vpr	1400	125	1119	125	1119
176.gcc	1100	70.8	1554	70.8	1554
181.mcf	1800	78.1	2305	78.1	2305
186.crafty	1000	81.9	1221	81.9	1221
197.parser	1800	183	983	183	983
252.eon	1300	84.0	1547	84.0	1547
253.perlbmk	1800	149	1210	149	1210
254.gap	1100	102	1074	102	1074
255.vortex	1900	97.8	1944	97.8	1944
256.bzip2	1500	123	1217	123	1217
300.twolf	3000	234	1280	234	1280



Hardware

CPU:	Intel Itanium 2
CPU MHz:	1500
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	1-2
Parallel:	no
Primary Cache:	16KBI + 16KBD (on chip) per CPU
Secondary Cache:	256KB (on chip) per CPU
L3 Cache:	6.0MB (on chip) per CPU
Other Cache:	N/A
Memory:	12GB (12 * 1GB DIMMs)
Disk Subsystem:	1x36GB 10k RPM SCSI disk
Other Hardware:	N/A

Software

Operating System:	HPUX11i-TCOE B.11.23
Compiler:	HP C/ANSI C Compiler B.11.23
	HP aC++ Compiler B.11.23
File System:	vxfs
System State:	Multi-user

Notes/Tuning Information

```
Portability Flags
176.gcc     : -DHOST_WORDS_BIG_ENDIAN
181.mcf     : -DWANT_STDC_PROTO
186.crafty  : -DHP
252.eon     : -I. -DFMAX_IS_DOUBLE -DNDEBUG
              -DSPEC_CPU2000_LP64 (because of 64-bit compile)
253.perlbmk : -DSPEC_CPU2000_HP
254.gap     : -DSPEC_CPU2000_HP -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO
              -DSYS_HAS_TIME_PROTO -DSYS_HAS_CALLOC_PROTO

Base Flags
  all       : +Oprofile=collect:all/+Oprofile=use
  C         : +Ofaster -exec +Odatalayout
  C++       : +Ofaster +inline_level 2 -minshared +DD64

Peak Flags
  same as baseline (basepeak=true set globally)


Kernel Tunables:
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
    maxdsiz             0x7b03a000
    maxdsiz_64bit    0x04000000000
    maxssiz             0x10000000
    maxssiz_64bit       0x40000000
    vps_ceiling              16384
    vps_pagesize              4096
    swapmem_on                   0
    dbc_max_pct                 20
    dbc_min_pct                 20

  Note:
    EFI shell utility 'cpuconfig' used
    to deconfigure processors if necessary
```