CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer pSeries 655 (1700 Mhz, 1 CPU LPAR)

SPECint2000 = --

SPECint_base2000 = 1023

SPEC license #: 11 | Tested by: IBM, Austin, Tx | Test date: Jul-2003 | Hardware Avail: Jul-2003 | Software Avail: May-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	186	754		
175.vpr	1400	170	824		
176.gcc	1100	99.5	1105		
181.mcf	1800	131	1376		
186.crafty	1000	109	918		
197.parser	1800	206	873		
252.eon	1300	105	1237		
253.perlbmk	1800	215	838		
254.gap	1100	119	922		
255.vortex	1900	151	1260		
256.bzip2	1500	139	1078		
300.twolf	3000	224	1337		



Hardware

CPU:	POWER4+
CPU MHz:	1700
FPU:	Integrated
CPU(s) enabled:	1 core, 4 chips, 1 cores/chip, 4 chips/MCM
CPU(s) orderable:	1 MCM (order by # MCM)
Parallel:	No
Primary Cache:	64KBI+32KBD (on chip) per core
Secondary Cache:	1536KB unified (off chip) per chip
L3 Cache:	128MB unified (off-chip) per MCM, 1 MCM in SUT
Other Cache:	None
Memory:	8 GB
Disk Subsystem:	1x36GB SCSI, 10K RPM
Other Hardware:	None

Software

Operating System:	SLES 8 for pSeries w/2.4.19 kernel
Compiler:	IBM VisualAge C++ Version 6.0 for Linux on pSeries, May 2003 PTF IBM XL Fortran Version 8.1 for Linux on pSeries, May 2003 PTF
File System:	ext2
System State:	Multi-user

Notes/Tuning Information

```
cfg file:  ppc32-linux-ibm-ref-o5.cfg

Compiled 32-bit applications

CC  = /opt/ibmcmp/vac/6.0/bin/cc
CXX = /opt/ibmcmp/vacpp/6.0/bin/xlC



SCM: Acronym for "Single-chip module"
SUT: Acronym for "System under test"

SLES: SuSE Linux Enterprise Server

Running in 1-CPU partition with 8 GB memory on 4-CPU 16GB p655 system.
No other partitions running on the system.

Integer optimization flags
   Int: -qpdf1/pdf2 -O5
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
Integer portability flags
   gcc:  -DHOST_WORDS_BIG_ENDIAN
   mcf: None
   crafty: -DLINUX_PPC32
   parser: None
   eon: -DHAS_ERRLIST
   eon:
   eon: Using srcalt=fmax_errno

   perlbmk: -DSPEC_CPU2000_LINUX_PPC32 -DSPEC_CPU2000_NEED_BOOL
            -DHAS_FGETPOS -DHAS_FSETPOS
   gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_CALLOC_PROTO
   vortex: None
   bzip2: None
   twolf: -DHAVE_SIGNED_CHAR
```