



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant DL580 G2(2.8GHz, Intel Xeon MP)

SPECint\_rate2000 = 47.6  
SPECint\_rate\_base2000 = 45.1

SPEC license #: 3 Test date: Sep-2003 Hardware Avail: Jul-2003 Software Avail: Jun-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	134	48.5	4	134	48.4
175.vpr	4	185	35.1	4	184	35.2
176.gcc	4	106	48.0	4	79.0	64.6
181.mcf	4	555	15.1	4	538	15.5
186.crafty	4	93.3	49.7	4	92.8	50.0
197.parser	4	170	49.2	4	169	49.3
252.eon	4	105	57.3	4	91.3	66.1
253.perlbnk	4	146	57.3	4	134	62.1
254.gap	4	129	39.6	4	129	39.6
255.vortex	4	123	71.5	4	123	71.6
256.bzip2	4	175	39.8	4	171	40.7
300.twolf	4	220	63.4	4	207	67.2

### Hardware

CPU: Intel Xeon MP (2.8GHz, 400MHz bus)  
CPU MHz: 2800  
FPU: Integrated  
CPU(s) enabled: 4 cores, 4 chips, 1 core/chip (Hyper-Threading disabled)  
CPU(s) orderable: 1,2,4  
Parallel: No  
Primary Cache: 12K micro-ops I + 8KBD on chip  
Secondary Cache: 512KB(I+D) on chip  
L3 Cache: 2048KB(I+D) on chip  
Other Cache: N/A  
Memory: 16x512MB PC1600  
Disk Subsystem: 2x18.2GB 15K Ultra3 SCSI  
Other Hardware:

### Software

Operating System: Windows 2000 Advanced Server(Build 2195 SP3)  
Compiler: Intel C++ Compiler 7.1 Build 20030801Z  
Microsoft Visual Studio .NET 7.0.9466 (for libraries)  
MicroQuill Smartheap Library 7.0  
File System: NTFS  
System State: Hyperthreading disabled in BIOS

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -QxW -Qipo -O3 +FDO ONESTEP=yes
Base tuning for C++ programs: -Qipo -GX -GR +FDO ONESTEP=yes
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -QxW -Qipo -O3 +FDO ONESTEP=yes
175.vpr: -QxW -Qipo -O3 +FDO ONESTEP=yes
176.gcc: -QxW -Qipo -O3 -Oi- +FDO ONESTEP=yes
181.mcf: -Oa -Qipo +FDO shlw32M.lib ONESTEP=yes
186.crafty: -QxW -Qipo -O3 +FDO ONESTEP=yes
197.parser: -QxW -Qipo -O3 -Oa +FDO ONESTEP=yes
252.eon: -QxW -Qipo -O3 +FDO shlw32M.lib ONESTEP=yes
253.perlbnk: -Qipo -O3 -Oa +FDO shlw32M.lib ONESTEP=yes
254.gap: -QxW -Qipo -O3 +FDO ONESTEP=yes
255.vortex: -QxW -Qipo -O3 +FDO ONESTEP=yes
256.bzip2: -Qunroll1 -Qipo -Oa +FDO ONESTEP=yes
```



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant DL580 G2(2.8GHz, Intel Xeon MP)

SPECint\_rate2000 = 47.6  
SPECint\_rate\_base2000 = 45.1

SPEC license #: 3 | Test address: Hewlett-Packard Company, Houston TX | Test date: Sep-2003 | Hardware Avail: Jul-2003 | Software Avail: Jun-2003

## Notes/Tuning Information (Continued)

300.twolf: -QxW -Qipo -O3 -Oa +FDO shlw32M.lib ONESTEP=yes