CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company

HP Integrity Server rx4640 (1300 MHz, Itanium 2)

SPECint_rate2000 = 51.4

SPECint_rate_base2000 = 50.7

SPEC license #: 3 | Tested by: HP Richardson | Test date: Jan-2004 | Hardware Avail: Jan-2004 | Software Avail: Mar-2004



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	172	37.8	4	172	37.8
175.vpr	4	153	42.5	4	150	43.3
176.gcc	4	84.2	60.6	4	84.2	60.6
181.mcf	4	178	47.0	4	178	47.0
186.crafty	4	93.5	49.6	4	93.5	49.6
197.parser	4	209	39.9	4	209	39.9
252.eon	4	82.8	72.9	4	80.8	74.7
253.perlbmk	4	165	50.5	4	154	54.3
254.gap	4	121	42.3	4	121	42.3
255.vortex	4	118	74.5	4	117	75.2
256.bzip2	4	138	50.6	4	138	50.6
300.twolf	4	254	54.8	4	249	55.9

Hardware

CPU:	Intel Itanium 2
CPU MHz:	1300
FPU:	Integrated
CPU(s) enabled:	4 cores, 4 chips, 1 core/chip
CPU(s) orderable:	1-4
Parallel:	no
Primary Cache:	16KBI + 16KBD (on chip) per CPU
Secondary Cache:	256KB (on chip) per CPU
L3 Cache:	3.0MB (on chip) per CPU
Other Cache:	N/A
Memory:	32GB (16 * 2GB DIMMs)
Disk Subsystem:	1x36GB 10k RPM SCSI disk
Other Hardware:	N/A

Software

Operating System:	HPUX11i-TCOE B.11.23
Compiler:	HP C/ANSI C Compiler C.05.55
	HP aC++ Compiler C.05.55
File System:	VxFS
System State:	Multi-user

Notes/Tuning Information

```
 Portability Flags
 176.gcc    : -DHOST_WORDS_BIG_ENDIAN
 186.crafty : -DHP
 252.eon    : -DFMAX_IS_DOUBLE
 253.perlbmk: -DSPEC_CPU2000_HP
 254.gap    : -DSPEC_CPU2000_HP -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO
              -DSYS_HAS_TIME_PROTO -DSYS_HAS_CALLOC_PROTO

Base Flags
 PBO        : +Oprofile=collect:all/+Oprofile=use
 C          : PBO +Ofaster -exec +Odatalayout
 C++        : PBO +Ofaster +inline_level 2 -minshared

Peak Flags
 164.gzip   : basepeak=true
 175.vpr    : PBO +Ofaster +Odatalayout +Onorecovery
                +Onoptrs_to_globals -exec
              LIBS = -Wl,-aarchive_shared -Bprotected
 176.gcc    : basepeak=true
 181.mfc    : basepeak=true
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
186.crafty : basepeak=true
197.parser : basepeak=true
252.eon    : PBO +Ofaster +Odatalayout +Otype_safety=ansi
               +inline_level 2 -minshared
253.perlbmk: PBO +Ofaster +Odatalayout +Onoptrs_to_globals -exec
             LIBS = -Wl,-aarchive_shared -Bprotected_def fastmem.o
254.gap    : basepeak=true
255.vortex : PBO +Ofaster +Odatalayout +Onorecovery
               +Onoptrs_to_globals -exec
             LIBS = -Wl,-aarchive_shared -Bprotected
256.bzip2  : basepeak=true
300.twolf  : PBO +Ofaster +Odatalayout +Onoptrs_to_globals -exec
             LIBS = -Wl,-aarchive_shared -Bprotected_data effmem.o

Kernel Tunables:
  maxssiz             268435456
  vps_ceiling             16384
  vps_pagesize             4096
  swapmem_on                  1
  dbc_max_pct                20
  dbc_min_pct                20

Note:
  EFI shell utility 'cpuconfig' used
  to deconfigure processors if necessary
```