CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V890 (4 processor)

SPECint_rate2000 = 59.8

SPECint_rate_base2000 = 54.5

SPEC license #: 6 | Tested by: Sun Microsystems | Test date: Aug-2004 | Hardware Avail: Sep-2004 | Software Avail: Sep-2004



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	314	41.3	8	275	47.2
175.vpr	8	265	49.1	8	262	49.6
176.gcc	8	182	56.1	8	171	59.9
181.mcf	8	333	50.2	8	267	62.6
186.crafty	8	166	55.9	8	134	69.4
197.parser	8	341	49.0	8	301	55.6
252.eon	8	169	71.2	8	176	68.7
253.perlbmk	8	303	55.1	8	280	59.6
254.gap	8	268	38.0	8	230	44.4
255.vortex	8	187	94.5	8	178	99.1
256.bzip2	8	236	59.1	8	224	62.2
300.twolf	8	531	52.4	8	510	54.6

Hardware

CPU:	UltraSPARC IV
CPU MHz:	1200
FPU:	Integrated
CPU(s) enabled:	8 cores, 4 chips, 2 cores/chips
CPU(s) orderable:	4,8 (order by # of chips)
Parallel:	No
Primary Cache:	32KBI+64KBD per core on chip (64KBI+128KBD on chip)
Secondary Cache:	8MB(I+D) per core off chip (16MB(I+D) off chip)
L3 Cache:	None
Other Cache:	None
Memory:	32GB 8-way interleaved
Disk Subsystem:	1x73GB
Other Hardware:	None

Software

Operating System:	Solaris 9 9/04
Compiler:	Sun Studio 9
File System:	ufs with ufs logging
System State:	Multi-User

Notes/Tuning Information

```
Compiler invocation:
  C: cc
  CXX: CC



Integer base flags:
     -fast -xipo=2 with ONESTEP=yes and feedback

Integer peak flags:
 ONESTEP=yes and feedback for all benchmarks

 164.gzip:    -xO4  -xbuiltin=%all -xtarget=native -xalias_level=std
              -xipo=2 -Wc,-Qeps:enabled=1,
              -Qeps:rp_filtering_margin=30,-Qeps:do_spec_load=1
 175.vpr:     -fast -xalias_level=std -xipo=2
              -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=100,
              -Qeps:do_spec_load=1 -lmopt -lm
 176.gcc:     -fast -xipo=2 -ll2amm
 181.mcf:     -fast -xipo=2 -xprefetch_level=2 -Wc,-Qeps:enabled=1
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
 186.crafty:  -fast -xinline= -xipo=2 -xalias_level=strong -W2,-Ashort_ldst
              Feedback adds -xlinkopt in PASS2
 197.parser:  -fast -xipo=2 -xalias_level=strong
              -Wc,-Qgsched-T6,-Qipa:valueprediction
 252.eon:     -fast -xipo=2  -noex
              -Qoption cg -Qeps:enabled=1,-Qeps:ws=32
 253.perlbmk: -xO5 -xtarget=native xmemalign=4s
              -xipo -Wc,-Qeps:enabled=1,-Qeps:ws=8
              -xalias_level=std -xsafe=mem
              -Wc,-Qiselect-funcalign=32,Qicache-chbab=1
              -Wc,-Qiselect-sw_pf_tbl_th=20,
              -Qeps:do_spec_load=1 -xprefetch=no
 254.gap:     -fast -xipo=2 -xalias_level=strong -xvector
              -xprefetch_level=3 -W2,-Abcopy
 255.vortex:  -fast -xrestrict -xipo=2
              -W2,-crit,-Ainline:recursion=1:cs=500:irs=6000
              -Wc,-Qeps:enabled=1,-Qdepgraph-early_cross_call=1,
              -Qiselect-funcalign=32,-Qpeep-Sh0 -ll2amm
 256.bzip2:   -fast -xipo -xalias_level=strong -xrestrict
              -Wc,-Qeps:enabled=1 -xsafe=mem -Qeps:rp_filtering_margin=99
 300.twolf:   -fast -xalias_level=strong -xsafe=mem -xipo=2
              -xprefetch=no%auto -Wc,-Qms_pipe+intdivusefp

Feedback is done as follows, unless otherwise noted:
 fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
 PASS1:     -xprofile=collect:./feedback
 PASS2:     -xprofile=use:./feedback

Portability:
 176.gcc:     -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
 186.crafty:  -DSUN
 252.eon:     -library=iostream
 253.perlbmk: -DSPEC_CPU2000_SOLARIS
 254.gap:     -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
              -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

Shell Environments:
  Stack size set to unlimited via "ulimit -s unlimited"
  MPSSHEAP=512K
  MPSSSTACK=512K
  LD_PRELOAD=mpss.so.1

Kernel Parameters (/etc/system):
 autoup=900
 tune_t_fsflushr=1
```