CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company

HP Integrity rx1620-2 (1.6GHz/3MB Itanium 2)

SPECint2000 = 1452

SPECint_base2000 = 1452

SPEC license #: 3 | Tested by: HP Richardson | Test date: Oct-2004 | Hardware Avail: Jan-2005 | Software Avail: Dec-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	129	1081	129	1081
175.vpr	1400	118	1188	118	1188
176.gcc	1100	61.8	1779	61.8	1779
181.mcf	1800	122	1476	122	1476
186.crafty	1000	76.0	1315	76.0	1315
197.parser	1800	166	1084	166	1084
252.eon	1300	65.6	1982	65.6	1982
253.perlbmk	1800	125	1442	125	1442
254.gap	1100	86.6	1270	86.6	1270
255.vortex	1900	85.3	2228	85.3	2228
256.bzip2	1500	108	1392	108	1392
300.twolf	3000	185	1624	185	1624



Hardware

CPU:	Intel Itanium 2 (1.6 GHz/3MB, 533 MHz FSB)
CPU MHz:	1600
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	1-2
Parallel:	no
Primary Cache:	16KBI + 16KBD on chip, per core
Secondary Cache:	256KB (I+D) on chip, per core
L3 Cache:	3.0MB (I+D) on chip, per core
Other Cache:	N/A
Memory:	16GB (8x2GB DIMMs)
Disk Subsystem:	1x36GB 15K SCSI
Other Hardware:	N/A

Software

Operating System:	HPUX11i-TCOE B.11.23.0409
Compiler:	HP C/ANSI C Compiler C.06.00 HP aC++ Compiler C.06.00
File System:	vxfs
System State:	Multi-user

Notes/Tuning Information

```
Portability Flags
176.gcc     : -DHOST_WORDS_BIG_ENDIAN
186.crafty  : -DHP
252.eon     : -DFMAX_IS_DOUBLE
253.perlbmk : -DSPEC_CPU2000_HP
254.gap     : -DSPEC_CPU2000_HP -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO
              -DSYS_HAS_TIME_PROTO -DSYS_HAS_CALLOC_PROTO

Base Flags
  all       : +Oprofile=collect:all/+Oprofile=use
  C         : +Ofaster -exec +Otype_safety=ansi
  C++       : +Ofaster +Otype_safety=ansi

Peak Flags
  same as base (basepeak=true set globally)

Kernel Tunables:
  dbc_max_pct=20
  dbc_min_pct=20
  maxdsiz=3221225472
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
  maxssiz=401604608
  maxdsiz_64bit=4396972761584
  maxssiz_64bit=1073741824
  vps_pagesize=4096
  vps_ceiling=16384

Notes:

The system under test had the HP-UX 11i v2 (version 11.23.0409,
  September, 2004) Technical Computing Operating Environment and
  AR1204 compilers installed, along with the following patches:

  PHSS_31849 linker + fdp cumulative patch
  PHSS_31850 assembler patch
  PHSS_31851 Integrity Unwind Library
  PHSS_31852 aC++ Runtime (IA: A.05.60, PA A.03.60)
  PHSS_31853 Math Library Cumulative Patch
  PHSS_31854 milli cumulative patch

EFI command "cpuconfig" used prior to booting to
  deconfigure other processors if necessary
```