



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices
TYAN S2865 K8E Tomcat, AMD Opteron (TM) 150

SPECint2000 = 1696
SPECint_base2000 = 1601

SPEC license #: 49 Tested by: AMD, Austin, TX Test date: Jul-2005 Hardware Avail: Aug-2005 Software Avail: Aug-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	105	1329	105	1329	
175.vpr	1400	104	1340	101	1388	
176.gcc	1100	61.7	1783	61.4	1790	
181.mcf	1800	160	1122	131	1371	
186.crafty	1000	64.8	1543	58.4	1713	
197.parser	1800	117	1542	117	1540	
252.eon	1300	57.4	2265	51.4	2530	
253.perlbnk	1800	110	1630	110	1630	
254.gap	1100	64.8	1697	64.8	1697	
255.vortex	1900	78.5	2421	72.1	2635	
256.bzip2	1500	115	1305	113	1327	
300.twolf	3000	178	1685	155	1935	

Hardware

CPU: AMD Opteron (TM) 150 (939-pin)
 CPU MHz: 2400
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 1024KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4x512 MB DDR400 CL2.0
 Disk Subsystem: SATA, Western Digital WD740GD, 10000 rpm
 Other Hardware: None

Software

Operating System: Microsoft Windows XP Pro SP2
 Compiler: Intel C++ 8.0 build 20040714Z
 Microsoft Visual Studio .NET 7.0.9466 (libraries)
 MicroQuill Smartheap Library 7.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

shlw32M7.lib is the SmartHeap library V7.0 from MicroQuill www.microquill.com
 +FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability:

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Baseline C: -fast -arch:SSE2 -Oi- +FDO

Baseline C++: -fast -arch:SSE2 -GX -GR

Peak Tuning:

164.gzip: basepeak=yes
 175.vpr: -fast -arch:SSE2 +FDO
 -Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500
 176.gcc: -fast -arch:SSE2 +FDO -Oi- -Qunroll3
 181.mcf: -fast -QaxN +FDO
 186.crafty: -fast -arch:SSE2 +FDO
 197.parser: -arch:SSE2 +FDO -Oi- -Qipo
 252.eon: -fast -arch:SSE2 +FDO -Qansi_alias
 -Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500
 253.perlbnk: basepeak=yes



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices
TYAN S2865 K8E Tomcat, AMD Opteron (TM) 150

SPECint2000 = 1696
SPECint_base2000 = 1601

SPEC license #: 49 | Tested by: AMD, Austin, TX | Test date: Jul-2005 | Hardware Avail: Aug-2005 | Software Avail: Aug-2004

Notes/Tuning Information (Continued)

```
254.gap:      basepeak=yes
255.vortex:   -fast -arch:SSE +FDO -Oi- shlw32M7.lib
              -Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500
256.bzip2:    -fast -Qunroll2
300.twolf:    -fast -arch:SSE2 +FDO -Qunroll3 shlw32M7.lib -Qansi_alias
```

The tested system can be assembled using a standard ATX footprint, an Antec True 550 Watt EPS12V power supply, and a PCI or PCIe graphics card.
All memory slots were populated with Corsair CMX512-3200XL.
Memory timings manually set in BIOS: CAS=2, TRCD=2, TRAS=5, TRP=2
BIOS version 1.01