



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL140 G2 (3.8GHz, Intel Xeon)

SPECint_rate2000 = 42.3
SPECint_rate_base2000 = 42.1

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2005 Hardware Avail: Sep-2005 Software Avail: May-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	167	38.9	4	166	39.0
175.vpr	4	240	27.1	4	231	28.1
176.gcc	4	90.6	56.3	4	90.6	56.3
181.mcf	4	354	23.6	4	353	23.7
186.crafty	4	137	34.0	4	137	34.0
197.parser	4	200	41.7	4	200	41.7
252.eon	4	111	54.2	4	111	54.5
253.perlbnk	4	178	46.8	4	178	46.9
254.gap	4	110	46.3	4	109	46.9
255.vortex	4	127	69.3	4	127	69.5
256.bzip2	4	197	35.4	4	195	35.6
300.twolf	4	261	53.4	4	261	53.4

Hardware

CPU: Intel Xeon (3.8GHz, 2MB L2, 800MHz bus)
CPU MHz: 3800
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12K micro-ops I + 16KBD on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8x1024MB PC2-3200
Disk Subsystem: 1x80.0GB SATA
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
Compiler: Intel C++ Compiler for 32-bit applications, (Version 8.1 Build 20050524Z)
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning for C programs: -fast +FDO ONESTEP=yes shlw32M.lib

Base tuning for C++ programs: -fast -Qcxx_features +FDO ONESTEP=yes

Portability flags:

176.gcc: -Dalloca=_alloca /F10000000

186.crafty: -DNT_i386

253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDDL /MT

254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Peak tuning:

164.gzip: -fast +FDO ONESTEP=yes

175.vpr: -fast +FDO ONESTEP=yes

176.gcc: basepeak = 1

181.mcf: -fast +FDO ONESTEP=yes shlw32M.lib

186.crafty: -fast -Oa +FDO ONESTEP=yes shlw32M.lib

197.parser: -fast +FDO ONESTEP=yes

252.eon: -fast +FDO

253.perlbnk: -fast -Oa +FDO ONESTEP=yes shlw32M.lib

254.gap: -fast +FDO ONESTEP=yes

255.vortex: -fast +FDO ONESTEP=yes shlw32M.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL140 G2 (3.8GHz, Intel Xeon)

SPECint_rate2000 = 42.3
SPECint_rate_base2000 = 42.1

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2005 | Hardware Avail: Sep-2005 | Software Avail: May-2005

Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll11 +FDO ONESTEP=yes shlw32M.lib
300.twolf: -fast +FDO shlw32M.lib
BIOS Configuration Notes
Hyper-Threading Technology enabled