CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant DL385 (AMD Opteron (TM) 280)

SPECint2000 = 1666

SPECint_base2000 = 1500

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2005 | Hardware Avail: Sep-2005 | Software Avail: Apr-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	96.0	1459	96.7	1447
175.vpr	1400	118	1188	115	1221
176.gcc	1100	65.2	1688	64.4	1709
181.mcf	1800	245	735	154	1167
186.crafty	1000	48.8	2050	47.7	2098
197.parser	1800	157	1147	132	1363
252.eon	1300	56.9	2284	51.5	2523
253.perlbmk	1800	112	1605	98.3	1832
254.gap	1100	68.8	1599	66.7	1649
255.vortex	1900	79.5	2390	75.8	2505
256.bzip2	1500	110	1358	110	1358
300.twolf	3000	223	1347	171	1750



Hardware

CPU:	AMD Opteron (TM) 280
CPU MHz:	2400
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 2 cores/chip
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	64KBI + 64KBD (on chip) per core
Secondary Cache:	1024KB(I+D) (on chip) per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4x2048MB PC3200 CL3.0
Disk Subsystem:	1x36.4GB 15K Ultra320 SCSI
Other Hardware:	

Software

Operating System:	SuSE Linux Enterprise Server 9 (x86_64) SP 1 SuSE kernel 2.6.5-7.139-default
Compiler:	PathScale EKOPath(TM) Compiler Suite, Release 2.1
File System:	Linux/ext2
System State:	Multi-user run level 3

Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata  PASS2= -fb_opt fbdata
Base tuning for C programs:   -Ofast +FDO
Base tuning for C++ programs: -Ofast +FDO
Portability flags:
  176.gcc:     srcalt=64bitgcc
  186.crafty:  -DLINUX_i386
  252.eon:     -DHAS_ERRLIST -DSPEC_CPU2000_LP64 srcalt=fmax_errno
  253.perlbmk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
               -DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
  254.gap:     -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
               -DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64
  255.vortex:  -DSPEC_CPU2000_LP64 srcalt=closed_files
Peak tuning:
  164.gzip:    -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO
  175.vpr:     -O2 -ipa -OPT:alias=disjoint -CG:p2align_freq=500000
               -INLINE:aggressive=on
               -IPA:space=300:plimit=10000:callee_limit=5000:linear=on +FDO
  176.gcc:     -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO
  181.mcf:     -O3 -ipa -IPA:field_reorder=on -m32 +FDO
  186.crafty:  -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
    197.parser:  -O3 -ipa -m32 -IPA:ctype=on +FDO
    252.eon:     -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
                 -OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
                 -LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
    253.perlbmk: -O2 -ipa -OPT:Ofast:transform_to_memlib=off
                 -fno-math-errno -IPA:plimit=10000 +FDO
    254.gap:     -Ofast -IPA:min_hotness=5 -OPT:alias=disjoint -CG:movnti=1 +FDO
    255.vortex:  -Ofast -OPT:goto=off +FDO
    256.bzip2:   basepeak=true
    300.twolf:   -O2 -CG:gcm=off:p2align_freq=100000
                 -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
                 -WOPT:mem_opnds=on -m32 +FDO
BIOS Configuration Notes
  Node Interleaving Disabled
Other Configuration Notes
   Single-processor kernel was used
```