CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY RX220, AMD Opteron (TM) 250

SPECint_rate2000 = 19.6

SPECint_rate_base2000 = 18.0

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Dec-2005 | Software Avail: Mar-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	1	106	15.3	1	106	15.3
175.vpr	1	107	15.2	1	104	15.6
176.gcc	1	62.0	20.6	1	62.4	20.5
181.mcf	1	161	13.0	1	135	15.4
186.crafty	1	64.3	18.0	1	58.7	19.8
197.parser	1	120	17.5	1	120	17.5
252.eon	1	69.9	21.6	1	49.8	30.3
253.perlbmk	1	114	18.3	1	105	19.8
254.gap	1	65.0	19.6	1	65.0	19.6
255.vortex	1	77.1	28.6	1	70.4	31.3
256.bzip2	1	118	14.8	1	115	15.1
300.twolf	1	187	18.7	1	157	22.1

Hardware

CPU:	AMD Opteron (TM) 250 processor (2.40 GHz)
CPU MHz:	2400
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	64KBI + 64KBD on chip
Secondary Cache:	1024KB (I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4x2048MB DDR-RAM PC3200R
Disk Subsystem:	Western Digital WD2500 (SATA, 7.2krpm)
Other Hardware:	None

Software

Operating System:	Windows Server 2003 Enterprise Edition + SP1
Compiler:	Intel C++ 8.0 Build 20040318Z (for 32-bit applications), Microsoft Visual Studio .Net 2003 7.1.3088 (for libraries), SmartHeap Library Version 8.0 from http://www.microquill.com
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
GENERAL
+FDO: PASS1= -Qprof_gen  PASS2= -Qprof_use

Portability flags
   176.gcc:     -Dalloca=_alloca /F10000000
   186.crafty:  -DNT_i386
   253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
   254.gap:     -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags
   for C programs:   -fast -arch:SSE2 -Oi- +FDO
   for C++ programs: -fast -GX -GR +FDO

Peak tuning flags
   164.gzip:    basepeak=yes
   175.vpr:     -fast -arch:SSE2 -Qoption,c,-ip_ninl_max_stats=2000,
                -ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
   176.gcc:     -fast -arch:SSE2 -Oi- -Qunroll3 +FDO shlw32M.lib
   181.mcf:     -fast -QaxN +FDO shlw32M.lib
   186.crafty:  -fast -arch:SSE2 +FDO ONESTEP=yes shlw32M.lib
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
    197.parser:  basepeak=yes
    252.eon:     -fast -arch:SSE2 -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000,
                 -ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes shlw32M.lib
    253.perlbmk: -fast -arch:SSE2 -Oi- +FDO ONESTEP=yes shlw32M.lib
    254.gap:     basepeak=yes
    255.vortex:  -fast -arch:SSE -Oi- -Qoption,c,-ip_ninl_max_stats=2000,
                 -ip_ninl_max_total_stats=4500 +FDO shlw32M.lib
    256.bzip2:   -fast -Qunroll2 shlw32M.lib
    300.twolf:   -fast -arch:SSE2 -Qansi_alias +FDO ONESTEP=yes shlw32M.lib


    'start /b /wait /affinity' command is used to bind CPU(s) to processes

    boot options:  /Execute
                   /NOPAE
                   /USEPMTIMER
    BIOS settings: Memory timing=1T

    This result was measured with 32-bit binaries using the 32-bit version of
    the operating system.

    For information about Fujitsu Siemens Computers in your country please see:
    http://www.fujitsu-siemens.com/countries
```