



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices
TYAN Thunder K8SD Pro (S2882-D), AMD Opteron (TM) 256

SPECint2000 = 2043
SPECint_base2000 = 1821

SPEC license #: 49 Tested by: AMD Austin, Texas Test date: Mar-2006 Hardware Avail: Apr-2006 Software Avail: Jan-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	77.8	1798	77.5	1805	
175.vpr	1400	99.2	1411	94.5	1481	
176.gcc	1100	53.9	2040	54.8	2008	
181.mcf	1800	226	795	142	1264	
186.crafty	1000	37.8	2648	36.9	2709	
197.parser	1800	134	1346	105	1709	
252.eon	1300	42.6	3054	36.5	3559	
253.perlbnk	1800	90.8	1982	79.4	2268	
254.gap	1100	57.1	1926	57.1	1926	
255.vortex	1900	64.3	2954	59.7	3185	
256.bzip2	1500	91.3	1643	91.3	1643	
300.twolf	3000	187	1601	145	2063	

Hardware

CPU: AMD Opteron (TM) 256
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1-2
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 1024KB (I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 2x512MB, DDR400 CL2 ECC Reg
 Disk Subsystem: SATA, 250 GB
 Other Hardware: None

Software

Operating System: SuSE Linux Enterprise Server 9 SP3 (64-bit)
 Compiler: PathScale EKOPath(TM) Compiler Suite, Release 2.3
 File System: Linux/ext3
 System State: Multi-user, run level 3

Notes/Tuning Information

+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata

Baseline optimization flags:

C programs: -Ofast +FDO
 C++ programs: -Ofast +FDO

Portability Flags:

186.crafty: -DLINUX_i386
 252.eon: -DHAS_ERRLIST -DSPEC_CPU2000_LP64
 253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
 -DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
 254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
 -DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64
 255.vortex: -DSPEC_CPU2000_LP64

Peak Tuning:

164.gzip: -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO
 175.vpr: -O3 -ipa -m32 +FDO
 176.gcc: -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices

TYAN Thunder K8SD Pro (S2882-D), AMD Opteron (TM) 256

SPECint2000 = 2043

SPECint_base2000 = 1821

SPEC license #: 49 | Tested by: AMD Austin, Texas | Test date: Mar-2006 | Hardware Avail: Apr-2006 | Software Avail: Jan-2006

Notes/Tuning Information (Continued)

```
181.mcf:      -O3 -ipa -IPA:field_reorder=on -m32 +FDO
186.crafty:   -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
197.parser:   -O3 -ipa -m32 -IPA:ctype=on +FDO
252.eon:      -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
              -OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
              -LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
253.perlbmk:  -O2 -ipa -OPT:Ofast:transform_to_memlib=off
              -fno-math-errno -IPA:plimit=10000 +FDO
255.vortex:   -Ofast -OPT:goto=off -CG:p2align=on
              -GRA:optimize_boundary=on -IPA:min_hotness=120 +FDO
256.bzip2:    basepeak = true
300.twolf:    -O2 -CG:gcm=off:p2align_freq=100000
              -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
              -WOPT:mem_opnds=on -m32 +FDO
```

Corsair CMX512RE-3200LL (XMS3200REv2.1) memory used in Dual Channel configuration.
BIOS rev 3.06
The tested system can be assembled using a standard ATX case and an Antec True 550 watt EPS12V Power Supply.
Single-processor kernel (2.6.5-7.244-default) was used.