



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX200 S3, Intel Xeon 5110 processor, 1.60 GHz

SPECint_rate2000 = 36.0

SPECint_rate_base2000 = 36.0

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: May-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

70 60 50 40 30 20 10				Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
				164.gzip	2	143	22.7	2	143	22.7
				175.vpr	2	123	26.3	2	123	26.3
				176.gcc	2	62.4	40.9	2	62.4	40.9
				181.mcf	2	113	37.0	2	113	37.0
				186.crafy	2	68.5	33.9	2	68.5	33.9
				197.parser	2	145	28.8	2	145	28.8
				252.eon	2	62.8	48.0	2	62.8	48.0
				253.perlbnk	2	94.8	44.0	2	94.8	44.0
				254.gap	2	68.9	37.1	2	68.9	37.1
				255.vortex	2	72.3	60.9	2	72.3	60.9
				256.bzip2	2	133	26.2	2	133	26.2
				300.twolf	2	164	42.4	2	164	42.4

Hardware

CPU: Intel Xeon 5110 processor (1.60 GHz, 4MB L2, 1066 MHz system bus)
CPU MHz: 1600
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32KBI + 32KBD on chip, per core
Secondary Cache: 4096KB(I+D) on chip, shared
L3 Cache: N/A
Other Cache: N/A
Memory: 8x1GB DDRII-RAM PC2-4200F (CAS 4-4-4)
Disk Subsystem: Seagate ST373454SS (SAS, 15.4krpm, 73GB)
Other Hardware: none

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler: Intel C++ Compiler 9.1
Build 20060323Z (for 32-bit applications),
Microsoft Visual Studio .Net 2003
7.1.3088 (for libraries),
SmartHeap Library Version 8.0
from <http://www.microquill.com>
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability flags

176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags

for C programs: -fast +FDO shlw32m.lib
for C++ programs: -fast -Qcxx_features +FDO shlw32m.lib

Peak tuning flags

same as baseline (basepeak=true set globally)

The system bus runs at 1066 MHz

This result was measured with 32-bit binaries using the 32-bit version of the operating system.



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX200 S3, Intel Xeon 5110 processor, 1.60 GHz

SPECint_rate2000 = 36.0

SPECint_rate_base2000 = 36.0

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: May-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>