



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX200 S3, Intel Xeon 5150 processor, 2.66 GHz

SPECfp_rate2000 = 44.5

SPECfp_rate_base2000 = 44.5

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jun-2006 | Hardware Avail: Jul-2006 | Software Avail: Jan-2006

					Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
150	120	90	60	30	168.wupwise	2	57.7	64.4	2	57.7	64.4
					171.swim	2	210	34.3	2	210	34.3
					172.mgrid	2	138	30.2	2	138	30.2
					173.applu	2	152	32.1	2	152	32.1
					177.mesa	2	52.6	61.7	2	52.6	61.7
					178.galgel	2	60.3	112	2	60.3	112
					179.art	2	48.6	124	2	48.6	124
					183.quake	2	86.0	35.1	2	86.0	35.1
					187.facerec	2	83.0	53.1	2	83.0	53.1
					188.amp	2	126	40.5	2	126	40.5
					189.lucas	2	145	32.0	2	145	32.0
					191.fma3d	2	141	34.6	2	141	34.6
					200.sixtrack	2	110	23.2	2	110	23.2
					301.apsi	2	180	33.5	2	180	33.5

Hardware

CPU: Intel Xeon 5150 processor (2.66 GHz, 4MB L2, 1333 MHz system bus)
CPU MHz: 2666
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32KBI + 32KBD on chip, per core
Secondary Cache: 4096KB(I+D) on chip, shared
L3 Cache: N/A
Other Cache: N/A
Memory: 8x1GB DDRII-RAM PC2-5300F (CAS 5-5-5)
Disk Subsystem: Seagate ST336754SS (SAS, 15.4krpm, 36GB)
Other Hardware: none

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 9 with SP3
Kernel 2.6.5-7.244-smp on an x86_64
Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T
Build 20060120 (for 64-bit applications)
File System: ext3
System State: Multi-user run level 3

Notes/Tuning Information

GENERAL

+FDO implies feedback-directed optimization
PASS1: -prof_gen PASS2: -prof_use

Optimization flags
ONESTEP=yes set for all benchmarks

Portability flags
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

Base tuning flags
for Fortran and C programs: -fast +FDO

Peak tuning flags
same as baseline (basepeak=true set globally)



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX200 S3, Intel Xeon 5150 processor, 2.66 GHz

SPECfp_rate2000 = 44.5

SPECfp_rate_base2000 = 44.5

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jun-2006 | Hardware Avail: Jul-2006 | Software Avail: Jan-2006

Notes/Tuning Information (Continued)

The system bus runs at 1333 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>