# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Dell

PowerEdge 1955 (Intel Xeon processor 5110, 1.60GHz)

SPECint_rate2000 = 68.7

SPECint_rate_base2000 = 68.6

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: May-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006




| Benchmark | Base Copies | Base Runtime | Base Ratio | Copies | Runtime | Ratio |
|---|---|---|---|---|---|---|
| 164.gzip | 4 | 144 | 45.1 | 4 | 144 | 45.1 |
| 175.vpr | 4 | 123 | 52.6 | 4 | 122 | 53.4 |
| 176.gcc | 4 | 65.0 | 78.5 | 4 | 65.0 | 78.5 |
| 181.mcf | 4 | 119 | 70.1 | 4 | 119 | 70.1 |
| 186.crafty | 4 | 68.5 | 67.7 | 4 | 68.6 | 67.6 |
| 197.parser | 4 | 159 | 52.6 | 4 | 158 | 52.8 |
| 252.eon | 4 | 62.2 | 97.0 | 4 | 62.3 | 96.8 |
| 253.perlbmk | 4 | 95.5 | 87.4 | 4 | 95.5 | 87.4 |
| 254.gap | 4 | 90.5 | 56.4 | 4 | 89.8 | 56.8 |
| 255.vortex | 4 | 75.0 | 118 | 4 | 75.0 | 118 |
| 256.bzip2 | 4 | 144 | 48.4 | 4 | 144 | 48.2 |
| 300.twolf | 4 | 164 | 85.1 | 4 | 164 | 85.1 |

### Hardware

| | |
|---|---|
| CPU: | Intel Xeon processor 5110 (1066MHz system bus) |
| CPU MHz: | 1600 |
| FPU: | Integrated |
| CPU(s) enabled: | 4 cores, 2 chips, 2 cores/chip |
| CPU(s) orderable: | 1,2 |
| Parallel: | No |
| Primary Cache: | 32KB(I) + 32KB(D) on chip, per core |
| Secondary Cache: | 4096KB(I+D) on chip, shared |
| L3 Cache: | N/A |
| Other Cache: | N/A |
| Memory: | 8 x 1GB 667MHz ECC CL5 DDR2 FB-DIMM |
| Disk Subsystem: | 1 x 73GB SAS 10000 RPM |
| Other Hardware: | None |

### Software

| | |
|---|---|
| Operating System: | Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit) |
| Compiler: | Intel C++ Compiler 9.1 for IA32(20060323Z)<br>Microsoft Visual Studio .NET 2003(7.1.3088)<br>MicroQuill SmartHeap Library 8.0 |
| File System: | NTFS |
| System State: | Default |

## Notes/Tuning Information

```
GENERAL
  ONESTEP=yes
  +FDO:   PASS1=-Qprof_gen  PASS2=-Qprof_use
PORTABILITY FLAGS
  176.gcc:     -Dalloca=_alloca /F10000000
  186.crafty:  -DNT_i386
  253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
  254.gap:     -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
BASE TUNING
  C:           -fast +FDO shlW32M.lib
  C++:         -fast -Qcxx_features +FDO
PEAK TUNING
  164.gzip:    -fast +FDO
  175.vpr:     -fast +FDO
  176.gcc:     basepeak=yes
  181.mcf:     basepeak=yes
  186.crafty:  -fast -Oa +FDO shlW32M.lib
  197.parser:  -fast +FDO
  252.eon:     -fast +FDO
  253.perlbmk: basepeak=yes
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation



## Notes/Tuning Information (Continued)

```
254.gap:     -fast +FDO
255.vortex   basepeak=yes
256.bzip2:   -fast -Qunroll1 -Oa +FDO
300.twolf:   basepeak=yes
```