



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY BX630, AMD Opteron (TM) 885

SPECint_rate2000 = 155
SPECint_rate_base2000 = 140

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Mar-2006 | Software Avail: Jul-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	102	128	8	104	125
175.vpr	8	118	110	8	116	112
176.gcc	8	62.6	163	8	63.0	162
181.mcf	8	253	66.2	8	195	85.8
186.crafty	8	59.0	157	8	53.0	175
197.parser	8	124	134	8	125	134
252.eon	8	52.7	229	8	40.7	297
253.perlbnk	8	98.9	169	8	90.5	185
254.gap	8	67.8	151	8	67.3	152
255.vortex	8	86.2	205	8	73.1	241
256.bzip2	8	132	106	8	124	112
300.twolf	8	193	144	8	144	193

Hardware

CPU: AMD Opteron (TM) 885 processor (2.60 GHz)
CPU MHz: 2600
FPU: Integrated
CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip
CPU(s) orderable: 1,2,4
Parallel: No
Primary Cache: 64KBI + 64KBD on chip, per core
Secondary Cache: 1024KB (I+D) on chip, per core
L3 Cache: N/A
Other Cache: N/A
Memory: 16x2GB DDR-RAM PC3200R (CAS 3-3-3)
Disk Subsystem: Seagate ST373454SS (SAS, 15.4krpm)
Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1
Compiler: Intel C++ 9.1
Build 20060519Z (for 32-bit applications),
Microsoft Visual Studio .Net 2003
7.1.3088 (for libraries),
SmartHeap Library Version 8.0
from <http://www.microquill.com>
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

Portability flags

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags

for C programs: -fast -arch:SSE2 -Oi- +FDO
for C++ programs: -O3 -Qipo -Qcxx-features +FDO

Peak tuning flags

164.gzip: -O3 -Qipo -QxW +FDO
175.vpr: -O3 -Qipo -QxW -Qoption,c,-ip_ninl_max_stats=2000,
-ip_ninl_max_total_stats=4500 +FDO
176.gcc: -O3 -Qipo -QxW -Oi- -Qunroll3 +FDO shlw32M.lib
181.mcf: -O3 -Qipo -QaxN +FDO shlw32M.lib
186.crafty: -O3 -Qipo -QxW +FDO shlw32M.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY BX630, AMD Opteron (TM) 885

SPECint_rate2000 = 155
SPECint_rate_base2000 = 140

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Mar-2006 | Software Avail: Jul-2006

Notes/Tuning Information (Continued)

```
197.parser: -Oi -Qipo -QxW +FDO shlw32M.lib
252.eon: -O3 -Qipo -QxW -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000,
        -ip_ninl_max_total_stats=4500 +FDO shlw32M.lib
253.perlbnk: -O3 -Qipo -QxW +FDO shlw32M.lib
254.gap: -O3 -Qipo -QxW +FDO shlw32M.lib
255.vortex: -O3 -Qipo -arch:SSE -Oi- -Qoption,c,-ip_ninl_max_stats=2000,
        -ip_ninl_max_total_stats=4500 +FDO shlw32M.lib
256.bzip2: -O3 -Qipo -Qunroll2 shlw32M.lib
300.twolf: -O3 -Qipo -QxW -Qunroll3 -Qansi_alias +FDO shlw32M.lib
```

'start /b /wait /affinity' command is used to bind CPU(s) to processes

Boot options: /noexecute=alwaysoff

BIOS settings: Memory timing=1T
DRAM Bank Interleave=AUTO

This result was measured with 32-bit binaries using the 32-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>