



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices

Tyan Thunder K9HM (S3992), AMD Opteron (TM) 2210

SPECint2000 = 1297

SPECint_base2000 = 1150

SPEC license #: 49 Tested by: AMD Austin, TX Test date: Jul-2006 Hardware Avail: Sep-2006 Software Avail: Sep-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	160	874	141	995	
175.vpr	1400	168	835	132	1059	
176.gcc	1100	118	934	80.9	1360	
181.mcf	1800	184	978	150	1203	
186.crafty	1000	82.6	1211	78.6	1273	
197.parser	1800	156	1157	156	1155	
252.eon	1300	78.4	1658	70.2	1852	
253.perlbnk	1800	134	1346	131	1378	
254.gap	1100	88.4	1245	88.4	1245	
255.vortex	1900	108	1755	102	1870	
256.bzip2	1500	147	1023	143	1052	
300.twolf	3000	262	1144	210	1429	

Hardware

CPU: AMD Opteron (TM) 2210
 CPU MHz: 1800
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: no
 Primary Cache: 64KBI + 64KBD on chip per core
 Secondary Cache: 1024KB (I+D) on chip per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4x512MB, DDR2-667 CL4 ECC Reg
 Disk Subsystem: IDE, 120 GB
 Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition SP1 (32-bit)
 Compiler: Intel C++ 9.0 build 20050912Z for IA32
 Microsoft Visual Studio .NET 7.0.9466 (libraries)
 MicroQuill Smartheap Library 7.0
 File System: NTFS
 System State: default

Notes/Tuning Information

shlw32M.lib is the SmartHeap library V7.0 from MicroQuill (www.microquill.com)

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability:

176.gcc: -Dalloca=_alloca /F10000000

186.crafty: -DNT_i386

253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT

254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Baseline C: -O3 -Qipo -Op +FDO

Baseline C++: -O3 -Qipo -Qcxx-features +FDO

Peak Tuning:

164.gzip: -O3 -Qipo -QxW +FDO

175.vpr: -O3 -Qipo -QxW +FDO

-Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500

176.gcc: -O3 -Qipo -QxW -Oi- -Qunroll3 +FDO

181.mcf: -O3 -Qipo -QaxN +FDO

186.crafty: -O3 -Qipo -QxW +FDO

197.parser: -QxW +FDO -Oi- -Qipo

252.eon: -O3 -Qipo -QxW +FDO -Qansi_alias

-Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500

253.perlbnk: -O3 -Qipo -QxW +FDO

Standard Performance Evaluation Corporation

info@spec.org

<http://www.spec.org>



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices

Tyan Thunder K9HM (S3992), AMD Opteron (TM) 2210

SPECint2000 = 1297

SPECint_base2000 = 1150

SPEC license #: 49 | Tested by: AMD Austin, TX | Test date: Jul-2006 | Hardware Avail: Sep-2006 | Software Avail: Sep-2005

Notes/Tuning Information (Continued)

```
254.gap:          basepeak = yes
255.vortex:       -O3 -Qipo -arch:SSE +FDO -Oi- shlw32M.lib
                  -Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500
256.bzip2:        -O3 -Qipo -Qunroll2
300.twolf:        -O3 -Qipo -QxW +FDO -Qunroll3 shlw32M.lib -Qansi_alias
system can be built using a standard ATX case and a Zippy 700W PSL-6701P power supply
Half memory slots populated on CPU in dual channel configuration
```