



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Hewlett-Packard Company**  
ProLiant BL480c (1.60 GHz, Intel Xeon processor 5110)

SPECfp2000 = **1904**  
SPECfp\_base2000 = **1747**

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2006 Hardware Avail: Jun-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	56.6	2828	56.6	2828	
171.swim	3100	136	2272	131	2360	
172.mgrid	1800	156	1152	117	1542	
173.applu	2100	140	1496	113	1864	
177.mesa	1400	83.0	1688	76.2	1837	
178.galgel	2900	76.1	3812	76.1	3812	
179.art	2600	40.5	6421	40.5	6421	
183.quake	1300	75.0	1733	61.0	2130	
187.facerec	1900	104	1827	75.8	2506	
188.amp	2200	182	1206	182	1206	
189.lucas	2000	130	1544	129	1556	
191.fma3d	2100	153	1370	153	1370	
200.sixtrack	1100	181	609	181	609	
301.apsi	2600	238	1093	228	1140	

### Hardware

CPU: Intel Xeon processor 5110 (1.60 GHz, 4 MB L2 shared, 1066 MHz bus)  
CPU MHz: 1600  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 2 cores/chip  
CPU(s) orderable: 1,2 chips  
Parallel: No  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 4 MB I+D on chip per chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 16 GB (8x2048 MB PC2-5300F)  
Disk Subsystem: 2x36 GB 10 K SAS  
Other Hardware:

### Software

Operating System: RedHat Enterprise Linux 4.0 Advanced Server for AMD64/EM64T, Update 3 Kernel 2.6.9-34.EL  
Compiler: Intel C++ Compiler for EM64T-based applications, (Version 9.1 Build 20060323)  
Intel Fortran Compiler for EM64T-based applications, (Version 9.1 Build 20060323)  
PathScale EKOPATH(TM) Compiler Suite, Release 2.4  
File System: ext2  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1= -prof_gen PASS2=-prof_use (Intel Compiler)
+FDO: PASS1= -fb_create fbdata PASS2=-fb_opt fbdata (PathScale Compiler)
ifort is the Intel Fortran compiler, icc is the Intel C++ compiler; and
pathf95 is PathScale Fortran compiler, pathcc is the PathScale C compiler.
Base tuning for C programs: icc -fast -auto_ilp32 +FDO
Base tuning for FORTRAN programs: ifort -fast +FDO
Portability:
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI
Peak tuning:
168.wupwise: basepeak=1
171.swim: pathf95 -Ofast -LNO:fusion=2:simd=0 -WOPT:val=0 -march=em64t
172.mgrid: pathf95 -Ofast -CG:load_exe=0 -LNO:blocking=off:prefetch_ahead=5
-OPT:ro=3:unroll_size=256 -WOPT:mem_opnds=on -march=em64t
173.applu: pathf95 -O3 -ipa -CG:load_exe=0
-LNO:fission=1:fusion=2:blocking=off:full_unroll_size=9000
-OPT:IEEE_a=3:ro=3 -TENV:X=3 -march=em64t
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Hewlett-Packard Company**  
ProLiant BL480c (1.60 GHz, Intel Xeon processor 5110)

SPECfp2000 = 1904  
SPECfp\_base2000 = 1747

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2006 | Hardware Avail: Jun-2006 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

```

177.mesa: pathcc -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on
          -GRA:optimize_boundary=on -march=em64t +FDO
178.galgel: basepeak=1
179.art: basepeak=1
183.quake: icc -fast +FDO ONESTEP=yes -rcd -auto-ilp32
187.facerec: pathf95 -Ofast -IPA:plimit=1500 -LNO:fusion=2
            -OPT:IEEE_NaN_Inf=off:ro=3:unroll_size=0 -march=em64t +FDO
188.ammamp: basepeak=1
189.lucas: ifort -fast ONESTEP=yes
191.fma3d: basepeak=1
200.sixtrack: basepeak=1
301.apsi: pathf95 -Ofast -CG:load_exe=0 -LNO:opt=0:prefetch=1 -march=em64t

```

BIOS Configuration Notes  
Power Regulator set to Static High Performance Mode

Other Configuration Notes  
Single processor kernel used