



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire E20K (36 processor)

SPECint\_rate2000 = 853  
SPECint\_rate\_base2000 = 733

SPEC license #: 6 Tested by: Sun Microsystems Test date: Jul-2006 Hardware Avail: Aug-2006 Software Avail: Jun-2006

2000	1500	1000	500	Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
				164.zip	72	195	599	72	179	654
				175.vpr	72	168	694	72	163	719
				176.gcc	72	190	484	216	301	917
				181.mcf	72	252	596	216	635	710
				186.crafty	72	82.9	1007	72	76.5	1092
				197.parser	72	213	705	72	184	819
				252.eon	72	104	1049	72	97.7	1111
				253.perlbnk	72	170	884	72	163	921
				254.gap	72	271	339	72	190	483
				255.vortex	72	116	1372	72	108	1468
				256.bzip2	72	161	780	72	156	801
				300.twolf	72	297	845	72	270	928

### Hardware

CPU: UltraSPARC IV+  
 CPU MHz: 1800  
 FPU: Integrated  
 CPU(s) enabled: 72 cores, 36 chips, 2 cores/chip  
 CPU(s) orderable: 4-36 (order by number of chips, groups of 4)  
 Parallel: No  
 Primary Cache: 64KBI+64KBD per core on chip  
 Secondary Cache: 2MB(I+D) per chip (on chip)  
 L3 Cache: 32MB(I+D) per chip (off chip)  
 Other Cache: None  
 Memory: 144GB 16-way interleaved (288x512MB)  
 Disk Subsystem: Sun StorageTek S1 Disk Array (2x73GB, 10000 RPM)  
 Sun StorageTek 6130 Array (14x73GB, 10000 RPM)  
 Other Hardware: None

### Software

Operating System: Solaris 10 6/06  
 Compiler: Sun Studio 11  
 File System: ufs  
 System State: Multi-User

## Notes/Tuning Information

Compiler invocation:

C: cc  
CXX: CC

Integer base flags:

-fast -xipo=2 with ONESTEP=yes and feedback

Integer peak flags:

ONESTEP=yes for all benchmarks  
Profile feedback used for those marked with +FDO

164.zip: -x04 -xbuiltin=%all -xtarget=native -xalias\_level=std  
 -xipo=2 -Wc,-Qeps:enabled=1,-Qeps:rp\_filtering\_margin=30,  
 -Qeps:do\_spec\_load=1 +FDO  
 175.vpr: -fast -Wc,-Qeps:enabled=1,-Qeps:do\_spec\_load=1,  
 -Qeps:rp\_filtering\_margin=30 -xipo=2 -xpagesize\_stack=8K  
 -lmopt -lm +FDO



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire E20K (36 processor)

SPECint\_rate2000 = 853  
SPECint\_rate\_base2000 = 733

SPEC license #: 6 Tested by: Sun Microsystems Test date: Jul-2006 Hardware Avail: Aug-2006 Software Avail: Jun-2006

## Notes/Tuning Information (Continued)

```

176.gcc: -fast -xipo=2 -Wc,-Qicache-chbab=1 -Wc,-Qeps:enabled=1
        -Qeps:ws=32 -Wc,-Qdepgraph-early_cross_call=1
        -Wc,-Qms_pipe-pref_prolog -ll2amm +FDO
181.mcf: -fast -xipo=2 -xprefetch_level=2
186.crafty: -fast -xpagesize=8k -xipo=2 -xalias_level=strong
        -W2,-Ashort_ldst -xinline= -xprefetch -xrestrict
        +FDO (-xlinkopt during pass2)
197.parser: -fast -xipo=2 -xalias_level=strong -Wc,Qgsched-T6
        -Wc,-Qipa:valueprediction -Wc,-Qms_pipe-prefstrong=0,
        -Qlp-pt=weak +FDO
252.eon: -fast -xipo=2 -xalias_level=compatible -Qoption cg
        -Qeps:enabled=1 -xvector -Qoption iropt -Abcopy -xunroll=16
        +FDO
253.perlbnk: -fast -xipo -Wc,-Qeps:enabled=1,-Qeps:ws=16 -xalias_level=std
        -xsafe=mem -Wc,-Qiselect-funcalign=128,-Qicache-chbab=1
        -Wc,-Qiselect-sw_pf_tbl_th=40,-Qeps:do_spec_load=1 +FDO
254.gap: -fast -W2,-Abcopy -xvector -xprefetch_level=3 +FDO
255.vortex: -fast -xrestrict -xipo=2 -Wc,-Qeps:enabled=1
        -W2,-Ainline:recursion=1:cs=400:irs=5000
        -Wc,-Qdepgraph-early_cross_call=1 -Wc,-Qiselect-funcalign=64
        -Wc,-Qpeep-Sh0 -W2,-crit -xprefetch=latx:1.7 -fsimple=1
        -Wc,-Qiselect-sw_pf_tbl_th=30 -Wc,-Qicache-chbab=1
        -W2,-Ainline:inc=300 -ll2amm +FDO
256.bzip2: -fast -xipo=2 -xalias_level=strong -xrestrict
        -Wc,-Qeps:enabled=1,-Qeps:do_spec_load=1 +FDO
300.twolf: -fast -xalias_level=strong -xsafe=mem -xipo=2
        -xprefetch=no%auto -Wc,-Qms_pipe+intdivusefp -xinline= +FDO

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0: rm -rf ./feedback.profile ./SunWS_cache
PASS1: -xprofile=collect:./feedback
PASS2: -xprofile=use:./feedback

```

Portability:

```

176.gcc: -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSUN
253.perlbnk: -DSPEC_CPU2000_SOLARIS
254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
        -DSYS_HAS_CALLOC_PROTO

```

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```

For 254.gap peak, jobs were bound to cores using the pbind command.

The system was configured with multiple file systems.  
The O/S was installed on one disk of the Sun StorageTek S1 Disk  
Array (ufs, ufs w/logging). The benchmark was run on the Sun  
StorageTek 6130 Array, using H/W Raid 5 and ufs with ufs logging



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire E20K (36 processor)

SPECint\_rate2000 = 853

SPECint\_rate\_base2000 = 733

SPEC license #: 6 Tested by: Sun Microsystems Test date: Jul-2006 Hardware Avail: Aug-2006 Software Avail: Jun-2006

## Notes/Tuning Information (Continued)

file system.