



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire E4900 (12 processor)

SPECint\_rate2000 = 296  
SPECint\_rate\_base2000 = 269

SPEC license #: 6 Tested by: Sun Microsystems Test date: Jun-2006 Hardware Avail: Aug-2006 Software Avail: Jun-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	24	184	212	24	167	234
175.vpr	24	156	249	24	149	261
176.gcc	24	123	250	24	98.8	310
181.mcf	24	227	221	24	193	260
186.crafty	24	81.3	343	24	75.0	371
197.parser	24	205	244	24	176	285
252.eon	24	104	349	24	98.1	369
253.perlbnk	24	164	305	24	157	320
254.gap	24	216	142	24	203	151
255.vortex	24	103	515	24	95.8	552
256.bzip2	24	152	274	24	148	281
300.twolf	24	296	282	24	266	314

### Hardware

CPU: UltraSPARC IV+  
CPU MHz: 1800  
FPU: Integrated  
CPU(s) enabled: 24 cores, 12 chips, 2 cores/chip  
CPU(s) orderable: 4, 8, 12 (order by number of chips)  
Parallel: No  
Primary Cache: 64KBI+64KBD per core on chip  
Secondary Cache: 2MB(I+D) per chip (on chip)  
L3 Cache: 32MB(I+D) per chip (off chip)  
Other Cache: None  
Memory: 48GB 16-way interleaved (96x512GB)  
Disk Subsystem: Sun StorageTek D240 Media Tray (2x73GB, 10000 RPM)  
Sun StorageTek 6130 Array (14x73GB, 10000 RPM)  
Other Hardware: None

### Software

Operating System: Solaris 10 6/06  
Compiler: Sun Studio 11  
File System: ufs  
System State: Multi-User

## Notes/Tuning Information

Compiler invocation:

C: cc  
CXX: CC

Integer base flags:

-fast -xipo=2 with ONESTEP=yes and feedback

Integer peak flags:

ONESTEP=yes for all benchmarks  
Profile feedback used for those marked with +FDO

164.gzip: -x04 -xbuiltin=%all -xtarget=native -xalias\_level=std  
-xipo=2 -Wc,-Qeps:enabled=1,-Qeps:rp\_filtering\_margin=30,  
-Qeps:do\_spec\_load=1 +FDO  
175.vpr: -fast -Wc,-Qeps:enabled=1,-Qeps:do\_spec\_load=1,  
-Qeps:rp\_filtering\_margin=30 -xipo=2 -xpagesize\_stack=8K  
-lmopt -lm +FDO



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire E4900 (12 processor)

SPECint\_rate2000 = 296  
SPECint\_rate\_base2000 = 269

SPEC license #: 6 Tested by: Sun Microsystems Test date: Jun-2006 Hardware Avail: Aug-2006 Software Avail: Jun-2006

## Notes/Tuning Information (Continued)

```

176.gcc: -fast -xipo=2 -Wc,-Qicache-chbab=1 -Wc,-Qeps:enabled=1
        -Qeps:ws=32 -Wc,-Qdepgraph-early_cross_call=1
        -Wc,-Qms_pipe-pref_prolog -ll2amm +FDO
181.mcf: -fast -xipo=2 -xprefetch_level=2
186.crafty: -fast -xpagesize=8k -xipo=2 -xalias_level=strong
        -W2,-Ashort_ldst -xinline= -xprefetch -xrestrict
        +FDO (-xlinkopt during pass2)
197.parser: -fast -xipo=2 -xalias_level=strong -Wc,Qgsched-T6
        -Wc,-Qipa:valueprediction -Wc,-Qms_pipe-prefstrong=0,
        -Qlp-pt=weak +FDO
252.eon: -fast -xipo=2 -xalias_level=compatible -Qoption cg
        -Qeps:enabled=1 -xvector -Qoption iropt -Abcopy -xunroll=16
        +FDO
253.perlbnk: -fast -xipo -Wc,-Qeps:enabled=1,-Qeps:ws=16 -xalias_level=std
        -xsafe=mem -Wc,-Qiselect-funcalign=128,-Qicache-chbab=1
        -Wc,-Qiselect-sw_pf_tbl_th=40,-Qeps:do_spec_load=1 +FDO
254.gap: -fast -W2,-Abcopy -xvector -xprefetch_level=3 +FDO
255.vortex: -fast -xrestrict -xipo=2 -Wc,-Qeps:enabled=1
        -W2,-Ainline:recursion=1:cs=400:irs=5000
        -Wc,-Qdepgraph-early_cross_call=1 -Wc,-Qiselect-funcalign=64
        -Wc,-Qpeep-Sh0 -W2,-crit -xprefetch=latx:1.7 -fsimple=1
        -Wc,-Qiselect-sw_pf_tbl_th=30 -Wc,-Qicache-chbab=1
        -W2,-Ainline:inc=300 -ll2amm +FDO
256.bzip2: -fast -xipo=2 -xalias_level=strong -xrestrict
        -Wc,-Qeps:enabled=1,-Qeps:do_spec_load=1 +FDO
300.twolf: -fast -xalias_level=strong -xsafe=mem -xipo=2
        -xprefetch=no%auto -Wc,-Qms_pipe+intdivusefp -xinline= +FDO

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
PASS1:    -xprofile=collect:./feedback
PASS2:    -xprofile=use:./feedback

```

Portability:

```

176.gcc: -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSUN
253.perlbnk: -DSPEC_CPU2000_SOLARIS
254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
        -DSYS_HAS_CALLOC_PROTO

```

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```

For peak run, jobs were bound to cores using the pbind command.

The system was configured with multiple file systems.

The O/S was installed on one disk of the Sun StorageTek D240 Media Tray (ufs, ufs w/logging). The benchmark was run on the Sun StorageTek 6130 Array, using H/W Raid 5 and ufs with



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire E4900 (12 processor)

SPECint\_rate2000 = 296

SPECint\_rate\_base2000 = 269

SPEC license #: 6 Tested by: Sun Microsystems Test date: Jun-2006 Hardware Avail: Aug-2006 Software Avail: Jun-2006

## Notes/Tuning Information (Continued)

ufs logging file system.