CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL460c (2.66 GHz, Intel Xeon processor X5355)

SPECint_rate2000 = 200

SPECint_rate_base2000 = 199

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jan-2007 | Hardware Avail: Jan-2007 | Software Avail: Nov-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	89.4	145	8	89.7	145
175.vpr	8	91.2	143	8	89.9	144
176.gcc	8	57.4	178	8	57.4	178
181.mcf	8	122	137	8	119	140
186.crafty	8	41.3	225	8	41.3	225
197.parser	8	94.9	176	8	94.7	176
252.eon	8	37.7	320	8	37.6	321
253.perlbmk	8	59.8	279	8	59.1	283
254.gap	8	70.0	146	8	69.9	146
255.vortex	8	51.8	340	8	51.5	342
256.bzip2	8	92.7	150	8	92.7	150
300.twolf	8	97.3	286	8	97.3	286

Hardware

CPU:	Intel Xeon processor X5355 (2.66 GHz, 2x4 MB L2 shared, 1333 MHz bus)
CPU MHz:	2666
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1,2 chips
Parallel:	No
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip (4 MB shared per 2 cores)
L3 Cache:	N/A
Other Cache:	N/A
Memory:	16 GB (8x2 GB PC2-5300F CL5)
Disk Subsystem:	2x72 GB 10 K SAS
Other Hardware:	

Software

Operating System:	Windows Server 2003 Enterprise X64 Edition (x86_64) SP1
Compiler:	Intel C++ Compiler for 32-bit applications, (Version 9.1 Build 20061103Z) Microsoft Visual Studio .NET 2003 (v7.1.3088, for libraries) MicroQuill Smartheap Library 8.0
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use

Base tuning for C programs:   -fast         +FDO  ONESTEP=yes shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO  ONESTEP=yes
Portability flags:
  176.gcc: -Dalloca=_alloca /F10000000
  186.crafty: -DNT_i386
  253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
  254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
  164.gzip:     -fast               +FDO  ONESTEP=yes
  175.vpr:      -fast               +FDO  ONESTEP=yes
  176.gcc:      basepeak=1
  181.mcf:      -fast               +FDO
  186.crafty:   -fast -Oa           +FDO  ONESTEP=yes shlw32M.lib
  197.parser:   -fast               +FDO  ONESTEP=yes
  252.eon:      -fast               +FDO
  253.perlbmk:  -fast -Oa           +FDO  ONESTEP=yes shlw32M.lib
  254.gap:      -fast               +FDO  ONESTEP=yes
  255.vortex:   -fast               +FDO  ONESTEP=yes shlw32M.lib
```

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
    256.bzip2:    basepeak=1
    300.twolf:    -fast               +FDO              shlw32M.lib
  BIOS Configuration Notes
    Power Regulator set to Static High
    Adjacent Sector Prefetch disabled
  Other Configuration Notes
    The start /b /wait /affinity command is used to bind CPU(s) to processes.
```