

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Hewlett-Packard Co.: HP Netserver LP 1000r
Microsoft: Microsoft Internet Information Server 5.0

SPECweb99 = 1420

Test Date: Jul-2001
Tester: Hewlett-Packard Company

Hardware Avail: May-2001 OS Avail: Feb-2000 HTTP Software Avail: Feb-2000 Sup. Software Avail: Jan-2000 SPEC license #: 3

Hardware

Vendor: Hewlett-Packard Co.
Model: HP Netserver LP 1000r
Processor: Intel Pentium III/512 at 1.26Ghz
Processors: 2 cores, 2 chips, 1 core/chip
Primary Cache: 16KBI+16KBD on chip
Secondary Cache: 512KB on chip
Other Cache: none
Memory: 4 GB
Disk Subsystem: 3 18GB 15K Ultra3 SCSI
Disk Controllers: Integrated Ultra3 SCSI
Other Hardware: none

Software

Operating System: Windows 2000 Server
File System: NTFS
Other Software: none

HTTP Software

Vendor: Microsoft
HTTP Software: Microsoft Internet Information Server 5.0
API: ISAPI
Server Cache: None
Log Mode: W3C Extended Log File Format

Test Sponsor

Test Date: Jul-2001
Tested By: Hewlett-Packard Company
SPEC License: 3

Network

of Controllers: 1
Network Controllers: Intel Pro/1000F Server Adapter
of Nets: 1
Type of Nets: Gigabit Ethernet
Network Speed: 1 Gb/s
MSL (sec): 30 (Non RFC1122)
Time-Wait (sec): 60 (Non RFC1122)
MTU: 1500

Clients

of Clients: 5
Model: HP Kayak XU
Processor: Intel Pentium II at 550MHZ
of Processors: 2
Memory: 256MB
Network Controller: Alteon
Operating System: Microsoft Windows 2000 Pro
Compiler: Microsoft C++ Version 6

Notes/Tuning Information

SUT Notes

IIS settings: maximum performance.
IIS Home Directory: Access for Read & Write, Scripts & Executables.
IIS Virtual Directory spec99 points back to web server root, low application protection.
IIS Logging: W3C Extended logging, defaults plus bytes sent.

Operating System Notes

Tuning parameters:
TCP/IP Settings in registry:
- Tcpip/Parameters/MaxHashTableSize=0x2000, sets TCB hash table size to 8,192 entries, default is 512.
- Tcpip/Parameters/TcpTimedWaitDelay=0x3c, sets TIME_WAIT parameter to 60 seconds (non-RFC 1122), default is 240.
- Tcpip/Parameters/MaxFreeTwTcbs=400000, sets maximum number of TIME_WAIT tcbs to 400000.
- Tcpip/Parameters/MaxUserPort = 0xffff, sets maximum open ports to 65534.
- Tcpip/Parameters/TcpWindowSize = 17520, sets TCP send/receive window size, default 8192.
- Tcpip/Parameters/NumTcbTablePartitions = 16, sets number of independent TCB table segments, default 4.
IIS Settings in Registry:
- Inetinfo/Parameters/ObjectCacheTTL=0xfffff, sets IIS object cache timeout in seconds, default 10 minutes.
- Inetinfo/Parameters/ListenBacklog=1000, default 25.
- Inetinfo/Parameters/AcceptExTimeout=1, sets time for accept ex socket to wait for receive, default 120.
- Inetinfo/Parameters/MaxPoolThreads=20, maximum network request threads per processor, default 10.
- Inetinfo/Parameters/LogFileFlushInterval=60, forces flush every 60 seconds, default 300.

Intel Pro/1000 NIC settings in registry:
- MaxFrameSIze=1514, default.

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Operating System Notes (Continued)

- NumTxDescriptors=768, Number of buffers available for transmit acceleration, default 128.

HTTP API Notes

Microsoft ISAPI for IIS 5.0 compiled with VC++ 6.0, code optimization = Pentium Pro.

Hardware Notes

One 18GB 15K RPM disk for OS, IIS logs and paging, and 2 striped for web pages.