

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Angstrom Microsystems: Titan 64 Classic 4
Red Hat: Red Hat Content Accelerator 2

SPECweb99 = 9396

Test Date: Mar-2003
Tester: Advanced Micro Devices

Hardware Avail: Jul-2003 OS Avail: Oct-2001 HTTP Software Avail: Jun-2002 Sup. Software Avail: Jun-2002 SPEC license #: 49

Hardware

Vendor: Angstrom Microsystems
Model: Titan 64 Classic 4
Processor: AMD Opteron 842, 1.6 GHz
Processors: 4 cores, 4 chips, 1 core/chip
Primary Cache: 64KBI+64KBD
Secondary Cache: 1MB on chip
Other Cache: none
Memory: 32 GB pc2100 DDR
Disk Subsystem: 3: 15k Ultra320 SCSI
Disk Controllers: Onboard LSI SCSI
Other Hardware: 1 Extreme Summit 7i Gigabit Switch

Software

Operating System: Red Hat Linux 7.2
File System: ext2
Other Software: Intel 4.2.17 driver
LSI mptlinux-2.03.011, RHBA-2002-104

HTTP Software

Vendor: Red Hat
HTTP Software: Red Hat Content Accelerator 2
API: RHCA API
Server Cache: None
Log Mode: Binary CLF

Test Sponsor

Test Date: Mar-2003
Tested By: Advanced Micro Devices
SPEC License: 49

Network

of Controllers: 4
Network Controllers: Intel Pro/1000 MT Dual Port Server Adapter
of Nets: 4
Type of Nets: Gigabit Ethernet
Network Speed: 1 Gb/s
MSL (sec): 30 (Non RFC1122)
Time-Wait (sec): 60 (Non RFC1122)
MTU: 1500

Clients

of Clients: 16
Model: Tyan Tiger/AMD Athlon MP
Processor: AMD Athlon MP 1900+
of Processors: 2
Memory: 512MB
Network Controller: Intel Pro1000 XT
Operating System: Windows 2000 Professional
Compiler: Microsoft Visual C++ 6.0

Notes/Tuning Information

SUT Notes

1 disk for OS, 1 disk for logs, 1disk for web pages.

Operating System Notes

ulimit -n 10000, sets number of open files, default 1024
1 port of each dual port NIC used, one NIC irq bound per CPU.
Each NIC's TX queue length set to 20000 via ifconfig, default 100
File systems mounted with "noatime,nodiratime", no inode access time updating
net.ipv4.nonlocal_bind = 1, allows processes to bind to non-local IP addresses
net.ipv4.tcp_timestamps = 0, turns TCP timestamp support off, default on
net.ipv4.tcp_max_tw_buckets = 2000000, sets TCP time-wait buckets pool size, default 180000
net.ipv4.tcp_rmem = 10000000 10000000 10000000, sets min/default/max TCP read buffer, default 4096 87380 174760
net.ipv4.tcp_wmem = 10000000 10000000 10000000, sets min/pressure/max TCP write buffer, default 4096 16384 131072
net.ipv4.tcp_mem = 10000000 10000000 10000000, sets min/pressure/max TCP buffer space, default 31744 32256 32768
net.ipv4.tcp_sack = 0, turn SACK support off, default on
net.ipv4.tcp_window_scaling = 0, turn TCP window scaling support off, default on
net.core.hot_list_length = 20000, maximum number of skb-heads to be cached, default 128
net.core.rmem_max = 10000000, maximum receive socket buffer size, default 131071
net.core.wmem_max = 10000000, maximum send socket buffer size, default 131071
net.core.rmem_default = 10000000, default receive socket buffer size, default 65535
net.core.wmem_default = 10000000, default send socket buffer size, default 65535
net.core.optmem_max = 10000000, maximum amount of option memory buffers, default 10240
net.core.netdev_max_backlog = 300000, number of unprocessed input packets before kernel starts dropping them, default 300
Kernel Parameters:
idle=poll, idle threads pool reschedule flag, default is to use HLT instruction
acpispmp=force, use ACPI tables for processor information, default MP table

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

HTTP Software Notes

net.tux.logging = 1, turns on logging of requests, default 0
net.tux.cgiroot = /, cgi root check, default /var/www/tux/cgiroot/
net.tux.max_backlog = 3000, maximum per-listening-socket TCP backlog size, default 2048
net.tux.noid = 1, suppress the Server id string, default 0

Client Notes

Clients require a Tyan Tiger motherboard and an ATX capable case.
Case uses 300W ATX power supply, Clients use a 40G ATA 133 IDE hard drive.
Clients use DDR pc2100 memory.

Other Notes

Tuning Disclosure: See above.
Dynamic API: Dell-20020204-RHCA.tar.gz
Kernel config: AMD-20030318-config.tux