

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Hewlett-Packard: hp server rp5470
Zeus Technology Limited: Zeus 4.0r1 64bit

SPECweb99 = 2507

Test Date: Dec-2001
Tester: Hewlett-Packard Company

Hardware Avail: Nov-2001 OS Avail: Dec-2001 HTTP Software Avail: Nov-2001 Sup. Software Avail: Dec-2001 SPEC license #: 3

Hardware

Vendor: Hewlett-Packard
Model: hp server rp5470
Processor: PA-8700 750Mhz
Processors: 2 cores, 2 chips, 1 core/chip
Primary Cache: 768KBI+1512KBD on chip
Secondary Cache: None
Other Cache: None
Memory: 16 GB
Disk Subsystem: See SUT Notes
Disk Controllers: 1xHP A5158A FC Card
Other Hardware: HP VA7100 Disk Array

Software

Operating System: HP-UX 11.11 (64-bit) + patches
File System: HFS - Largefiles
Other Software: None

HTTP Software

Vendor: Zeus Technology Limited
HTTP Software: Zeus 4.0r1 64bit
API: ISAPI
Server Cache: See Zeus parameters
Log Mode: Binary Log Format

Test Sponsor

Test Date: Dec-2001
Tested By: Hewlett-Packard Company
SPEC License: 3

Network

of Controllers: 4
Network Controllers: HP A4926A PCI Gigabit Ethernet
of Nets: 4
Type of Nets: Gigabit Ethernet
Network Speed: 1 Gb/s
MSL (sec): 30 (Non RFC1122)
Time-Wait (sec): 60 (Non RFC1122)
MTU: 1500

Clients

of Clients: 12
Model: HP 9000/A500-5x
Processor: 550Mhz PA-8600
of Processors: 2
Memory: 4 GB
Network Controller: HP A5230A, PCI 100BaseT
Operating System: HPUX 11.0 ACE
Compiler: B3901BA B.11.02.02 HP C/ANSI C

Notes/Tuning Information

SUT Notes

Bound one Zeus instance to processor corresponding to its NIC
Processor binding performed by: mpsched -c cpu# -p pid
15 (18GB 15K rpm) disks (VA7100 disk array) used for file_set
1 (8GB 10K rpm) disk used for logs
1 (32GB 10K rpm) disk used for OS

Operating System Notes

HP-UX 11i Internet Operating Environment with following patches:
PHNE_25084 - Cumulative STREAMS Patch
PHNE_25642 - Cumulative ARPA Transport Patch

HP-UX Tunable Parameters:

dbc_max_pct=81 Max buffer cache size as percent of RAM (50)
dbc_min_pct=81 Min buffer cache size as percent of RAM (5)
maxfiles=60000 Soft file limit per process (60)
maxfiles_lim=60000 Hard file limit per process (1024)
maxssiz_64bit=0x180000000 Max stack size for 64-bit procs (0x00800000)
maxswapchunks=4868 Max number of swap chunks (256)
maxuprc=10000 Max number of user processes (75)
nfile=550000 Max number of open files (790)
ninode=150000 Max number of inodes (444)
nkthread=8000 Max number of kernel threads (499)
nproc=1000 Max number of processes (276)
tcpshasz=16384 Relative scaling factor for TCP&IP int. tables (2048)
vps_ceiling=4096 Max system selected page size [KB] (16)

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Operating System Notes (Continued)

vps_pagesize=64 Default user page size [KB] (4)
maxdsiz_64bit=0x18000000 (0x40000000)
maxssiz=0x1000000 (0x800000)
ncallout=8000 Max number of pending timeouts (515)

HTTP Software Notes

Zeus Global Parameters:

```
tuning!bind_any          no
tuning!cache_cooling_time 0
tuning!cache_files       356750
tuning!cache_flush_interval 86400
tuning!cache_large_file  1000000
tuning!cache_max_bytes   0
tuning!cache_small_file  0
tuning!cache_stat_expire 86400
tuning!cbuff_size        65536
tuning!keepalive_timeout 1200
tuning!keepalive_max     -1
tuning!listen_queue_size 8192
tuning!maxaccept         1024
tuning!modules!cgi!cbuff_size 1048576
tuning!modules!isapi!enabled yes
tuning!sendfile_reservefd 57000
tuning!sendfile_minsize  0
tuning!sendfile_maxsize  1048576
tuning!softservers       no
tuning!so_rbuff_size     0
tuning!so_wbuff_size     1048576
tuning!timeout           600
tuning!unique_bind       yes
tuning!use_poll           no
tuning!multiple_accept   yes
tuning!sendfile           yes
tuning!modules!cgi!cleansize 0
tuning!modules!stats!enabled no
tuning!modules!nsapi!enabled no
tuning!keepalive         yes
```

HTTP API Notes

Zeus ISAPI interface used
Zeus PEPP Toolkit(0.6) used for SPECweb99 dynamic content
./Configure --sendfile=yes --checkconfig=yes --locking=semop

Network Notes

4 HP Procurve 1600M Switches

Network Tunable Parameters:

tcp_xmit_hiwater_def=2000000 Max unsent data triggers flow control (32768)
tcp_conn_request_max=1024 Max outstanding connection reqs (20)

Gigabit Tunable Parameters:

send_max_bufs=32 Number of sending buffers consumed to trigger interrupt (16)
recv_max_bufs=12 Number of receiving buffers consumed to trigger interrupt (16)
recv_coal_ticks=10000 Number of ticks to wait to trigger interrupt (0)

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Client Notes

HP-UX Tunable Parameters:

max_thread_proc=800 Number of threads per process (64)

maxusers=256 Value of MAXUSERS macro (32)

ncallout=5000 Increase number of pending timeouts (515)

nkthread=8000 Maximum number of system-wide threads (499)

Other Notes

Tuning Disclosure: HP-20010917.txt

Dynamic API: HP-20010917-API.tar.gz