

# SPECweb99\_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company: HP ProLiant BL35p  
Zeus Technology Limited: Zeus V4.2r4 (64-bit)

SPECweb99\_SSL =2040

Test Date: Feb-2005  
Tester: Hewlett-Packard Company

Hardware Avail: Feb-2005 OS Avail: Aug-2004 HTTPS Software Avail: Nov-2003 Sup. Software Avail: Nov-2003 SPEC license #: 3

## Hardware

Vendor: Hewlett-Packard Company  
Model: HP ProLiant BL35p  
Processor: AMD Opteron 250, 2.4GHz  
# Processors: 2 cores, 2 chips, 1 core/chip  
Primary Cache: 64KBI+64KBD  
Secondary Cache: 1MB on chip  
Other Cache: none  
Memory: 8 GB (4x2GB PC3200 DDR)  
Disk Subsystem: 2x60GB ATA100  
Disk Controllers: ATA  
Other Hardware: 2xHP BladeSystem interconnect switches

## Software

Operating System: SuSE Linux Enterprise Server 9  
File System: ext2  
Other Software: none

## HTTPS Software

Vendor: Zeus Technology Limited  
HTTPS Software: Zeus V4.2r4 (64-bit)  
API: Zeus PEPP 0.9pre1 ISAPI for dynamic content  
Server Cache: none  
Log Mode: Binary Common Log Format

## Test Sponsor

Test Date: Feb-2005  
Tested By: Hewlett-Packard Company  
SPEC License: 3

## Network

# of Controllers: 2  
Network Controllers: Integrated NC7782  
# of Nets: 2  
Type of Nets: Gigabit Ethernet  
Network Speed: 1 Gb/s  
MSL (sec): 30 (Non RFC1122)  
Time-Wait (sec): 60 (Non RFC1122)  
MTU: 1500

## Clients

# of Clients: 4  
Model: HP ProLiant DL360 G3  
Processor: 3.06GHz 1MB L3 cache Intel Xeon  
# of Processors: 2 cores, 2 chips, 1 core/chip  
Memory: 512MB  
Network Controller: 2xIntegrated NC7781  
Operating System: Windows Server 2003 Std. Edition  
Compiler: Microsoft Visual C++ 6.0

## Notes/Tuning Information

### SUT Notes

1 drive used for OS and log, 1 drive used for workload  
1xHP BladeSystem p-Class enclosure  
1xHP BladeSystem p-Class Power Subsystem

### Operating System Notes

Filesystem mounted with noatime,nodiratime - no inode access time updating, no access control lists  
irq\_balancer disabled  
One NIC irq bound per CPU  
Each NIC's TX queue length set to 40000, default 100  
ulimit -n 72720, sets number of open files, default 1024  
1 &gt; /proc/sys/net/ipv4/conf/all/rp\_filter #enables source route verification, default 0  
0 &gt; /proc/sys/net/ipv4/tcp\_timestamps #turns TCP timestamp support off, default 1  
2000000 &gt; /proc/sys/net/ipv4/tcp\_max\_tw\_buckets #sets TCP time-wait buckets pool size, default 180000  
30000000 30000000 30000000 &gt; /proc/sys/net/ipv4/tcp\_rmem #maximum TCP read-buffer space allocatable, default 4096 87380 174760  
30000000 30000000 30000000 &gt; /proc/sys/net/ipv4/tcp\_wmem #maximum TCP write-buffer space allocatable, default 4096 16384 131072  
30000000 30000000 30000000 &gt; /proc/sys/net/ipv4/tcp\_mem #maximum TCP buffer space allocatable, default 31744 32256 32768  
10000000 &gt; /proc/sys/net/core/rmem\_max #maximum receive socket buffer size, default 65535  
10000000 &gt; /proc/sys/net/core/rmem\_default #default receive socket buffer size, default 65535  
10000000 &gt; /proc/sys/net/core/wmem\_max #maximum send socket buffer size, default 65535  
10000000 &gt; /proc/sys/net/core/wmem\_default #default send socket buffer size, default 65535  
10000000 &gt; /proc/sys/net/core/optmem\_max #default 10240  
291879 &gt; /proc/sys/fs/file-max #maximum number of open files, default 1024

### HTTPS Software Notes

tuning!bind\_any no  
tuning!unique\_bind yes  
tuning!cache\_cooling\_time 0

For more  
Information  
Contact

SPEC

info@spec.org  
http://www.spec.org

# SPECweb99\_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

## Notes/Tuning Information (Continued)

### HTTPS Software Notes (Continued)

tuning!cache\_files 282011  
tuning!cache\_flush\_interval 180000  
tuning!cache\_small\_file 90000  
tuning!cache\_large\_file 1048576  
tuning!cache\_max\_bytes 12884901888  
tuning!cache\_stat\_expire 180000  
tuning!cbuff\_size 65536  
tuning!clientfirst\_optimise yes  
tuning!keepalive yes  
tuning!keepalive\_max -1  
tuning!keepalive\_timeout 3600  
tuning!listen\_queue\_size 8192  
tuning!maxaccept 2048  
tuning!modules!cgi!cleansize 0  
tuning!sendfile no  
tuning!sendfile\_maxsize 0  
tuning!sendfile\_minsize 0  
tuning!so\_wbuff\_size 1048576  
tuning!softservers no  
tuning!ssl\_diskcache no  
tuning!ssl\_sessioncache\_size 6037  
tuning!ssl\_cbuff\_size 32840  
tuning!num\_children 4  
tuning!modules!stats!enabled no  
tuning!modules!nsapi!enabled no  
runninsite/wstest: bindaddr IP address 1 IP address 2

### HTTP API Notes

Dynamic API: HP-20020724-API.tgz  
Zeus PEPP configured with the ./Configure --ssl=yes

### Client Notes

The alternative performance neutral alt.Win32 client was used.  
Tcip\Parameters\MaxUserPort=0xfffe, sets maximum open ports to 65534  
Tcip\Parameters\TcpTimedWaitDelay=60, sets TIME\_WAIT parameter to 60 seconds (non-RFC 1122), default 240  
Tcip\Parameters\MaxFreeTwTcbs\100000, sets maximum number of TIME\_WAIT tcbs to 100,000  
Tcip\Parameters\TcpWindowSize=65535, sets TCP receive window size, default 8192

### Other Notes

Server kernel: default SLES 9 (2.6.5-7.97-smp)